

Sy. No 168/3A, Plot No U-Administrative Building Mangalore Special Economic Zone Bajpe Village, Mangalore taluk Dakshina Kannada (Dist) Karnataka-574142 31 Dec. 2020

MSEZL/MNG/EC/COMP/2019-20

To,

The Director,
Southern Region, Regional Office,
Ministry of Environment and Forests,
Kendriya Sadan, 4th Floor, E&F Wings,
17th Main Road, 1st Block, Koramangala,
Bangalore – 560 034

Sir.

Sub: Six monthly Compliance Report.

Regional Office

Karnataka State Pollution Control Board

Plot No.10-'B'

Baikampady Industrial Ares,
Mangaluru-5750

Ref:

1. Environmental Clearance No: 21-383/2007-IA-III, dated 3rd April 2008.

 Amendment to Environmental Clearance for setting up of Phase-I of Special Economic Zone at Mangalore by M/s Mangalore SEZ Ltd – regarding No: 21-383/2007-IA-III dated 13th July, 2012.

 Amendment to Environmental Clearance for setting up of Phase-I of Special Economic Zone at Mangalore by M/s Mangalore SEZ Ltd date 27 Aug 2014.

4. Amendment to Environmental Clearance for development of Multi Product Units as Mangalore SEZ dated 18 June 2015.

With reference to above, we would like to submit the compliance report as on

date.

S. No.	A. SPECIFIC CONDITIONS	COMPLIANCE
(i)	No Objection Certificate from the Karnataka State Pollution Control Board shall be obtained before initiating the project.	Consent For Establishment from KSPCB obtained on 30 April 2008 and Extension of validity of Consent For Establishment obtained on 27 May 2013 and the copy was submitted to MoEF.
(ii)	The MSEZ project shall be restricted to the Phase- I of the project, proposed over 1,800 acres. The phase II of the project shall be considered by Ministry of Environment and Forests only after	per EIA Notification, 2006 for Phase-

Sy.No 168/3A, Plot No U-1, Administrative Building, Mangalore Special Economic Zone, Bajpe Village, Mangalore taluk, Website: www.mangaloresez.com



		Karnataka-574142
S. No.	A. SPECIFIC CONDITIONS	COMPLIANCE
	receipt of all requisite documents/information as laid down in the Environmental Impact Assessment Notification, 2006 and Coastal Regulation Zone Notification, 1991 as applicable.	
(iii)	All development in the Coastal Regulation Zone area shall be in accordance with the Coastal Regulation Zone Notification, 1991. No destruction of mangroves shall be undertaken except while undertaking the permissible activities in the Coastal Regulation Zone-I areas.	
(iv)	The project proponent shall not take up any activity in 875 acres of Coastal Regulation Zone land, other than those permissible under the Coastal Regulation Zone Notification 1991 such as pipeline corridors, pipelines roads on stilts.	Complied.
(\(\forall \)	With regard to the containing the suspected contamination of the groundwater near Athurkodi area of Kuthethoor village, MRPL have given an undertaking vide their letter dated 19.3.2008 which is as follows: a) Implementation of recommendation of NGPRI will be started by MRPL immediately after submission of their report. b) Depending upon the nature of their recommendations, we will make efforts to complete necessary actions within 6 months from the date of receipt of their report. c) In addition to above, a daily vigil is already in place to take samples from different places and to monitor any suspected oil leakage. This will continue till the problem is resolved. d) We are also in continuous contact with the residents in the surround areas with regard to any contamination. KSPCB and MRPL shall ensure that (a) to (d)	This condition pertains to MRPL phase III expansion project. MRPL phase III expansion has been detached from MSEZ phase I project vide EC amendment dated 13th July 2012, MRPL shall be complying conditions relevant to them as part of their existing clearance.



		Karnataka-574142
S. No.	A. SPECIFIC CONDITIONS	COMPLIANCE
	above is implemented in a time bound manner and a monthly report on the progress of the activities provided to the Regional Office of this Ministry at Bangalore. For this purpose a separate budget would be allocated by MRPL.	
(∨i)	The project proponent shall obtain a report from the Wildlife Department with regard to existence of wildlife in the proposed site as claimed by the public before implementing the project.	Report from the chief conservator of Forest regarding existence of wildlife in the proposed site was submitted to the MoEF dated June 5, 2008.
(∨ ii)	The R&R package shall be strictly in accordance with the laid down norms of the State Government.	1
(√iii)	A marine Environment Impact Assessment and Risk Assessment along with the Disaster Management Plan shall be prepared for the outfall facilities proposed in the Coastal Regulation Zone and the marine areas.	Oceanography, IIT Chennai. The design report was also vetted by



	Karnataka-5/4142	
S. No.	A. SPECIFIC CONDITIONS	COMPLIANCE
		discharge line from KSPCB vide dated 9 Sep 2014, 8 Oct 2015 & 27 Aug 2016.
(ix)	Project proponent shall put up a dedicated website and a display panel to inform the public regarding the Ambient Air Quality along with SO ₂ NOx and other parameters as prescribed as Central Pollution Control Board (CPCB).	MSEZL has dedicated website 'www.msezl.com', wherein Environment Monitoring Parameters are periodically uploaded and made available to the public. Installation and commissioning of Continuous Ambient Air Quality Monitoring station (CAAQMS) has been completed during the month July 2017 and presently data is being transferred to CPCB server continuously. The location of monitoring station is finalized in consultation with KSPCB.
(x)	The gaseous emissions (SO2, NOx, HC, VOC and Benzene) from various process units shall conform to the standards prescribed by the concerned State Pollution Control Board. All the measures detailed in the EMP and response to the Public Hearing shall be taken to control the point/stack and fugitive gaseous emissions from the proposed facilities, processes and storage units etc., for ensuring that the ambient air quality around the Refinery due to the expansion is maintained at the predicted 24 hourly average maximum concentration.	complying the conditions and submitting reports to KSPCB directly. MRPL phase III expansion has been detached from MSEZ phase I project vide EC amendment dated 13th July 2012. MRPL shall be complying conditions relevant to them as part of their existing
(xi)	The emission levels of the other pollutants shall also remain within the permissible levels	Noted.
(xii)	The industrial units in the SEZ and the associated facilities shall be strictly in accordance with the norms laid down by the Karnataka State Government and CPCB.	Noted and will be adhered.
(xiii)	The project proponent shall ensure that the greenery of the area is maintained. Further, 33% of the project area shall be dedicated for green belt development of which at least 5% shall be	Green Belt development in 272 acres out of 272 acres by planting



		Karnataka-5/4/4Z
S. No.	A. SPECIFIC CONDITIONS	COMPLIANCE
	for mangrove afforestation. The local Forest Department shall be associated for this purpose and requisite budget earmarked.	
(xiv)	The project proponent shall ensure that the water requirement of the Mangalore city does not get affected due to the SEZ operation. Adequate provision shall be made in the reservoirs to provide for the water requirement of the cities.	Noted.
(xv)	The project proponent shall ensure that during construction and operation of the project the traffic in the city is not affected.	Complied.
(xvi)	All precautions of the highest standards shall be incorporated in the design of the project to ensure that there is no chance of emission/leakage of hazardous chemicals including Benzene. Detailed monitoring programme shall be designed and the information provided to the public through display and dedicated website by means of online monitoring.	Noted and will be complied.
(xvii)	Low Sulphur internal fuel oil and fuel gas shall be fired in process heaters and boilers.	Noted and will be complied.
(xviii)	Quarterly monitoring of fugitive emissions shall be carried out by Fugitive Emission Detectors (GMI Leak Surveyor). Guidelines of CPCB will be followed for monitoring fugitive emissions. For control of fugitive emissions, all unsaturated hydrocarbons shall be routed to the flare system. The flare system shall be designed for smokeless burning. Flare Gas Recovery System shall be installed for reduction of Hydrocarbon loss and emission of VOCs, NOx, N2O, SOx & CO2 to the environment.	Noted and will be complied.
(xix)	Regular Ambient Air Quality Monitoring shall be carried out. The location and results of existing	Ambient Air Quality Monitoring is being carried out regularly in three



	Karnataka-574	
\$. No.	A. SPECIFIC CONDITIONS	COMPLIANCE
	monitoring stations shall be reviewed in consultation with the concerned State Pollution Control Board based on the occurrence of maximum ground level concentration and downwind direction of wind. Additional Stations shall be set up, if required. It shall be ensured that at least one monitoring station is set up in up-wind & in down-wind direction along with those in other directions.	monitoring are selected in consultation with KSPCB. The
(xx)	On-line data for air emissions shall be transferred to the CPCB and SPCB regularly. The instruments used for ambient air quality monitoring shall be calibrated regularly. The monitoring protocol shall ensure continuous monitoring of all the parameters.	Installation and commissioning of Continuous Ambient Air Quality Monitoring station (CAAQMS) has been completed during the month July 2017 and presently data is being transferred to CPCB server continuously. The location of monitoring station is finalized in consultation with KSPCB.
(xxi)	The practice of acoustic plant design shall be adopted to limit noise exposure for personnel to an 8 hr time weighted average of 90 dB (A).	Noted and will be complied.
(xxii)	All the pumps and other equipment's, where there is a likelihood of HC leakages, shall be provided with appropriate indicators and detectors. Provision for immediate isolation of such equipment, in case of a leakage shall also be made. The company shall adopt Leak Detection And Repair (LDAR) programme for quantification and control of fugitive emissions.	
(xxiii)	The product loading gantry shall be connected to the product sphere in closed circuit through the vapour arm connected to the tanker. Data on fugitive emissions shall be regularly monitored and records shall be maintained	
(xxiv)	The company shall ensure that no halogenated organic is sent to the flares. If any of the halogenated organic are present, then the respective streams may be incinerated, if there are no technically feasible or economically	Noted and will be complied.



	Karnataka-5/4142	
S. No.	A. SPECIFIC CONDITIONS	COMPLIANCE
-	viable reduction/recovery options. Any stream containing organic carbon, other than halogenated shall be connected to proper flaring system, if not to a recovery device or an incinerator.	
(xxv)	The new standards/norms that are being proposed by the CPCB for Petrochemical Plants and Refineries shall be applicable for the proposed expansion unit. The company shall conform to the process vent standards for organic chemicals including non-VOCs and all possible VOCs i.e., TOCs standards and process vent standards for top priority chemicals. Regular monitoring will be carried out for VOC and HC and On-line monitors for VOC measurements may be installed.	The individual units complying the conditions and submitting the
(xxvi)	Regular monitoring of relevant parameters for the underground water in the surrounding areas shall be undertaken and the results shall be submitted to the relevant States Pollution Control Board.	is being carried out in 10 locations
(xxvii)	Solid waste generated as Pretreater and Reformer Catalysts, Sulphur guard absorbent and Alumina Balls shall be disposed off as per the authorization from the State Pollution Control Board.	Individual unit obtaining separate
(xxviii)	Oily sludge shall be sent to melting pit treatment for recovery of oil. The recovered oil shall be recycled into the refinery system. The residual	The individual units complying the conditions and submitting the
(xxix)	The company shall strictly follow all the recommendations mentioned in the Charter on Corporate Responsibility for Environmental Protection (CREP).	Noted and will be complied.
(xxx)	The Company shall harvest surface as well as rainwater from the rooftops of the buildings proposed in the expansion project and storm	Noted and will be complied.



S. No.	A. SPECIFIC CONDITIONS	COMPLIANCE
	water drains to recharge the ground water and use the same water for the various activities of the project to conserve fresh water.	
(xxxi)	Occupational Health Surveillance of the workers should be done on a regular basis and records maintained as per the Factories Act.	
(xxxii)	The Company shall implement all the recommendations made in the Environmental Impact Assessment /EMP report and risk assessment report.	MSEZL has implemented most of the recommendations of EIA/EMP report and still some of the projects of MSEZL as per EIA/EMP recommendations are under way.
(xxxiii)	The company will undertake all relevant measures, as indicated during the Public Hearing for improving the Socio-economic conditions of the surrounding area.	MSEZL is undertaking all relevant measures for improving the Socio-economic condition of the surrounding area as indicated during the Public Hearing.
(xxxiv)	With regard to R&R colony the project proponent shall obtain all requisite clearances as prescribed by the concerned agencies.	The R&R Colonies are developed after obtaining the requisite clearances from the concerned Departments like MoEF, KSPCB, Mangalore Urban Development Authority etc.

S. No	B. GENERAL CONDITIONS	Compliance
(i)	The project authorities shall strictly adhere to the stipulations made by the concerned State Pollution Control Board (SPCB) and the State Government.	Noted and will be complied.
(11)	No further expansion or modifications in the plant shall be carried out without prior approval of the Ministry of Environment and Forests.	MSEZ obtained amendment to EC 1. Dated 13 July 2012 2. 27 Aug 2014, this involves widening of existing public road towards river side adjacent to MSEZ pipeline cum road Corridor in Reach-II area. 3. 18th June 2015 for development of Multi Product



		Karnataka-5/4142
S. No	B. GENERAL CONDITIONS	Compliance
		Units at Mangalore SEZ. Copies of amendments are submitted.
(111)	At no time, the emissions shall be allowed to go beyond the prescribed standards. In the event of failure of any pollution control system adopted by the units, the respective unit should be immediately put out of operation and should not be restarted until the desired efficiency has been achieved.	Noted and will be complied.
(iv)	Adequate number of influent and effluent quality monitoring stations shall be set up in consultation with the SPCB. Regular monitoring shall be carried out for relevant parameters for both surface and ground water.	The treated effluent parameters are measured through online measuring instruments installed at outlet line of Marine outfall pump house for the parameters like pH, DO, COD, TSS, and Conductivity. Further Ground water and surface water monitoring is carried out in the surrounding areas regularly & the reports are attached as Annexure-1. The locations are finalized in consultation with KSPCB.
(v)	Industrial wastewater shall be properly collected and treated so as to conform to the standards prescribed under GSR 422 (E) dated 19th May 1993 and 31st December, 1993 or as amended from time to time. The treated wastewater shall be utilized for plantation purpose.	Noted and will be complied.
(vi)	The overall noise levels in and around the plant area shall be limited within the prescribed standards (85dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels should conform to the standards prescribed under EPA Rules, 1989 viz. 75dBA (day time) and 70dBA (night time).	Noted and will be complied.
(vii)	The project authorities shall strictly comply with the provisions made in Manufacture, Storage	



		Karnataka-574142
S. No	B. GENERAL CONDITIONS	Compliance
	and Import of Hazardous Chemicals Rules 1989 as amended in 2000 for handling of hazardous chemicals etc. Necessary approvals from Chief Controller of Explosives must be obtained before commission of the expansion project. Requisite On-site and Off-site Disaster Management Plans will be prepared and implemented.	MRPL phase III expansion has been detached From MSEZ phase I project vide EC amendment dated 13th July 2012. MRPL shall be complying conditions relevant to them as part of their existing clearance.
(viii)	Authorization from the State Pollution Control Board must be obtained for collections/treatment/storage/ disposal of hazardous wastes.	Noted and will be complied.
(ix)	The project authorities shall provide adequate funds both recurring and non-recurring to implement the conditions stipulated by the Ministry of Environment and Forests as well as the State Government along with the implementation schedule for all the conditions stipulated herein. The funds so provided shall not be diverted for any other purposes.	Noted and will be complied.
(x)	The stipulated conditions shall be monitored by the concerned Regional Office of this Ministry/Central Pollution Control Board/State Pollution Control Board. A six monthly compliance report and the monitored data shall be submitted to them regularly. It shall also be displayed on the Website of the Company.	Compliance report is being submitted to MoEF/KSPCB on regular basis for every six months along with Ambient Air Quality monitoring report, Noise monitoring report & Ground water monitoring report. Compliance report is also displayed in the Company website.
(xi)	The Project Proponent shall inform the public that the project has been accorded environmental clearance by the Ministry and copies of the clearance letter are available with the State Pollution Control Board/ Committee and may also be seen at Website of the Ministry of Environment and Forests at http://www.envfor.nic.in. This should be advertised within seven days from the date of issue of the clearance letter at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular	



S. No	B. GENERAL CONDITIONS	Compliance
	language of the locality concerned and a copy of the same should be forwarded to the concerned Regional office of this Ministry.	
(xii)	The date of Financial Closure and final approval of the project by the concerned authorities and the date of commencing the land development work as well as the commissioning of the project shall be informed to the Ministry and its Regional Office.	MSEZL has taken up the land development & infrastructure works from April 2011. MSEZL Board has approved the Business Plan for Infrastructure Development during Aug. 2012.
(xiii)	Proper Housekeeping and adequate occupational health programmes shall be taken up. Regular Occupational Health Surveillance Programme for the relevant diseases shall be carried out and the records shall be maintained properly for at least 30-40 years. Sufficient preventive measures shall be adopted to avoid direct exposure to emission and other Hydrocarbons etc.	Noted and will be complied.
(xiv)	A separate environment management cell with full fledge laboratory facilities to carry out various management and monitoring functions shall be set up under the control of a Senior Executive.	Sr. General Manager (Environment & Civil) & Sr. Environmental Engineer are in place to take care of Environmental issues. Horticulture Dy. General Manager is appointed for development and maintenance of Green belt.

\$. No	EC Amendment conditions dtd. 13th July 2012	Compliance
(1)	Only the sector Specific shall be permitted in the SEZ & those units shall obtain separate Environmental Clearance as applicable.	MSEZL obtained amendment to EC for development of Multi Product units as Mangalore SEZ dated 18th June 2015.
(ii)	Proponent shall enhance the allocation for the CSR activities from 2.5 to 5 % of the total cost & itemwise details along with time bound action plan shall be prepared & submitted to the Ministry's Regional office at Bangalore. Implementation of such program shall be ensured accordingly in a time bound manner.	MSEZL has already taken up CSR activities as per CSR guidelines.



Sy. No 168/3A, Plot No U-Administrative Building Mangalore Special Economic Zone Bajpe Village, Mangalore taluk Dakshina Kannada (Dist) Karnataka-574142

S. N	EC Amendment conditions dtd. 13th July 2012	Compliance
(iii)	The green belt shall be 33% all along the periphery & width of the green belt shall be minimum 50 mts.	Noted and will be complied.

S. No	EC Amendment conditions dtd. 27th Sep 2014	Compliance
(i)	The project proponent while carrying out the road widening works towards river side should not cause any impact to the river water flow and should be clear of river water way.	Complied.
(ii)	The project proponent to take up the bank protection works like stone pitching etc to avoid soil erosion of the banks.	River bank protection works as directed by WRDO are carried out.
(iii)	The project proponent to take up all adequate measures to mitigate the dust pollution during the road widening works.	Complied.
(iv)	The proponent shall not dump any construction wastes etc in the river portion.	Complied.

With Regards

Eta Sreenivasulu

Sr. General Manager

Mangalore SEZ Ltd.

Encl.:

- 1. Monitoring reports for Air, Water & Noise Environment.
- 2. Environmental compliance report & Environmental Monitoring Reports from OMPL.

Copy to: Environmental Officer, Karnataka State Pollution Control Board, Mangalore.



Sy. No 168/3A, Plot No U-1 Administrative Building Mangalore Special Economic Zone Bajpe Village, Mangalore taluk Dakshina Kannada (Dist) Karnataka-574142 31 Dec. 2020

MSEZL/MNG/R&R/COMP/2019-20

To.

The Director,
Southern Region, Regional Office,
Ministry of Environment and Forests,
Kendriya Sadan, 4th Floor, E&F Wings,
17th Main Road, 1st Block, Koramangala,
Bangalore – 560 034

Regional Office

Karnataka State Pollution Control Board

Plot No.10-'B', Baikampady Industria Mangaluru-575011.

Sir,

(i)

(ii)

Sub: Development of Residential Colony for Rehabilitation and Resettlement for SEZ Complex at Kulai & Thokur village, Mangalore Taluk & District by M/s Mangalore SEZ Limited, Mangalore.

Ref: 1) Environmental Clearance No: SEIAA: 140: CON: 2008, dated 25th June 2008.

With reference to above, we would like to submit the compliance report as on date

A. SPECIFIC CONDITIONS

I. CONSTRUCTION PHASE

Setup an Environment Management cell and ensure that the cell manages/maintains all the environmental aspects such as sewage treatment, solid waste disposal, maintenance of areen belt areas etc, and in case the commercial space is sold/leased, then enter into agreement as per the draft agreement copy submitted, with the prospective buyers to ensure that they maintain the cell and take care of all environment concerns during the operation phase of the project. In addition sufficient fees should be levied so as to raise a corpus fund to maintain the Environment Cell. Appoint an Environment and Safety Engineer

during the construction phase to take care of

environment and safety aspects as committed.

MSEZL Environment Management cell is established to look after the environmental aspects like sewage treatment, Solid waste disposal & Development and maintenance of Green belt etc.

The conditions specified regarding selling or leasing of Commercial space in R&R colony will be complied in case of selling /leasing of land is taken up.

Yes. Sr. Environmental Engineer and Sr. General Manager (Environment & Civil) are in place to take care of



	Karnataka-574142	
		Environmental issues and Safety aspects. Horticulture Dy. General Manager has appointed for development and maintenance of Green belt.
(iii)	All required sanitary and hygienic measures should be in place before starting construction activities and to be maintained throughout the construction phase. Sufficient number of toilets/bathrooms should be provided with required septic tanks and soak pits for construction work force.	Complied.
(iv)	A First Aid Room should be provided in the project both during construction and operation of the project.	A Doctor, clinic and Medical shop is established at 48 acres R&R colony to look after the Project Rehabilitated People. MSEZL has taken up with GoK for setting up Primary Health centre and agreed to provide land for the setting up the same.
(v)	Adequate drinking water and sanitary facilities should be provided for construction workers at the site. The safe disposal of waste water and solid wastes generated during the construction phase should be ensured.	Works are completed.
(vi)	Provision should be made for the supply of fuel (kerosene or cooking gas) utensils such as pressure cookers etc, to the labourers during the construction phase.	Works are completed.
(∨ii)	All the labourers to be engaged for construction should be screened for health and adequately treated before engaging them to work at the site and detailed report submitted to SEIAA. Safety standards as per National Building Code (NBC) should be ensured.	Works are completed.
(viii)	For disinfection of waste water meant for uses other than toilet flushing, use ultra violet radiation and not chlorination. For recirculation of treated waste water for toilet flushing, use chlorination.	Works are completed.
(ix)	All the top soil excavated during construction activities should be stored for use in	Works are completed.



		Karnataka-5/4142
	horticulture/Landscape development within the Project site.	
(x)	Disposal of construction waste during construction phase should not create any adverse effect on the neighbouring communities and be disposed taking the necessary precautions for general safety and health aspects of people, only in approved sites with the approval of competent authority.	Works are completed.
(xi)	Soil and ground water samples should be tested at the project site during the construction phase to ascertain that there is no threat to ground water quality by leaching of heavy metals and or other toxic contaminants and report submitted to SEIAA.	The project is for development of R&R Colony and the scope of works is to develop the graded sites to Project displaced families with water and sanitation facilities. There are no chances of heavy metals or toxic contaminants produced from the activity. However MSEZL has carried out the portability test for water & report has been forwarded.
(xii)	Construction spoils, including bituminous material and other hazardous materials, must not be allowed to contaminate water courses and the dumpsites for such material must be secured, so that they should not leach into the ground water.	Noted. The project is development of R&R Colony and the scope of works is to develop the graded sites to Project displaced families with water and sanitation facilities. There are no chances of construction spoils or Hazardous materials produced from the activity.
(xiii)	The diesel generator sets to be used during construction phase should be of low sulphur diesel type and should conform to Environment (Protection) Rules prescribed for air and noise emission standards.	Noted. No Diesel generators were used during the construction works.
(xiv)	Vehicles hired for bringing construction material to the site should be in good condition and should conform to applicable air and noise emission standards and should be operated only during non-peak hours.	Works are completed.
(xv)	Ambient noise levels should conform to residential standards both during day and night. Incremental pollution loads on the	Works are completed.



		Namataka-J/4142
	ambient air and noise quality should be closely monitored during construction phase. Adequate measures to reduce air and noise pollution during construction keeping in mind CPCB norms on noise limits.	
(xvi)	Fly ash should be used as building material in the construction as per the provisions of Fly Ash Notification of September 1999 and amended as on August 2003	The Project is for development of R&R Colonies with Infrastructure like roads, water & Drainage facilities. There is no requirement of building construction and hence usage of Fly ash does not arise. However in future if MSEZL takes up any building the same will be complied.
(xvii)	Ready mixed concrete must be used in building construction.	The Project is for development of R&R Colonies with Infrastructure like roads, water & Drainage facilities. There is no requirement of building construction and hence usage of Ready mixed concrete does not arise. However in future if MSEZL takes up any building the same will be complied.
(xviii)	Storm water control and its re-use as per CGWB and BIS standards for various applications.	Complied by developing efficient drainage facilities.
(xix)	Water demand during construction should be reduced by use of pre-mixed concrete, curing agents and other best practices.	Complied.
(xx)	The Project Authorities shall not undertake either drawls of Ground water or drilling of bore wells.	Complied.
(xxi)	Separation of grey and black water should be done by the use of dual plumbing line for separation of grey and black water.	Project is development of R&R colonies and there is no scope for MSEZ in plumbing work.
(xxii)	Treatment of 100% grey water by decentralized treatment should be done.	100 cum/day Skid mounted STP is erected already in 48 Acres & 35 Acres colony to treat the grey water.
(xxiii)	Fixtures for showers, tollet flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based	The Project is for development of R&R Colonies with Infrastructure like roads, water & Drainage facilities. There is



	Namataka-574142	
	control.	no requirement for usage of Showers, toilet flushing etc and the condition is not relevant to project implementation.
(xxiv)	Use of glass may be reduced by up to 40% of exposed area to reduce the electricity consumption and load on air conditioning. If necessary, use high quality double glass with special reflective coating in windows.	The Project is for development of R&R Colonies with Infrastructure like roads, water & Drainage facilities. There is no requirement for usage of glass etc and the condition is not relevant to project implementation.
(xxv)	Roof should meet prescriptive requirement as per Energy Conservation Building Code by using appropriate thermal insulation material.	The Project is for development of R&R Colonies with Infrastructure like roads, water & Drainage facilities. There is no requirement for construction of Building roof etc and the condition is not relevant to project implementation.
(xxvi)	Opaque wall should meet prescriptive requirement as per Energy Conservation Building Code which is proposed to be mandatory for all air conditioned spaces while it is optional for non-air conditioned spaces by use of appropriate thermal insulation material to fulfil the requirement.	The Project is for development of R&R Colonies with Infrastructure like roads, water & Drainage facilities. There is no requirement for construction of Building wall or air conditioned spaces etc and the condition is not relevant to project implementation.
II. OP	ERATION PHASE	
(ii)	The installation of the Sewage Treatment Plant (STP) of 16.5 MLD capacity should be carried out before the construction of the second floor of the main structures is commenced and the plant shall be got certified by an independent expert and a report in this regard should be submitted to the SEIAA immediately. Discharge of treated sewage shall conform to the norms & standards of the Karnataka State Pollution Control Board. Treated sewage should be used for flushing, gardening, etc. as proposed.	It was informed to the Assessment Authority by vide our letter dated 22 nd July 2008, that MSEZL has not proposed installation of 16.5 MLD STP, but however the sewage generated in the proposed Colonies will be taken to the existing 16.5 MLD STP by Mangalore City Corporation.
(ii)	Rainwater harvesting for roof run-off with sufficient capacity artificial pond at ground	





7	level for rainwater collection and also surface run-off harvesting should be implemented. Before recharging the surface runoff, pretreatment must be done to remove suspended matter, oil and grease. Detailed rainwater harvesting plan should be submitted	development of plots and hand over to PDF's. The building construction is in the scope of PDF's.
(111)	immediately. Ensure that the excess runoff rainwater from the green belt area, which is irrigated by treated water, does not get into infiltration pits and contaminate the ground water. Such excess flow should be safely let in to the storm water drains.	Complied.
(iv)	The solid waste generated should be properly collected and segregated before disposal to the City Municipality Facility.	Noted. Being complied.
(v)	Any hazardous waste including biomedical waste should be disposed of as per applicable Rules and norms with necessary approvals of the Karnataka State Pollution Control Board.	Noted and will be complied.
(∨i)	As agreed to by the project proponent, develop minimum 13% of the project area i.e., minimum 50 acres area for green belt and plant with tree species at an espacement of 3mts x 3mts i.e. 1,111 plants/hectare. The balance 20% shall be made up by taking up tree planting on the road sides in the project and if required outside the project so as to ensure that 33% of the project area covered under green belt. The green belt design along the Periphery of the plot shall achieve attenuation factor conforming to the day and night noise standards prescribed for residential land use. The open spaces inside the plot should be suitably landscaped and covered with vegetation of indigenous variety.	The final developed area of MSEZL R&R colony is 111.24 Acres. The total green belt development area as per clearance is 36.71 Acres. Presently MSEZL has developed 12.08 acres of green belt inside project area and 24.30 acres of green belt outside the project area. The total green belt developed area by MSEZ is 36.38 Acres and balance 0.33acres will be complete by the end of year 2021.
(∨ii)	Incremental pollution loads on the ambient air quality; noise and water quality should be periodically monitored after commissioning of the project.	Noted





(viii)	Application of Solar energy should be incorporated for illumination of common areas, lighting for gardens and street lighting in addition to provision for solar water heating. A hybrid system or fully solar system for the complex should be provided. Details in this regard should be submitted to the SEIAA.	The Project is for development of R&R Colonies with Infrastructure like roads, water & Drainage facilities. There is no requirement for solar water heating or lighting for gardens and the condition is not relevant to project implementation. The colony will be handed over to Mangalore City Corporation after development & O&M tenure issued. Hence the street lighting with MESCOM connections are provided.	
(ix)	Traffic congestion near the entry and exit points from the roads adjoining the proposed project site must be avoided. Parking must be fully internalized and no public space should be utilized.	Complied.	
(x)	A Report on the energy conservation measures confirming to energy conservation norms finalized by Bureau of Energy Efficiency should be prepared incorporating details about building materials & technology, R&U Factors etc and submit to the SEIAA in three months time.	Colonies with Infrastructure like roads, water & Drainage facilities. There is no requirement for energy consumption equipments or Building	
В.	GENERAL CONDITIONS		
(i)	The Environmental safeguards contained in the EIA Report should be implemented in letter and spirit.		
(ii)	All commitments made by the proponents in their application, and subsequent letters addressed to the SEAC/SEIAA should be accomplished before the construction work of the project is completed.		
(iii)	Six monthly monitoring reports should be submitted to the SEIAA and the Regional Office, MoEF, Bangalore, failing which action may be taken to cancel the Environmental Clearance certificate issued.		
(iv)	Officials from the Department of Ecology and Environment, Bangalore/Regional Office of MoEF, Bangalore/Regional Director	submitted to MoEF/SEIAA were	





		Karnataka-J74142
A CALLANDERS IN THE CALLANDERS	(Environment) Dept. of Ecology and Environment, Mangalore/ Regional Officer, KSPCB Mangalore and KSPCB Bangalore who would be monitoring the implementation of Environmental safe guards should be given full cooperation, facilities and documents/data by the project proponents during their inspection. A complete set of all the documents submitted to MoEF/SEIAA should be forwarded to the CCF, Regional Office of MoEF, Bangalore/Department of Ecology and Environment, Bangalore /Regional Director, (Environment, Mangalore/Regional Officer, KSPCB Mangalore and KSPCB Bangalore.	Conditions. MSEZL will comply in providing the full cooperation to the Monitoring officers.
(v)	In the case of any change(s) in the scope of project, the project would require a fresh appraisal by this Authority.	
(∨i)	The Authority reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environment	Noted.
(∨ii)	All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Fire Department, Civil Aviation Department, Forest Conservation Act 1980 and Wildlife (Protection) Act, 1972 etc shall be obtained, as applicable by project proponents from the competent authorities.	
(viii)	The project proponent should advertise in at least two local Newspapers widely circulated in the region, one of which shall be in vernacular language informing that the project has been accorded environmental clearance and copies of clearance letters are available with the Karnataka State pollution	Noted. The advertisement was made in three local News papers and the copy of the same was forwarded to all concerned as directed.





Sy. No 168/3A, Plot No U-1 Administrative Building Mangalore Special Economic Zone Bajpe Village, Mangalore taluk Dakshina Kannada (Dist) Karnataka-574142

	Control board and may also be seen on the website of the Ecology and Environment Department at http://seiaa.kar.nic.in. The advertisement should be made within 7 days from the day of issue of the clearance letter and a copy of the same should be forwarded to the Regional Office of MoEF at Bangalore/Department of Environment and Ecology, Bangalore.	
(ix)	These stipulations would be enforced among others under the provisions of water (Prevention and Control of Pollution) Act, 1974, The Air (Prevention and Control of Pollution) act 1981, the Environment (Protection) Act, 1986, the Public Liability (Insurance) Act, 1991 and EIA Notification, 2006.	Noted.
(x)	Under the provisions of Environment (Protection) Act, 1986, legal action shall be initiated against the project proponent if it was found that construction of the project has been started without obtaining environmental clearance.	Noted.

The R&R Package is being implemented strictly as per Approved policy by State Government. In 1st PDF 1246 families out of 1253, In 2nd PDF 214 families out of 214, In 3rd PDF 146 families out of 147 families & 14 shops has been compensated with R&R Packages. Totally 1620 families have vacated their houses and the process is in progress for the balance.

10 nos. R&R colonies developed - 1415 sites allotted to eligible Project Displaced Families so far and balance 28 is in the process. 358 nominees of the displaced people given training at Karnataka Polytechnic (KPT) for diploma equivalent programs in Chemical, Mechanical & Electrical disciplines and 347 nominees have already been employed. 1628 nominees would have been eligible for employment out of which 872 nominees have opted for "one time"





Sy. No 168/3A, Plot No U-1 Administrative Building Mangalore Special Economic Zone Bajpe Village, Mangalore taluk Dakshina Kannada (Dist) Karnataka-574142

compensation in lieu of job and balance 756 nominees opted for the jobs. 604 nos. PDF nominees have already got employment out of 756 nos. empanelled. The process of handing over civic communities, parks & roads to local bodies and service to utility provider is under way in different stages.

With Regards

Sr. General Manager

Civil & Environment

Mangalore SEZ Lfd.

Copy to: 1) Environmental Officer, Karnataka State Pollution Control Board, Mangalore.


[7499 2080]



Mangalore SEZ Limited

ENVIRONMENTAL MONITORING REPORT

AMBIENT AIR QUALITY AND MONITORING REPORT FOR THE MONTH OF Oct 2020



Submitted By

Court to water bouter

M/s One Earth Enviro Labs

(NABL Accredited, MOEF&CC Recognized Laboratory)

KSIA Building, 1st Floor, Baikampady Industrial Estate, Mangaluru,

Karnataka – 575011 Email: oneearthenviro@gmail.com

INDEX

DESCRIPTION	Page No.
Introduction - MSEZ	1
Environmental Monitoring	11
	1
Ambient Air Quality Sampling and Analysis	1-8
	9
Ambient Air Quality and Noise level	Test Reports (11 pages)
	Introduction - MSEZ Environmental Monitoring Scope and Methodology Ambient Air Quality Sampling and Analysis MSEZ Environmental Monitoring Schedule

AMBIENT AIR QUALITY MONITORING REPORT - October 2020

1. INTRODUCTION

Mangalore Special Economic Zone, known as MSEZ is spread across 1638 acres, located 15 km from Mangalore city, off Cochin-Mumbai NH 66, 5 km from Mangalore International Airport and 8 km from all-weather deep draft sea port, New Mangalore Port in Mangalore, Karnataka, India. MSEZ limited is jointly promoted by Oil and Natural Gas Corporation (ONGC), a fortune 500 company & infrastructure leasing & finance services, one of India's leading infrastructure development and finance companies, Karnataka Industrial Area Development Board (KIADB) and Kanara Chamber of Commerce and Industry (KCCI). A unique combination of Government entities, a large financial institution and an apex chamber brings in the expertise to develop MSEZL with world-class industrial infrastructure.

2. ENVIRONMENT MONITORING

Environmental monitoring is being carried out at Mangalore SEZ, following guidelines and regulations of MoEF&CC/CPCB and KSPCB statutory norms. In this regard, MSEZL has awarded the work to M/s *OneEarth* Enviro Labs and to monitor air quality, water quality & noise level for the three years. As per work order, during October 2020, we have conducted ambient air quality at 3 locations.

3. SCOPE AND METHODOLOGY

The scope of work carried out and methodology adopted for the survey are described below:

3.1. Ambient Air Quality

Ambient air quality monitoring was carried out at each location on 24 hour basis on two consecutive days in this month. The identified monitoring locations are: 1- WTP, 2- CETP & 3-Permude Area. To assess the ambient air quality status, monitoring stations are identified on the basis of meteorology in the upwind and downwind direction as well as to represent the cross sectional scenario of the MSEZ. Based on the activities the parameters chosen for assessment of air quality are PM2.5-Particulate matter size less than 2.5 Micron, PM10-Particulate matter size less than 10 Micron; SO₂ Sulphur dioxide; NO₂-Nitrogen-di-oxide; CO-Carbon Mono Oxide (DL 0.1 mg/m³); O₃-Ozone (DL 10 μ g/m³); NH₃-Ammonia (DL 5 μ g/m³); Pb-Lead (DL 0.05 μ g/m³); As-Arsenic (DL 0.1 ng/m³); Ni- Nickel (DL 0.5 ng/m³); Benzene-(DL 1 μ g/m³); B(α)P- Benzo- α -pyrene(DL 0.1 ng/m³) as per CPCB stipulation.

3.1.1. Sampling and analysis of PM2.5 and PM10 in ambient air (Gravimetric Method)

- i. Check the filter for any physical damages
- ii. Mark identification number on the filter
- iii. Condition the filter in conditioning room / desiccator for 24 hours
- iv. Record initial weight
- v. Place the filter on the sampler
- vi. Run the sampler for twenty four hours
- vii. Record the flow rate on hourly basis
- viii. Remove the filter from the sampler
- ix. Keep the exposed filter in a proper container
- x. Record the total time of sampling & average flow rate
- xi. Again condition the filter in conditioning room / desiccator for 24 hours
- xii. Record final weight

Laboratory analysis:

Weighing of exposed samples:

Calculate the concentration of PM10 or PM2.5 in µg/m3

Calculations:

- i. Average flow rate (initial and final flow rates) in L/ min
 - = (Initial flow rate + final flow rate)/2
- ii. Total vol. of air sampled (TVA) in m^3
 - = Avg. flow rate $(L/min) * 10^{-3} (m^3/L) *$ sampling time (hr) * 60 (min/hr)
- iii. Concentration of PM in $\mu g/m^3$
 - = $(w_i w_i)$ (mg)/TVA (m³) * $10^6 \mu g/m^3$ where w_i = initial & w_i =final weight of the filter paper

3.1.2. Sampling and analysis of Sulphur dioxide

- i. Place 30 ml of absorbing media in an impinger
- ii. Connect it to the gas-sampling manifold of gas sampling device (RDS/ HVS).
- iii. Draw air at a sampling rate of 1 lpm (litre per minute) for four hours
- iv. Check the volume of sample at the end of sampling and record it
- v. Transfer the exposed samples in storage bottle and preserve
- vi. Prepare calibration graph as recommended in method
- vii. Take 10/20 ml. aliquot of sample in 25 ml. Vol. Flask
- viii. Take 10/20 ml. of unexposed sample in 25 ml. Vol. Flask (blank)
- ix. Add 1 ml Sulphamic acid. Keep it 10 minutes
- x. Add 2 ml formaldehyde
- xi. Add 2 ml working PRA
- xii. Make up to mark (25 ml.) with distilled water.

- xiii. Keep it 30 minutes for reaction
- xiv. Set Zero of spectrophotometer with Distilled water
- xv. Measure absorbance at 560 nm
- xvi. Calculate concentration using calibration graph
- xvii. Calculate concentration of Sulphur Dioxide in µg/m³

3.1.3. Sampling and analysis of Nitrogen-di-oxide

- i. Place 30 ml of absorbing media in an impinger
- ii. Connect it to the gas sampling manifold of gas sampling device (RDS/HVS).
- iii. Draw air at a sampling rate of 1 lpm for four hours
- iv. Check the volume of sample at the end of sampling and record it
- v. Transfer the exposed samples in storage bottle and preserve
- vi. Prepare calibration graph as recommended in method
- vii. Take 10 ml. aliquot of sample in 50 ml. Vol. Flask
- viii. Take 10 ml. of unexposed sample in 50 ml. Vol. Flask (blank)
- ix. Add 1 ml hydrogen peroxide
- x. Add 10 ml sulphanilamide
- xi. Add 1.4 ml NEDA
- xii. Make up to mark (50 ml.) with distilled water.
- xiii. Keep it 10 minutes for reaction
- xiv. Set Zero of spectrophotometer with Distilled water
- xv. Measure absorbance at 540 nm
- xvi. Calculate concentration using calibration graph
- xvii. Calculate concentration of Nitrogen Dioxide in µg/m³

3.1.4. Sampling and analysis of Carbon Mono Oxide

Using Gas analyzer or by Gas detector tube or by portable GAS Detector calibrated against NIST Certified Gas cylinders of known concentration.

Gas Analyzer

Preparation of sample train:

- i. Sampling begins with conditioning a sampling train and then gas analyzer
- ii. Pressure system is preferred to condition the sampling train by installing pump before the analyzer. Reducing valve needs to be fitted between the analyser and pump to eliminate the pulsing effect of pump on the analyzer
- III. Flow meter is to be installed just before the analyzer
- iv. A fibre filter is used to capture the particulate matter prior to the optical cell to prevent its interference. As it often accumulates on the optical cell reducing the efficiency
- v. To eliminate the interference of water vapour, refrigeration or desiccant with magnesium perchlorate could be used

Mode of operation:

- i. Continuous analysis is carried out at the flow rate of about 100 ml/min to 1000 ml/min (depending upon the level of pollution near the location) for the desired sampling period
- ii. Discrete sampling could also be possible with infra red analyzer. It however requires proper cleaning of the sampling train.

Gas detector tube

Mode of operation:

- 1. At the flow rate of about 100 ml/min using hand held pump draw 250ml of air sample into the tube.
- 2. Based on colour indicator, concentration of CO is determined.

Steps:

- i. Calibration of Gas Tube detector can be carried out using NIST Certified CO gas of known concentration
- ii. Sampler is allowed to warm up for some time before drawing the sample and temperature stability

Portable CO GAS Detector

Mode of operation:

- 1. Switch on the CO GAS meter and wait for some time for meter to get adjusted to the environmental conditions
- 2. Once steady CO Concentration is displayed note down the display.

Steps:

- i. Calibration of Gas detector meter to be carried out using NIST Certified CO gas of known concentration
- ii. Sampler is allowed to warm up for some time before drawing the sample and temperature stability

3.1.5 Sampling and analysis of Ozone

- i. Place10 ml of absorbing media in an impinger
- ii. Connect it to the gas sampling manifold of gas sampling device (RDS/HVS).
- iii. Draw air at a sampling rate of 1 lpm for 60 minutes
- iv. Do not expose the absorbing reagent to direct sunlight
- v. Add de ionized water to make up the evaporation loss during sampling and bring the volume to 10 ml
- vi. Prepare calibration graph as recommended in method
- vii. Within 30 to 60 minutes after sample collection, read the absorbance in a cuvette at352 nm against a reference cuvette containing de ionized water
- viii. Calculate concentration using calibration graph
- ix. Calculate concentration of Ozone in μg/m³

3.1.6 Sampling and analysis of Ammonia

- i. Dilute 10ml of concentrated HCl (12 M) to 100 ml with distilled water. Wash the glassware with the water and finally rinse it thrice with distilled water
- ii. Adjust the Flow rate at 1L/min of the rotameter and the manifolds of the attached APM 411/APM 460 Dx

- iii. Place 10 ml of absorbing media in each midget impinger for samples and field blanks. Assemble (in order) prefilter & holder, flow meter, impinger and pump. Sample at the rate of 1L/min for 1 hour duration
- iv. Record the sampling time, average flow rate and final volume of the solution. After the sample collection, transfer the solution in the impinger to polyethylene bottle and recap it tightly for transport to laboratory for analysis
- v. Prepare the absorbing media, various reagents and working solutions as per the method described in protocol. Standardize the sodium thiosulphate solution by titrating it against potassium iodate and Sodium hypochlorite by titrating it against standardized sodium thiosulphate solution
- vi. Take 25 ml measuring flasks and rinse with distilled water. Transfer the contents from polyethylene bottles to 25 ml measuring flasks (Maintain all the solutions at 25°C). Add 2 ml of buffer (to maintain pH). Add 5 ml of working phenol solution, mix, fill to about 22 ml with distilled water and then add 2.5 ml of working hypochlorite solution & mix rapidly. Store in the dark for 30 mins to develop colour. Measure the absorbance of the solution at 630 nm using UV Spectrophotometer
- vii. Pipette 0.5, 1.0 and 1.5 ml of working standard solution (working ammonia solution) in 25 ml measuring flasks. Fill to 10 ml mark with absorbing solution (0.1 M H₂SO₄). Add the reagents as to each flask as in the procedure for analysis. Read the absorbance of each standard against the reagent blank.
- viii. Plot the calibration curve
 - ix. Calculate the concentration of NH₃ in µg/m³

3.1.7. Sampling and analysis of Lead, Nickel, Arsenic:

1. Sampling procedure:

Tilt back the inlet and secure it according to manufacturer's instructions. Loosen the face-plate wing-nuts and remove the face plate. Remove the filter from its jacket and centre it on the support screen with the rough side of the filter facing upwards. Replace the face-plate and tighten the wing-nuts to secure the rubber gasket against the filter edge. Gently lower the inlet. For automatically flow-controlled units, record the designated flow rate on the data sheet. Record the reading of the elapsed time meter. The specified length of sampling is commonly 8 hours or 24 hours. During this period, several reading (hourly) of flow rate should be taken. After the required time of sampling, record the flow meter reading and take out the filter media from the sampler and put in a container or envelope

2. Analysis:

Hot plate procedure:

Cut a 1" x 8" strip or half the filter from the 8" x 10" filter using a stainless steel pizza cutter. Place the filter in a beaker using vinyl gloves or plastic forceps. Cover the filter with the extraction solution (3% HNO $_3$ & 8% HCl). Place beaker on the hotplate, contained in a fume hood, and reflux gently while covered with a watch glass for 30 min. Do not allow sample to dry. Remove the beakers from the hot-plate and allow to cool. Rinse the beaker walls and wash with distilled water. Add approximately 10 mi. reagent water to the remaining filter material in the beaker and allow to stand for at least 30 min. Transfer the extraction fluid in the beaker to a 100 mL volumetric flask or other graduated vessel. Rinse the beaker and any remaining solid material with distilled water and add the rinses to the flask. Dilute to the mark with distilled water (Type I) water and shake. The final extraction solution concentration is 3 % HNO $_3$ / 8% HCl. The filtered sample is now ready for analysis

2.1. Analysis of samples:

i. Instrument / Equipment:

A light beam containing the corresponding wavelength of the energy required to raise the atoms of the analyte from the ground state to the excited state is directed through the flame or furnace. This wavelength is observed by a monochromator and a detector that measure the amount of light absorbed by the element, hence the number of atoms in the ground state in the flame or furnace. A hollow cathode lamp for the element being determined provides a source of that metal's particular absorption wavelength. The method describes both flame atomic absorption (FAA) spectroscopy and graphite furnace atomic absorption (GFAA) spectroscopy. Atomic Absorption Spectrophotometer - analyze the metals by Flame; if results are below detection limit then go for GTA. Arsenic is analyzed by Flame - VGA.

ii. Flame Procedure:

Set the atomic absorption spectrophotometer for the standard condition as follows: choose the correct hollow cathode lamp, align the instrument, position the monochromator at the value recommended by the manufacturer, select the proper monochromator slit width, set the light source current, ignite the flame, regulate the flow of fuel and oxidant, adjust the burner for maximum absorption and stability and balance the meter. Run a series of standards of the metal of interest and construct a calibration curve. Aspirate the blanks and samples. Dilute samples that exceed the calibration range. For Lead (Pb) and Nickel (Ni), the wavelength required for analysis is 217 nm and 232 nm respectively. Where as in case of Arsenic (As), the VGA should attach with Flame and the wavelength required for analysis is 193.7nm.

3. Calibration:

Prepare standard solutions from the stock solutions. Select at least three standards to cover linear range as recommended by method. Aspirate the standards into the flame or inject the standards into the furnace and record the absorbance. Prepare the calibration graph by plotting absorbance and concentration in $\mu g/ml$.

i. Preparation of Standards:

For each metal that is to be determined, standards of known concentration must be acquired commercially certified standards.

ii. Standard Curve:

Standard curve is prepared by using standard solutions of known concentration.

4. Calculations:

i. Sample Air Volume:

Sample air volume can be calculated by using the following equation:

V = (Q)(t)

Where,

V = volume of air, m³

Q = average sampling rate, m3/min.

t = time in minutes.

ii. Metal Concentration:

 $C = (Ms - Mb) \times Vs \times Fa/V \times Ft$

Where,

C = concentration, µg metal/m³

 $Ms = metal concentration \mu g/mL$

Mb = blank concentration µg/mL

Vs = total volume of extraction in mL

Fa = total area of exposed filter in cm²

V = Volume of air sampled in m³

Ft = Area of filter taken for digestion in cm^2

3.1.8. Sampling and analysis of Benzo- α -pyrene:

Benzo (a) Pyrene (BaP) is one of the most important constituent of PAH compounds and also one of the most potent carcinogens. This can be measured in both particulate phase and vapour phase. In the vapour phase the concentration of B(a)P is significantly less than the particulate phase. Therefore, more care to be taken for the measurement of Benzo (a) Pyrene in the particulate phase. The molecular formula of B(a)P is C_2OH_{12} having molecular weight of 252.

It is based on BiS method IS 5182 (Part 12):2004 and USEPA method (TO-13). This method is designed to collect particulate phase PAHs in ambient air and fugitive emissions and to determine individual PAH compounds using capillary gas chromatograph equipped with flame ionization detector. It is a high volume (1.2m³/min) sampling method capable of detecting sub.ng/m³ concentration of PAH in 24 hours sample (i.e. collected in 3 shifts of 8 hour each with 480 m³ sampling volume of air).

i. Sampling:

i. Instrument/Filter Selection:

24 hr. sampling using PM₁₀ high volume sampler with 8 hourly samples using EPM-2000 glass fibre or equivalent filter

ii. Sample Analysis

a. Extraction:

Filter papers (half of all the filters papers collected in a day) are cut into strips using scissors and transfer to 250 ml beaker. Add ~50 ml, of Toluene (GC/HPLC grade). These samples are extracted with toluene using ultra sonic sample can be extracted using Soxhlet bath for about 30 minutes. Repeat the procedure twice (50ml x 2 times) for complete extraction. Alternatively, extraction apparatus for about 8 hr. with Toluene and repeat it twice.

b. Filtration:

Filter the extracted samples with Whatman filter paper No.41 containing 2 gm of Anhydrous Sodium Sulphate (to remove moisture).

c. Concentration:

After filtration, the filtrate is concentrated using Rotary vacuum evaporator to 2ml final volume.

d. Clean-up with silica Gel:

To clean up the impurities, pass 2 ml of concentrated sample through silica gel column (pre conditioned, 60-80 mesh, and 200-250mm×10 mm with Teflon stopcock). After cleaning add 5ml cyclohexane and collect the elute in 25 ml beaker. Repeat the process for at least 3 times and collect it in the same beaker. Alternatively Solid Phase Extraction (SPE) could be used for clean up the impurities of sample.

e. Re-concentration with rotary vacuum evaporator:

The Cleaned up extract/filtrate (approximately 17 ml) is further concentrated using rotary evaporator and it is evaporated to nearly dryness with Nitrogen.

f. Final Sample volume:

The dried sample is re-dissolved in 1ml of toluene and transfer into 4 or 5 ml amber vials final analysis.

ii. Calculations:

Calculate the concentration in $ng/\mu L$ of each identified analyte or B(a)P in the sample extract (Cs) as follows: Calculate the air volume from the periodic flow reading taken during sampling using the following equation: $V = Q \times T$

Where.

Q =Average flow rate of sampling m³/min

T = sampling time, in min.

V = total sample volume at ambient conditions in m³

Concentration of analyte i.e B(a)P:

The concentration of PAH compound or Benzo(a)pyrene in ng/m³ in the air sampled is given by:

C (ng/m3) = Cs * Ve / Vi *Vs

Where,

Cs: Concentration of Benzo (a) pyrene in ng / μL in the sample extract recorded by GC.

Ve : Final volume of extract in μL (i.e 1000)

Vi : Injection Volume (i.e 1µL) Vs : Volume of air sample in m³



4. MONITORING SCHEDULE OF MANGALORE SEZ LIMITED ENVIRONMENTAL MONITORING

Sl.No	Environmental Attributes monitored	Parameters analyzed and presented in analysis Report	Monitoring requirement
1	Ambient Air Quality	PM2.5, PM10, SO ₂ , NO ₂ , CO, O ₃ , NH ₃ , Pb, As, Ni, Benzene, B(α)P	3 Locations/Month, 24 hrs/day consecutive 2 days
2	Surface/ Ground Water Quality	Colour, pH (at 25 °C), Odour, Taste, Turbidity, Total Dissolved Solids, Alkalinity as CaCO ₃ , Total Hardness, Calcium as Ca, Magnesium as Mg, Iron as Fe, Sulphate as SO ₄ , Chloride as Cl, Boron as B, Residual free chlorine, Fluoride, Phenolic Compounds, Manganese as Mn, Zinc as Zn, Arsenic as As, Cyanide as CN, Cadmium as Cd, Chromium as Cr, Aluminium as Al, Selenium as Se, Lead as Pb, Mercury as Hg, Nitrate Nitrogen NO ₃ , E.Coli	Ten Locations, Season wise (Summer, Winter, Post monsoon), By using grab sampling technique
3	Ambient Noise Level	Noise Level (dB) in Day and Night	Two Locations, two non consecutive days per week, for two weeks and Season wise (Summer, Winter, Post monsoon)

@

One Earth Enviro Labs

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph: 0824-240 9011 Mob: +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No. A/2020/0288 Report Date: 30/10/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name Address M/s Mangalore SEZ Limited

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Ambient Air Quality Monitoring for 24 Hrs

Sample Collected By

OneEarth Enviro Labs

Sampling Location

C ETP

71.20

Date of Sampling

20/10/2020 to 21/10/2020

Analysis Start Date

20/10/2020

Date of Sample Receipt

20/10/2020,21/10/2020

Analysis End Date

30/10/2020

Sampling Details

Humidity %

Temp °C

31°C

Pressure mmHg

756.89

Date & Time	20/10/2020 1000 A 288	NAAQ STD	Protocol
Location			
Parameters	Result (µg/m³)		
Respirable Particulate Matter PM2.5	23.04	60	IS 5182 : Part 24
	64.97	100	IS 5182 : Part 23
	BDL	500	IS 5182 : Part 4
	BDL	80	IS 5182 : Part 2
	BDL	80	IS 5182 : Part 6
	30.72	180	IS 5182 : Part 9
-	BDL	400	IS 5182 : Part 25
	1.24	4	Gas Detector
·	ND	1	IS 5182 : Part 22
	ND	6	CPCB Guidelines
· · · · · · · · · · · · · · · · · · ·	ND	20	IS 5182 : Part 26
, - ,		5	IS 5182 : Part 11
	ND	1	IS 5182 : Part 12
	Location	LocationA 288ParametersResult (μg/m³)Respirable Particulate Matter PM2.523.04Respirable Particulate Matter PM1064.97SPMBDLSulphur Dioxide SO₂BDLNitrogen Dioxide NO₂BDLOzone O₃30.72Ammonia NH₃BDLCarbon Monoxide CO (mg/m³)1.24Lead PbNDArsenic As (ng/m3)NDNickel Ni (ng/m3)NDBenzene C6H6ND	Location A 288 NAAQ STD Parameters Result (μg/m³) Respirable Particulate Matter PM2.5 23.04 60 Respirable Particulate Matter PM10 64.97 100 SPM BDL 500 Sulphur Dioxide SO₂ BDL 80 Nitrogen Dioxide NO₂ BDL 80 Ozone O₃ 30.72 180 Ammonia NH₃ BDL 400 Carbon Monoxide CO (mg/m³) 1.24 4 Lead Pb ND 1 Arsenic As (ng/m3) ND 6 Nickel Ni (ng/m3) ND 20 Benzene C6H6 ND 5

BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit BDL for SO₂ - 4 µg/m³ & NO₂ - 9.4µg/m³ μ-micro n-nano g-gram

Opinion .

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t

above tested parameters.

End of the Report ***

Bith En

240801

For One Earth Enviro Labs

Authorized Signatory

(Murlidhar S M, Quality Manager) Seno . 5150

Note: 1.The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after fifteen days from the date of issue of test reports unless otherwise specified. Perishable samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only, 5. Total liability of our lab is limited to the invoice amount only, 6. Conformity statement might be affected due to measurement uncertainty.

One Earth Enviro Labs

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph: 0824-240 9011 Mob: +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: A/2020/0289 Report Date: 30/10/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name

M/s Mangalore SEZ Limited

Address

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

Sampling Location

WTP

71.20

Date of Sampling

Humidity %

20/10/2020 to 21/10/2020

Analysis Start Date

Pressure mmHg

20/10/2020

Date of Sample Receipt

20/10/2020,21/10/2020

Temp °C

Analysis End Date

30/10/2020

Sampling Details

Ambient Air Quality Monitoring for 24 Hrs

31°C

756.89

SI. No	Date & Time	20/10/2020 1030	NAAQ STD	Protocol
	Location Parameters	289 Result (µg/m³)		
1	Respirable Particulate Matter PM2.5	14.00	60	IS 5182 : Part 24
2	Respirable Particulate Matter PM10	44.91	100	IS 5182 : Part 23
3	SPM	10.98	500	IS 5182 : Part 4
4	Sulphur Dioxide SO ₂	BDL	80	IS 5182 : Part 2
5	Nitrogen Dioxide NO ₂	BDL	80	IS 5182 : Part 6
6	Ozone O ₃	36.57	180	IS 5182 : Part 9
7	Ammonia NH₃	BDL	400	IS 5182 : Part 25
8	Carbon Monoxide CO (mg/m³)	ND	4	Gas Detector
9	Lead Pb	ND	1	IS 5182 : Part 22
10	Arsenic As (ng/m3)	ND	6	CPCB Guidelines
11	Nickel Ni (ng/m3)	ND	20	IS 5182 : Part 26
12	Benzene C6H6	ND	5	IS 5182 : Part 11
13	Benzo (a) pyrine BaP (ng/m3)	ND	1	IS 5182 : Part 12

BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit BDL for SO₂ - 4 µg/m³ & NO₂ - 9.4µg/m³ u-micro n-nano g-gram

Opinion

As per Standards mentioned in the report. Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

*** End of the Report ***

For OneEarth Enviro Labs

Authorized Signatory

(Murlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, Earnest be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after fifteen days from the date of issue of test reports unless otherwise specified. Perishable samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only. 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

PHONE

2400611

One Earth Enviro Labs

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph: 0824-240 9011 Mob: +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: A/2020/0290 Report Date: 30/10/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name Address M/s Mangalore SEZ Limited

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

Sampling Location

Permude Church

20/10/2020 to 21/10/2020 Date of Sampling

71.20

Analysis Start Date

20/10/2020

Date of Sample Receipt

20/10/2020,21/10/2020

Temp °C

Analysis End Date

30/10/2020

Sampling Details

Humidity %

Ambient Air Quality Monitoring for 24 Hrs

31°C

Pressure mmHg

756.89

Date & Time	20/10/2020 1430	NAAQ STD	Protocol
Location	A 290		
Parameters			
Respirable Particulate Matter PM2.5	36.49	60	IS 5182 : Part 24
	64.66	100	IS 5182 : Part 23
-	6.93	500	IS 5182 : Part 4
- ,	BDL	80	IS 5182 : Part 2
	BDL	80	IS 5182 : Part 6
	45.35	180	iS 5182 : Part 9
	BDL	400	IS 5182 : Part 25
	ND	4	Gas Detector
	ND	1	IS 5182 : Part 22
	ND	6	CPCB Guidelines
	ND	. 20	IS 5182 : Part 26
	ND	5	IS 5182 : Part 11
	ND	1	IS 5182 : Part 12
		Location ParametersA 290 Result (μg/m³)Respirable Particulate Matter PM2.536.49Respirable Particulate Matter PM1064.66SPM6.93Sulphur Dioxide SO2BDLNitrogen Dioxide NO2BDLOzone O345.35Ammonia NH3BDLCarbon Monoxide CO (mg/m³)NDLead PbNDArsenic As (ng/m3)NDNickel Ni (ng/m3)NDBenzene C6H6ND	Location A 290 STD Parameters Result (μg/m³) Respirable Particulate Matter PM2.5 36.49 60 Respirable Particulate Matter PM10 64.66 100 SPM 6.93 500 Sulphur Dioxide SO₂ BDL 80 Nitrogen Dioxide NO₂ BDL 80 Ozone O₃ 45.35 180 Ammonia NH₃ BDL 400 Carbon Monoxide CO (mg/m³) ND 4 Lead Pb ND 1 Arsenic As (ng/m3) ND 6 Nickel Ni (ng/m3) ND 20 Benzene C6H6 ND 5

BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit BDL for SO₂ - 4 µg/m² & NO₂ - 9.4µg/m³ µ-micro n-nano g-gram

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t

above tested parameters.

*** End of the Report *** aith Eng

For QueEarth Enviro Labs

Authorized Signatory

(Murlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after fifteen days from the date of Issue of test reports unless otherwise specified. Perishable samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only. 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

2408011

2/uru . 513

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: A/2020/0293 Report Date: 30/10/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name

M/s Mangalore SEZ Limited

Address

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

Sampling Location

C ETP

Date of Sampling

21/10/2020 to 22/10/2020

Analysis Start Date

21/10/2020

Date of Sample Receipt

21/10/2020,22/10/2020

Analysis End Date

30/10/2020

Sampling Details

Ambient Air Quality Monitoring for 24 Hrs

Humidity %

69.20

Temp ⁰C

31°C

Pressure mmHg

756.96

- '- ' - '-	Date & Time	21/10/2020 1030	NAAQ	
SI. No	Location Parameters	293 Result (µg/m³)	STD	Protocol
- 1	Respirable Particulate Matter PM2.5	11.50	60	IS 5182 : Part 24
. '	Respirable Particulate Matter PM10	66.44	100	IS 5182 : Part 23
3	SPM	14.42	500	IS 5182 : Part 4
	Sulphur Dioxide SO₂	BDL	80	IS 5182 : Part 2
4	the state of the s	BDL	80	IS 5182 : Part 6
5	Nitrogen Dioxide NO ₂	ND	180	IS 5182 : Part 9
6	Ozone O ₃	ND	400	iS 5182 : Part 25
7	Ammonia NH ₃	ND	4	Gas Detector
8	Carbon Monoxide CO (mg/m³)	ND	1	IS 5182 : Part 22
9	Lead Pb	ND	6	CPCB Guidelines
10	Arsenic As (ng/m3)	,		IS 5182 : Part 26
11	Nickel Ni (ng/m3)	ND	20	
12	Benzene C6H6	ND	<u>5</u>	IS 5182 : Part 11
_13	Benzo (a) pyrine BaP (ng/m3)	ND DOLLAR DOLLAR	1 1	IS 5182 : Part 12

BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit BDL for SO₂ - 4 µg/m³ & NO₂ - 9.4µg/m² µ-micro п-nano g-gram

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t

above tested parameters.

** End of the Report ***

₹ONE

or *OneEarth* Enviro Labs

Authorized Signatory

Wurlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after lifteen days from the date of issue of test reports unless otherwise specified. Perishable samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only. 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED Report No: A/2020/0294

Report Date: 30/10/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name

M/s Mangalore SEZ Limited

Address

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

Sampling Location

WTP

69.20

Date of Sampling

21/10/2020 to 22/10/2020

Analysis Start Date

21/10/2020

Date of Sample Receipt

21/10/2020,22/10/2020

Temp °C

Analysis End Date

30/10/2020

Sampling Details

Humidity %

Ambient Air Quality Monitoring for 24 Hrs.

31°C

Pressure mmHq

756.96

	Date & Time	21/10/2020 1100	NAAQ	
SI. No	Location	294		Protocol
	Parameters	Result (µg/m³)	STD :	
1	Respirable Particulate Matter PM2.5	10.08	60	IS 5182 : Part 24
2	Respirable Particulate Matter PM10	22.21	100	IS 5182 : Part 23
3	SPM	6.26	500	IS 5182 : Part 4
4	Sulphur Dioxide SO₂	BDL	80	IS 5182 : Part 2
5	Nitrogen Dioxide NO₂	BDL	80	IS 5182 : Part 6
6	Ozone O ₃	ND	180	IS 5182 : Part 9
7	Ammonia NH ₃	ND	400	IS 5182 : Part 25
8	Carbon Monoxide CO (mg/m³)	ND	4	Gas Detector
9	Lead Pb	ND	1	IS 5182 : Part 22
10	Arsenic As (ng/m3)	ND	6	CPCB Guidelines
11	Nickel Ni (ng/m3)	ND	20	IS 5182 : Part 26
12	Benzene C6H6	ND	5	IS 5182 : Part 11
13	Benzo (a) pyrine BaP (ng/m3)	ND	1	IS 5182 ; Part 12

BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit BDL for SO₂ - 4 µg/m³ & NO₂ - 9.4µg/m³ µ-micro n-nano g-gram

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t

above tested parameters.

End_of the Report ***

PHONE 2409011 For *OneEarth* Enviro Labs

Wurlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after fifteen days from the date of issue of test reports unless otherwise specified. Perishable samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only. 5. Total liability of our lab is limited to the involce amount only. 6. Conformity statement might be affected due to measurement uncertainty.

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph; 0824-240 9011 Mob; +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: A/2020/0295 Report Date: 30/10/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name

M/s Mangalore SEZ Limited

Address

Survey No 168/3A | Plot No U-1, Administrative Building , MSEZ, Baipe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

Sampling Location Date of Sampling

Permude Church

Analysis Start Date

21/10/2020

Date of Sample Receipt

21/10/2020 to 22/10/2020 21/10/2020.22/10/2020

Analysis End Date

30/10/2020

Sampling Details

Ambient Air Quality Monitoring for 24 Hrs

Humidity %

69.20

Temp ºC

31°C

Pressure mmHg

756.96

	Date & Time	21/10/2020 1500	NAAQ		
Si. No	Location Parameters	295 Result (µg/m³)		Protocol	
1	Respirable Particulate Matter PM2.5	36.28	60	IS 5182 : Part 24	
2	Respirable Particulate Matter PM10	58.89	100	IS 5182 : Part 23	
3	SPM	6.73	500	IS 5182 : Part 4	
4	Sulphur Dioxide SO ₂	BDL	80	IS 5182 : Part 2	
5	Nitrogen Dioxide NO ₂	BDL	80	IS 5182 : Part 6	
6	Ozone O ₃	· ND	180	IS 5182 : Part 9	
7	Ammonia NH₃	BDL	400	IS 5182 : Part 25	
8	Carbon Monoxide CO (mg/m³)	ND	4	Gas Detector	
9	Lead Pb	ND	1	IS 5182 : Part 22	
10	Arsenic As (ng/m3)	ND	6	CPCB Guidelines	
11	Nickel Ni (ng/m3)	BDL	20	IS 5182 : Part 26	
12	Benzene C6H6	ND	5	IS 5182 : Part 11	
13	Benzo (a) pyrine BaP (ng/m3)	ND	1	IS 5182 : Part 12	

BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit BDL for SO₂ - 4 µg/m³ & NO₂ - 9.4µg/m³ μ-micro n-nano g-gram

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

Epo of the Report ***

or *OneEarth* Enviro Labs

Murlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after fifteen days from the date of issue of test reports unless otherwise specified. Perishable samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only. 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website; oneearthenvirolabs.com



Contificate No. TC-7847

NABL ACCREDITED AS PER ISO/IEC 17025:2005 | ISO 9001:2015 | CHSAS 18001:2007 CERTIFIED | MOEF & CC RECOGNISED

Report No: N/2020/0124-1 Report Date:30/10/2020

AMBIENT NOISE LEVEL MONITORING REPORT

Name of the Industry

M/s Mangalore SEZ Limited

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Address

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By Sampling Location

OneEarth Enviro Labs

L1 - Near WTP

Date of Sample Receipt

On site

Method Adopted

IS:9989.1981

Sampling Details

Noise Level Monitoring Day and Night

		T :		: VCDCD Limite		
SL NO	Date	Time	Min	Leq	Max	KSPCB Limits
1	22/09/2020	1115		54.0		
2		1215		68.4		
3		1315	:	46.9		
4	:	1415		62.2		:
5		151 5	· · · · · · · · · · · · · · · · · · ·	51. 5		
6		1615		52.6		• [
7		1715		48.6	!	75dB
8		1815		44.2	:	7540
9		1915	:	68.5	68.5	
10		2015		50.3		
11		2145		44.78	:	
12		2215	:	43.88	•	
13		2315		48.9		
14	23/09/2020	0015		35.8		70dB
15	1	0115	32.8	32.8		700D
16	1	0215		36.3		** *

Leq - Arithmetically mean value in a period of set time

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

** End of the Report **

For One Earth Epviro Labs

2409011

Authorised Signatory
Murlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received, 3. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

The Santa

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph: 0824-240 9011 Mob: +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: N/2020/0124-2 Report Date:30/10/2020

AMBIENT NOISE LEVEL MONITORING REPORT

Name of the Industry

M/s Mangalore SEZ Limited

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By Sampling Location

Address

OneEarth Enviro Labs L2 - Near CETP

Date of Sample Receipt

On site

Sampling Details

Noise Level Monitoring Day and Night

Method Adopted

IS:9989.1981

ivietnoa Aac	ptcu	13.9909.1901				
SL NO	Date	Time	Parameters			KSPCB Limits
SE NO	: Date	i iniie	Min	Leq	Max	
1	23/09/2020	, 1045	:	65.35		
2		1145		63.0		
3	<u>.</u>	1255		72.5		
4		1345	:	70. 9		
5		1445		67.2	:	
6		1545		74.5	74.5	
7		1645		61.89		75dB
8		1745		64.2		7,000
9		1845		60.86		
10		1945		67.3		
11	-	2045	1	52.5		:
12		2145		58.4		· V
13		2245		56.8		
14		2345		44,7	:	·
15	24/09/2020	0045	41.6	41.6	•	70.10
16	· · · · · · · · · · · · · · · · · · ·	0145		51.6		70dB

Leg - Arithmetically mean value in a period of set time

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

> PHONE 2*0931

** End of the Report **

or One Earth Enviro Labs

Authorised Signatory

Angahuru (Mürlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received, 3, Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only 5. Total liability of our lab is limited to the Invoice amount only. 6. Conformily statement might be affected due to measurement uncertainty.

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph: 0824-240 9011 Mob: +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



Certificate No. TC-7847
NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: N/2020/0124-3 Report Date:30/10/2020

AMBIENT NOISE LEVEL MONITORING REPORT

Name of the Industry

M/s Mangalore SEZ Limited

Survey No 168/3A I Plot

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Address Village, Mangalore Taluk, Karnataka 574142

Sample Collected By Sampling Location

OneEarth Enviro Labs

L1 - Near WTP

Date of Sample Receipt

On site

Sampling Details

Noise Level Monitoring Day and Night

Method Adopted IS:9989.1981

ivietnoa Aac	phica	12:3303.7307				
SL NO Date		Time	Parameters			: KSPCB Limits
3L 140	Date	16110	Min	Leq	Max	NOI OD LINIE
1	29/09/2020	1030	:	66.8	66.8	
2		1130	:	58.6	:	
3		1230		61.4		:
4		1330		55.4	:	:
5		1430		61.3		•
6	1	1530		48.9		; ; ;
7		1630		56.8		75dB
8	:	1730		45.6		TOOL
9	!	1830		49.4		<u> </u>
10	7	1930		60.2	!	
11		2030		55.0		
12		2130		44.7		
13		2230		45.8		
14		2330		40.6		
15	30/09/2020	0030		35.5		
16		0130	32.3	32.3		70dB
17		0220		32.7		· control

Leg - Arithmetically mean value in a period of set time

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

** End of the Report **

Constant Enviro Labs

Authorised Signatory
(Myrighar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

Page 1 of 1

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph: 0824-240 9011 Mob: +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



Certificate No. TG-7847
NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: N/2020/0124-4 Report Date:30/10/2020

AMBIENT NOISE LEVEL MONITORING REPORT

Name of the Industry

M/s Mangalore SEZ Limited

riamo or are madea y

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Address

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By Sampling Location

OneEarth Enviro Labs L2 - Near CETP

Date of Sample Receipt

On site

Sampling Details

Noise Level Monitoring Day and Night

Method Adopted

IS:9989.1981

SL NO	Date	Time		Parameters		KSPCB Limits	
JE NO	JL NO	Date		Min	Leq	Max	NOF OD LIIIUS
1	30/09/2020	, 1045		70.6			
2	1	1 14 5		66.4	:		
3		1245	:	72.8	72.8		
4		1345		62.2	:		
5		14 4 5		60.5	. !		
6	1	1545		59.9			
7		1645		57.9	-:	75dB	
8		1745		52.4		7005	
9		1845		50.2		* ! !	
10 -		1945		48.8			
11		2045		59.5		- - - -	
12		2145		50.3			
13		2245		54.1	:		
14		2345		48.4		· pr	
15	01/10/2020	0045		44.4			
16		0145	40.2	40.2		70dB	

Leq - Arithmetically mean value in a period of set time

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t

above tested parameters.

** End of the Report **

For One Earth Enviro Labs

Authorised Signatory

(Murializar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

Page 1 of 1

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



Certificate No. TC-7847
NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: N/2020/0124-5 Report Date:30/10/2020

AMBIENT NOISE LEVEL MONITORING REPORT

Name of the industry

Address

M/s Mangalore SEZ Limited

reache of the mason,

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

L1 - Near WTP

Sampling Location

Date of Sample Receipt

On site

Sampling Details

Noise Level Monitoring Day and Night

Method Adopted

IS:9989.1981

Method Add	, preu	13.3363.1361		Parameters		1
SL NO	Date	Time		rarameters		KSPCB Limits
OE IIO	Duto	111110	Min	Leq	Max	
1	06/10/2020	1040		60.3		:
2		1140		61.4		:
3	:	1240		59.8		! !
4		1340		58.78		
5		1440		63.2	63.2	
6		154 0		57.4		
7		1640	: :	59.1	· i	75dB
8		1740	:	50.5		1040
9		1840		47.4		
10		1940		62.5	:	
11	:	2040		54.8	:	
12		2140		42.6	!	:
13		2240	i :	48.5	:	
14		2340		35.8	:	
15	07/10/2020	0040	32.4	32.4		
16		0140		35.5		70dB
17		0240		36.8		•

Leg - Arithmetically mean value in a period of set time

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t

above tested parameters.

** End of the Report **

For Cne Earth Enviro Labs

Authorised Signatory

(Murlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

Page 1 of

(

S .

SIEV NAME

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025;2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: N/2020/0124-6 Report Date:30/10/2020

AMBIENT NOISE LEVEL MONITORING REPORT

Name of the Industry

M/s Mangalore SEZ Limited

Address

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By Sampling Location

OneEarth Enviro Labs

L2 - Near CETP

Date of Sample Receipt

On site

Sampling Details

Noise Level Monitoring Day and Night

CL NO Data Time		Parameters Date Time				KSPCB Limits
SL NO	Date	Hine	Min	Leq	Max	NOPUB LIMITS
1	07/10/2020	, 1105		71.8		
2		1205		73.5	73.5	
3		1305		69.8	· · · · · · · · · · · · · · · · · · ·	and the state of t
4		1405		66.5		- - +
5		1505		64.7		
6		1605		62.9	. :	· ; - : - !
7		1705		59.4		75dB
8		1805		55.8	:	
9		1905		61.8	:	
10		2005		59.9		
11		2105		58.3	:	· · · · · · · · · · · · · · · · · · ·
12		2205		54.1	:	"" : : :
13		2305		50.3	:	
14	08/10/2020	0005		45.5		:
15		0105		40.8		70dB
16		0205	39.8	39.8	:	"; : :

Leg - Arithmetically mean value in a period of set time

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

** End of the Report ***

2*3861

For *OneEarth* Enviro Labs

Authorised Signatory

(Murlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only 5. Total liability of our lab is limited to the invoice amount only, 6. Conformity statement might be affected due to measurement uncertainty.

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



Certificate No. TC-7847
NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: N/2020/0124-7 Report Date:30/10/2020

AMBIENT NOISE LEVEL MONITORING REPORT

Name of the Industry

Address

M/s Mangalore SEZ Limited

-

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By Sampling Location

OneEarth Enviro Labs

L1 - Near WTP

Date of Sample Receipt

On site

Sampling Details

Noise Level Monitoring Day and Night

Method Adopted IS:9989.1981

SL NO	Date	Time	:	Parameters		KSPCB Limits
JL NO	Date	111116	Min	Leq	Max	KSFCB LIIIIIS
1	13/10/2020	1055	:	62.1	:	
2		1155		60.6		
3		1255		61.6		
4		1355		60.5	:	
5		1455		65.7	65.7	•
6	<u>:</u>	1555		62.2		1 2 1
7		1655		58.5	· · · · · · · · · · · · · · · · · · ·	75dB
8		1755		52.5	·,··· · · · · · · ·	TOUD
9		1855		60.3	:	
10		1955		50.3	"	
11		2055		52.2		
12		2155		49.4	······································	:
13		2255		45.1	. ;	
14		2355		55.4		
15	14/10/2020	0055	32.4	32.4		:
16		0155		34.6		70dB
17		0255		30.1		:

Leq - Arithmetically mean value in a period of set time

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

** End of the Report **

For One Earth Enviro Labs

Authorised Signatory (Murtidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



Certificate No. TC-7847
NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: N/2020/0124-8 Report Date:30/10/2020

AMBIENT NOISE LEVEL MONITORING REPORT

Name of the Industry

M/s Mangalore SEZ Limited

Name of the moustry

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Address

Viilage, Mangalore Taluk, Karnataka 574142

Sample Collected By Sampling Location

OneEarth Enviro Labs
L2 - Near CETP

Date of Sample Receipt

On site

Sampling Details

Noise Level Monitoring Day and Night

Method Adopted

IS:9989.1981

Wicellou Nuc	prea	13.3303.1301				
SL NO	Date	Time	:	Parameters		KSPCB Limits
020			Min	Leq	Max	Narob Lilling
1	14/10/2020	، 1105		71.8	:	
2	:	1205		74.4	74,4	· :
3	: : :	1305		69.8		
4	:	1405		66.5		
5	•	1505		64.7		
6	·	1605		62.9		
7	i	1705		59.4	. :	75dB
8	;	1805		55.8		•• •
9		1905		61.8		!
10		2005		59.9		
11		2105		58.3		-
12		2205		54.1		
13		2305		50.3		Ì
14	15/10/2020	0005		45,5		
15		0105		40.8		70dB
16		0205	37.9	37.9		.4

Leq - Arithmetically mean value in a period of set time

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

PHONE 2409011

** End of the Report **

For One Earth Enviro Labs

Authorised Signatory (Muriidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.


[7677 01.12.2020]



Mangalore SEZ Limited

ENVIRONMENTAL MONITORING REPORT

AMBIENT AIR QUALITY AND MONITORING REPORT FOR THE MONTH OF Nov 2020



Submitted By

M/s OneEarth Enviro Labs

(NABL Accredited, MOEF&CC Recognized Laboratory)

KSIA Building, 1st Floor, Baikampady Industrial Estate, Mangaluru,

Karnataka – 575011 Email: oneearthenviro@gmail.com

<u>INDEX</u>

()

sl. No	DESCRIPTION	Page No.
1	Introduction - MSEZ	1
2	Environmental Monitoring	11
3	Scope and Methodology	1
3.1-3.1.7	Ambient Air Quality Sampling and Analysis	1-8
4	MSEZ Environmental Monitoring Schedule	9
5	Ambient Air Quality Results	Test Reports (4 pages)

AMBIENT AIR QUALITY MONITORING REPORT - November 2020

1. INTRODUCTION

Mangalore Special Economic Zone, known as MSEZ is spread across 1638 acres, located 15 km from Mangalore city, off Cochin-Mumbai NH 66, 5 km from Mangalore International Airport and 8 km from all-weather deep draft sea port, New Mangalore Port in Mangalore, Karnataka, India. MSEZ limited is jointly promoted by Oil and Natural Gas Corporation (ONGC), a fortune 500 company & infrastructure leasing & finance services, one of India's leading infrastructure development and finance companies, Karnataka industrial Area Development Board (KIADB) and Kanara Chamber of Commerce and Industry (KCCI). A unique combination of Government entities, a large financial institution and an apex chamber brings in the expertise to develop MSEZL with world-class industrial infrastructure.

2. ENVIRONMENT MONITORING

Environmental monitoring is being carried out at Mangalore SEZ, following guidelines and regulations of MoEF&CC/CPCB and KSPCB statutory norms. In this regard, MSEZL has awarded the work to M/s *OneEarth* Enviro Labs and to monitor air quality, water quality & noise level for the three years. As per work order, during November 2020, we have conducted ambient air quality at 3 locations.

3. SCOPE AND METHODOLOGY

The scope of work carried out and methodology adopted for the survey are described below:

3.1. Ambient Air Quality

Ambient air quality monitoring was carried out at each location on 24 hour basis on two consecutive days in this month. The identified monitoring locations are: 1- WTP, 2- CETP & 3-Permude Area. To assess the ambient air quality status, monitoring stations are identified on the basis of meteorology in the upwind and downwind direction as well as to represent the cross sectional scenario of the MSEZ. Based on the activities the parameters chosen for assessment of air quality are PM2.5-Particulate matter size less than 2.5 Micron, PM10-Particulate matter size less than 10 Micron; SO₂ Sulphur dioxide; NO₂-Nitrogen-di-oxide; CO-Carbon Mono Oxide (DL 0.1 mg/m³);O₃-Ozone (DL 10 μ g/m³);NH₃-Ammonia (DL 5 μ g/m³); Pb-Lead (DL 0.05 μ g/m³); As-Arsenic (DL 0.1 ng/m³); Ni- Nickel (DL 0.5 ng/m³); Benzene-(DL 1 μ g/m³); B(α)P- Benzo- α -pyrene(DL 0.1 ng/m³) as per CPCB stipulation.

3.1.1. Sampling and analysis of PM2.5 and PM10 in ambient air (Gravimetric Method)

- i. Check the filter for any physical damages
- ii. Mark identification number on the filter
- iii. Condition the filter in conditioning room / desiccator for 24 hours
- iv. Record initial weight
- v. Place the filter on the sampler
- vi. Run the sampler for twenty four hours
- Record the flow rate on hourly basis
- viii. Remove the filter from the sampler
- ix. Keep the exposed filter in a proper container
- x. Record the total time of sampling & average flow rate
- xi. Again condition the filter in conditioning room / desiccator for 24 hours
- xii. Record final weight

Laboratory analysis:

Weighing of exposed samples:

Calculate the concentration of PM10 or PM2.5 in µg/m³

Calculations:

- Average flow rate (initial and final flow rates) in L/ min
 - = (Initial flow rate + final flow rate)/ 2
- ii. Total vol. of air sampled (TVA) in m^3
 - = Avg. flow rate (L/min) * 10⁻⁵ (m^3/L) * sampling time (hr) * 60 (min/hr)
- iii. Concentration of PM in $\mu g/m^3$
 - = $(w_f w_i) (mg) / TVA (m^3) * 10^6 \mu g/m^3$ where w_i =initial & w_f =final weight of the filter paper

3.1.2. Sampling and analysis of Sulphur dioxide

- i. Place 30 ml of absorbing media in an impinger
- ii. Connect it to the gas-sampling manifold of gas sampling device (RDS/ HVS).
- iii. Draw air at a sampling rate of 1 lpm (litre per minute) for four hours
- iv. Check the volume of sample at the end of sampling and record it
- v. Transfer the exposed samples in storage bottle and preserve
- vi. Prepare calibration graph as recommended in method
- vii. Take 10/20 ml. aliquot of sample in 25 ml. Vol. Flask
- viii. Take 10/20 ml. of unexposed sample in 25 ml. Vol. Flask (blank)
- ix. Add 1 ml Sulphamic acid. Keep it 10 minutes
- x. Add 2 mi formaldehyde
- xi. Add 2 ml working PRA
- xii. Make up to mark (25 ml.) with distilled water.

- xiii. Keep it 30 minutes for reaction
- xiv. Set Zero of spectrophotometer with Distilled water
- xv. Measure absorbance at 560 nm
- xvi. Calculate concentration using calibration graph
- xvii. Calculate concentration of Sulphur Dioxide in µg/m³

3.1.3. Sampling and analysis of Nitrogen-di-oxide

- Place 30 ml of absorbing media in an impinger
- ii. Connect it to the gas sampling manifold of gas sampling device (RDS/HVS).
- iii. Draw air at a sampling rate of 1 lpm for four hours
- iv. Check the volume of sample at the end of sampling and record it
- v. Transfer the exposed samples in storage bottle and preserve
- vi. Prepare calibration graph as recommended in method
- vii. Take 10 ml. aliquot of sample in 50 ml. Vol. Flask
- viii. Take 10 ml. of unexposed sample in 50 ml. Vol. Flask (blank)
- ix. Add 1 ml hydrogen peroxide
- x. Add 10 ml sulphanilamide
- xi. Add 1.4 ml NEDA
- xii. Make up to mark (50 ml.) with distilled water.
- xiii. Keep it 10 minutes for reaction
- xiv. Set Zero of spectrophotometer with Distilled water
- xv. Measure absorbance at 540 nm
- xvi. Calculate concentration using calibration graph
- xvii. Calculate concentration of Nitrogen Dioxide in µg/m³

3.1.4. Sampling and analysis of Carbon Mono Oxide

Using Gas analyzer or by Gas detector tube or by portable GAS Detector calibrated against NIST Certified Gas cylinders of known concentration.

Gas Analyzer

Preparation of sample train:

- I. Sampling begins with conditioning a sampling train and then gas analyzer
- ii. Pressure system is preferred to condition the sampling train by installing pump before the analyzer. Reducing valve needs to be fitted between the analyser and pump to eliminate the pulsing effect of pump on the analyzer
- iii. Flow meter is to be installed just before the analyzer
- iv. A fibre filter is used to capture the particulate matter prior to the optical cell to prevent its interference. As it often accumulates on the optical cell reducing the efficiency
- v. To eliminate the interference of water vapour, refrigeration or desiccant with magnesium perchlorate could be used

Profession and the

3

Mode of operation:

- i. Continuous analysis is carried out at the flow rate of about 100 ml/min to 1000 ml/min (depending upon the level of pollution near the location) for the desired sampling period
- ii. Discrete sampling could also be possible with infra red analyzer. It however requires proper cleaning of the sampling train.

Gas detector tube

Mode of operation:

- 1. At the flow rate of about 100 ml/min using hand held pump draw 250ml of air sample into the tube.
- 2. Based on colour indicator, concentration of CO is determined.

Steps:

- i. Calibration of Gas Tube detector can be carried out using NIST Certified CO gas of known concentration
- ii. Sampler is allowed to warm up for some time before drawing the sample and temperature stability

Portable CO GAS Detector

Mode of operation:

- 1. Switch on the CO GAS meter and wait for some time for meter to get adjusted to the environmental conditions
- 2. Once steady CO Concentration is displayed note down the display.

Steps:

- i. Calibration of Gas detector meter to be carried out using NIST Certified CO gas of known concentration
- ii. Sampler is allowed to warm up for some time before drawing the sample and temperature stability

3.1.5 Sampling and analysis of Ozone

- i. Place10 ml of absorbing media in an impinger
- ii. Connect it to the gas sampling manifold of gas sampling device (RDS/HVS).
- iii. Draw air at a sampling rate of 1 lpm for 60 minutes
- iv. Do not expose the absorbing reagent to direct sunlight
- v. Add de ionized water to make up the evaporation loss during sampling and bring the volume to 10 ml
- vi. Prepare calibration graph as recommended in method
- vii. Within 30 to 60 minutes after sample collection, read the absorbance in a cuvette at352 nm against a reference cuvette containing de ionized water
- viii. Calculate concentration using calibration graph
- ix. Calculate concentration of Ozone in μg/m³

3.1.6 Sampling and analysis of Ammonia

- i. Dilute 10ml of concentrated HCI (12 M) to 100 ml with distilled water. Wash the glassware with the water and finally rinse it thrice with distilled water
- ii. Adjust the Flow rate at 11/min of the rotameter and the manifolds of the attached APM 411/APM 460 Dx

4

- Place 10 ml of absorbing media in each midget impinger for samples and field blanks. Assemble (in order) prefilter & holder, flow meter, impinger and pump. Sample at the rate of 1L/min for 1 hour duration iii.
- Record the sampling time, average flow rate and final volume of the solution. After the sample collection, transfer the solution in the impinger to polyethylene bottle and recap it tightly for transport to laboratory for į٧.
- Prepare the absorbing media, various reagents and working solutions as per the method described in protocol. Standardize the sodium thiosulphate solution by titrating it against potassium iodate and Sodium ٧. hypochlorite by titrating it against standardized sodium thiosulphate solution
- Take 25 ml measuring flasks and rinse with distilled water. Transfer the contents from polyethylene bottles to 25 ml measuring flasks (Maintain all the solutions at 25°C). Add 2 ml of buffer (to maintain pH). Add 5 ml of working phenol solution, mix, fill to about 22 ml with distilled water and then add 2.5 ml of working vi. hypochlorite solution & mix rapidly. Store in the dark for 30 mins to develop colour. Measure the absorbance of the solution at 630 nm using UV Spectrophotometer
- Pipette 0.5, 1.0 and 1.5 ml of working standard solution (working ammonia solution) in 25 ml measuring flasks. Fill to 10 ml mark with absorbing solution (0.1 M $\rm H_2SO_4$). Add the reagents as to each flask as in the procedure for analysis. Read the absorbance of each standard against the reagent blank. vii.
- Plot the calibration curve viii.
 - Calculate the concentration of NH₃ in µg/m³ ix.

3.1.7. Sampling and analysis of Lead, Nickel, Arsenic:

Tilt back the inlet and secure it according to manufacturer's instructions. Loosen the face-plate wing-nuts and Sampling procedure: remove the face plate. Remove the filter from its jacket and centre it on the support screen with the rough side of the filter facing upwards. Replace the face-plate and tighten the wing-nuts to secure the rubber gasket against the filter edge. Gently lower the inlet. For automatically flow-controlled units, record the designated flow rate on the data sheet. Record the reading of the elapsed time meter. The specified length of sampling is commonly 8 hours or 24 hours. During this period, several reading (hourly) of flow rate should be taken. After the required time of sampling, record the flow meter reading and take out the filter media from the sampler and put in a container or envelope

2. Analysis:

i.

Cut a 1" \times 8" strip or half the filter from the 8" \times 10" filter using a stainless steel pizza cutter. Place the filter in a beaker using vinyl gloves or plastic forceps. Cover the filter with the extraction solution (3% HNO₃& 8% HCl). Place beaker on the hotplate, contained in a fume hood, and reflux gently while covered with a watch glass for 30 min. Do not allow sample to dry. Remove the beakers from the hot-plate and allow to cool. Rinse the beaker walls and wash with distilled water. Add approximately 10 mL reagent water to the remaining filter material in the beaker and allow to stand for at least 30 min. Transfer the extraction fluid in the beaker to a 100 mL volumetric flask or other graduated vessel. Rinse the beaker and any remaining solid material with distilled water and add the rinses to the flask. Dilute to the mark with distilled water (Type I) water and shake. The final extraction solution concentration is 3 % HNO $_3/$ 8% HCI. The filtered sample is now ready for analysis

2.1. Analysis of samples:

i. Instrument / Equipment:

A light beam containing the corresponding wavelength of the energy required to raise the atoms of the analyte from the ground state to the excited state is directed through the flame or furnace. This wavelength is observed by a monochromator and a detector that measure the amount of light absorbed by the element, hence the number of atoms in the ground state in the flame or furnace. A hollow cathode lamp for the element being determined provides a source of that metal's particular absorption wavelength. The method describes both flame atomic absorption (FAA) spectroscopy and graphite furnace atomic absorption (GFAA) spectroscopy. Atomic Absorption Spectrophotometer - analyze the metals by Flame; if results are below detection limit then go for GTA. Arsenic is analyzed by Flame - VGA.

ii. Flame Procedure:

Set the atomic absorption spectrophotometer for the standard condition as follows: choose the correct hollow cathode lamp, align the instrument, position the monochromator at the value recommended by the manufacturer, select the proper monochromator slit width, set the light source current, ignite the flame, regulate the flow of fuel and oxidant, adjust the burner for maximum absorption and stability and balance the meter. Run a series of standards of the metal of interest and construct a calibration curve. Aspirate the blanks and samples. Dilute samples that exceed the calibration range. For Lead (Pb) and Nickel (Ni), the wavelength required for analysis is 217 nm and 232 nm respectively. Where as in case of Arsenic (As), the VGA should attach with Flame and the wavelength required for analysis is 193.7nm.

3. Calibration:

Prepare standard solutions from the stock solutions. Select at least three standards to cover linear range as recommended by method. Aspirate the standards into the flame or inject the standards into the furnace and record the absorbance. Prepare the calibration graph by plotting absorbance and concentration in µg/ml.

i. Preparation of Standards:

For each metal that is to be determined, standards of known concentration must be acquired commercially certified standards.

ii. Standard Curve:

Standard curve is prepared by using standard solutions of known concentration.

4. Calculations:

i. Sample Air Volume:

Sample air volume can be calculated by using the following equation:

V = (Q)(t)

Where,

V = volume of air, m³

Q = average sampling rate, m3/min.

t = time in minutes.

ii. Metal Concentration:

 $C = (Ms - Mb) \times Vs \times Fa/V \times Ft$

Where,

C = concentration, µg metal/m³

Ms = metal concentration µg/mL

Mb = blank concentration µg/mL

Vs = total volume of extraction in mL

Fa = total area of exposed filter in cm2

V = Volume of air sampled in m³

Ft = Area of filter taken for digestion in cm2

3.1.8. Sampling and analysis of Benzo-α-pyrene:

Benzo (a) Pyrene (BaP) is one of the most important constituent of PAH compounds and also one of the most potent carcinogens. This can be measured in both particulate phase and vapour phase, in the vapour phase the concentration of B(a)P is significantly less than the particulate phase. Therefore, more care to be taken for the measurement of Benzo (a) Pyrene in the particulate phase. The molecular formula of B(a)P is C₂OH₁₂ having molecular weight of 252.

It is based on BIS method IS 5182 (Part 12):2004 and USEPA method (TO-13). This method is designed to collect particulate phase PAHs in ambient air and fugitive emissions and to determine individual PAH compounds using capillary gas chromatograph equipped with flame ionization detector. It is a high volume (1.2m³/min) sampling method capable of detecting sub.ng/m³ concentration of PAH in 24 hours sample (i.e. collected in 3 shifts of 8 hour each with 480 m³ sampling volume of air).

i. Sampling:

i. Instrument/Filter Selection:

24 hr. sampling using PM_{10} high volume sampler with 8 hourly samples using EPM-2000 glass fibre or equivalent filter

ii. Sample Analysis

a, Extraction:

Filter papers (half of all the filters papers collected in a day) are cut into strips using scissors and transfer to 250 ml beaker. Add ~50 ml, of Toluene (GC/HPLC grade). These samples are extracted with toluene using ultra sonic sample can be extracted using Soxhlet bath for about 30 minutes. Repeat the procedure twice (50ml x 2 times) for complete extraction. Alternatively, extraction apparatus for about 8 hr, with Toluene and repeat it twice.

b. Filtration:

Filter the extracted samples with Whatman filter paper No.41 containing 2 gm of Anhydrous Sodium Sulphate (to remove moisture).

c. Concentration:

After filtration, the filtrate is concentrated using Rotary vacuum evaporator to 2ml final volume.

d. Clean-up with silica Gel:

To clean up the impurities, pass 2 ml of concentrated sample through silica gel column (pre conditioned, 60-80 mesh, and 200-250mm×10 mm with Teflon stopcock). After cleaning add 5ml cyclohexane and collect the elute in 25 ml beaker. Repeat the process for at least 3 times and collect it in the same beaker. Alternatively Solid Phase Extraction (SPE) could be used for clean up the impurities of sample.

e. Re-concentration with rotary vacuum evaporator:

The Cleaned up extract/filtrate (approximately 17 ml) is further concentrated using rotary evaporator and it is evaporated to nearly dryness with Nitrogen.

f. Final Sample volume:

The dried sample is re-dissolved in 1ml of toluene and transfer into 4 or 5 ml amber vials final analysis.

Calculations:

Calculate the concentration in $ng/\mu L$ of each identified analyte or B(a)P in the sample extract (Cs) as follows: Calculate the air volume from the periodic flow reading taken during sampling using the following equation:

V≍QxT

Where,

Q =Average flow rate of sampling m³/min

T = sampling time, in min.

V = total sample volume at ambient conditions in m³

Concentration of analyte i.e B(a)P:

The concentration of PAH compound or Benzo(a)pyrene in ng/m^3 in the air sampled is given by:

C (ng/m3) = Cs * Ve / Vi * Vs

Where,

Cs: Concentration of Benzo (a) pyrene in ng / μL in the sample extract recorded by GC.

Ve : Final volume of extract in μL (i.e 1000)

Vi : Injection Volume (i.e 1µL)

Vs : Volume of air sample in m³

4. MONITORING SCHEDULE OF MANGALORE SEZ LIMITED ENVIRONMENTAL MONITORING

Si.No	Environmental Attributes monitored	Parameters analyzed and presented in analysis Report	Monitoring requirement
1	Ambient Air Quality	PM2.5, PM10, SO ₂ , NO ₂ , CO, O ₃ , NH ₃ , Pb, As, Ni, Benzene, $B(\alpha)P$	3 Locations/Month, 24 hrs/day consecutive 2 days
2	Surface/ Ground Water Quality	Colour, pH (at 25 °C), Odour, Taste, Turbidity, Total Dissolved Sollds, Alkalinity as CaCO ₃ , Total Hardness, Calcium as Ca, Magnesium as Mg, Iron as Fe, Sulphate as SO ₄ , Chloride as Cl, Boron as B, Residual free chlorine, Fluoride, Phenolic Compounds, Manganese as Mn, Zinc as Zn, Arsenic as As, Cyanide as CN, Cadmium as Cd, Chromium as Cr, Aluminium as Al, Selenium as Se, Lead as Pb, Mercury as Hg, Nitrate Nitrogen NO ₃ , E.Coli	Ten Locations, Season wise (Summer, Winter, Post monsoon), By using grab sampling technique
3	Ambient Noise Level	Noise Level (dB) in Day and Night	Two Locations, two non consecutive days per week, for two weeks and Season wise (Summer, Winter, Post monsoon)

@

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: A/2020/0333 Report Date: 27/11/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name Address M/s Mangalore SEZ Limited

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

Sampling Location

CETP

Date of Sampling

19/11/2020 to 20/11/2020

Analysis Start Date

19/11/2020

Date of Sample Receipt

19/11/2020, 20/11/2020

Analysis End Date

27/11/2020

Sampling Details

Ambient Air Quality Monitoring for 24 Hrs

Humidity %

69.00

Temp °C

32.1°C

Pressure mmHg

757.04

	Date & Time	19/11/2020 0945	NAAQ	Protocol
SI. No	Location Parameters	333 Result (µg/m³)	STD	·
		26.62	60	IS 5182 : Part 24
. 1	Respirable Particulate Matter PM2.5	95.33	100	IS 5182 : Part 23
2	Respirable Particulate Matter PM10	6.87	500	IS 5182 : Part 4
3	SPM	BDL	80	(S 5182 : Part 2
4	Sulphur Dioxide SO ₂		80	IS 5182 : Part 6
5	Nitrogen Dioxide NO ₂	BDL	180	IS 5182 : Part 9
6	Ozone O ₃	ND BDL	400	IS 5182 : Part 25
7	Ammonia NH ₃	ND	4	Gas Detector
8	Carbon Monoxide CO (mg/m³)	ND	1	IS 5182 : Part 22
9	Lead Pb	ND	6	CPCB Guidelines
10	Arsenic As (ng/m3)	ND	20	IS 5182 : Part 26
11	Nickel Ni (ng/m3)		5	IS 5182 : Part 11
12	Benzene C6H6	ND ND	1	IS 5182 : Part 12
13	Benzo (a) pyrine BaP (ng/m3)			-3 g NO . Q dun/m³

BDL for SO₂ - 4 µg/m³ & NO₂ - 9.4µg/m³ BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit µ-micro n-nano g-gram

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t

above tested parameters.

End of the Report ***

For One Earth Enviro Labs

Authorized Signatory

(Murlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after fifteen days from the date of issue of test reports unless only to the samples conceled be samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only, 5. Total liability of our lab is limited to the invoice amount only, 6. Conformity statement might be affected due to measurement uncertainty.

4 - 575 01

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011, Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



Certificate No. TC-7847 NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: A/2020/0335 Report Date: 27/11/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name

M/s Mangalore SEZ Limited

Address

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

Sampling Location

Date of Sampling

20/11/2020 to 21/11/2020

Analysis Start Date

20/11/2020

Date of Sample Receipt

20/11/2020, 21/11/2020

Analysis End Date

27/11/2020

Sampling Details

Ambient Air Quality Monitoring for 24 Hrs

Humidity %

89.40

Temp °C

30°C

Pressure mmHg

756.74

	Date & Time	20/11/2020 1015	- NAAQ	
SI. No	Location	335	STD	Protocol
NO	Parameters'	Result (µg/m³)		
1	Respirable Particulate Matter PM2.5	33.33	60	IS 5182 : Part 24
2	Respirable Particulate Matter PM10	83.98	100	IS 5182 : Part 23
3	SPM	8.77	500	IS 5182 : Part 4
4	Sulphur Dioxide SO ₂	BDL	80	IS 5182 : Part 2
5	Nitrogen Dioxide NO₂	BDL	80	IS 5182 : Part 6
6	Ozone O ₃	104.41	180	IS 5182 : Part 9
7	Ammonia NH₃	ND	400	IS 5182 : Part 25
8	Carbon Monoxide CO (mg/m³)	ND	4	Gas Detector
9	Lead Pb	ND	. 1	IS 5182 : Part 22
10	Arsenic As (ng/m3)	ND	6	CPCB Guidelines
11	Nickel Ni (ng/m3)	ND	20	IS 5182 : Part 26
12	Benzene C6H6	ND	5	IS 5182 : Part 11
13	Benzo (a) pyrine BaP (ng/m3)	ND	1	IS 5182 : Part 12

BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit BDL for SO₂ - 4 µg/m³ & NO₂ - 9.4µg/m³ μ-micro n-nano g-gram

Opinion

As per Standards mentioned in the report. Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

nd of the Report ***

HONE

or *OneEcuth* Enviro Labs

Authorized Signatory

Murlidhar S M, Quality Manager

Note: 1.The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after fifteen days from the date of issue of test reports unless otherwise specified. Perishable samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only, 5. Total liability of our lab is limited to the invoice amount only, 6. Conformity statement might be affected due to measurement uncertainty.

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph: 0824-240 9011 Mob: +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: A/2020/0334 Report Date: 27/11/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name

M/s Mangalore SEZ Limited

Address

Survey No 168/3A | Plot No U-1, Administrative Building ,MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

Sampling Location

WTP

69.00

Date of Sampling

19/11/2020 to 20/11/2020

Analysis Start Date

19/11/2020

Date of Sample Receipt

19/11/2020, 20/11/2020

Temp ºC

Analysis End Date

Pressure mmHg

27/11/2020

Sampling Details

Humidity %

Ambient Air Quality Monitoring for 24 Hrs

32.1°C

757.04

Si.	Date & Time	19/11/2020 1015		
No	Location	334	NAAQ STD	Protocol
	Parameters •	Result (µg/m³)	. 310	
. 1	Respirable Particulate Matter PM2.5	40.70	60	IS 5182 : Part 24
2	Respirable Particulate Matter PM10	72.70	100	IS 5182 : Part 23
3	SPM	5.46	500	IS 5182 : Part 4
4	Sulphur Dioxide SO ₂	BDL	80	IS 5182 ; Part 2
5	Nitrogen Dioxide NO₂	BDL	80	IS 5182 : Part 6
6	Ozone O ₃	ND	180	IS 5182 : Part 9
7	Ammonia NH₃	ND	400	IS 5182 : Part 25
8	Carbon Monoxide CO (mg/m³)	ND	4	Gas Detector
9	Lead Pb	ND	1	IS 5182 : Part 22
10	Arsenic As (ng/m3)	ND	6	CPCB Guidelines
11	Nickel Ni (ng/m3)	ND	20	IS 5182 : Part 26
12	Benzene C6H6	ND	5	IS 5182 : Part 11
_13	Benzo (a) pyrine BaP (ng/m3)	ND	· 1	IS 5182 : Part 12

BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit BDL for SO₂ - 4 µg/m³ & NO₂ - 9.4µg/m³ μ-micro n-nano g-gram

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t above tested parameters.

*** End of the Report ***

For One Earth Enviro Labs

Authorized Signatory Mxrlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after fifteen days from the date of issue of test reports unless otherwise specified. Perishable samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only. 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

1st Floor, KSIA Building, Industrial Area Road, Baikampady, Mangaluru - 575 011. Ph. 0824-240 9011 Mob. +91 87625 39077 Email: oneearthenviro@gmail.com Website: oneearthenvirolabs.com



NABL ISO/IEC 17025:2005

ISO 9001:2015

OHSAS 18001:2007 CERTIFIED

MOEF & CC RECOGNISED

Report No: A/2020/0336 Report Date: 27/11/2020

AMBIENT AIR QUALITY ANALYSIS REPORT

Name

M/s Mangalore SEZ Limited

Address

Survey No 168/3A | Plot No U-1, Administrative Building , MSEZ, Bajpe

Village, Mangalore Taluk, Karnataka 574142

Sample Collected By

OneEarth Enviro Labs

Sampling Location

WTP

Date of Sampling

20/11/2020 to 21/11/2020

Analysis Start Date

20/11/2020

Date of Sample Receipt

20/11/2020, 21/11/2020

Analysis End Date

27/11/2020

Sampling Details

Ambient Air Quality Monitoring for 24 Hrs

Humidity %

89.40

Temp °C

30°C

Pressure mmHg

756.74

-	Date & Time	20/11/2020 1130	:	
SI. No	Location	336	NAAQ STD	Protocol
140	Parameters'	Result (µg/m³)	310	
1	Respirable Particulate Matter PM2.5	25.79	60	IS 5182 : Part 24
2	Respirable Particulate Matter PM10	96.38	100	IS 5182 : Part 23
3	SPM	5.21	500	IS 5182 : Part 4
4	Sulphur Dioxide SO₂	BDL	80	IS 5182 : Part 2
5	Nitrogen Dioxide NO₂	BDL	80	IS 5182 : Part 6
6	Ozone O ₃	87.78	180	IS 5182 : Part 9
7	Ammonia NH₃	ND	400	IS 5182 : Part 25
8	Carbon Monoxide CO (mg/m³)	ND	4	Gas Detector
9	Lead Pb	ND	1	IS 5182 : Part 22
10	Arsenic As (ng/m3)	· ND	6	CPCB Guidelines
11	Nickel Ni (ng/m3)	ND	20	IS 5182 : Part 26
12	Benzene C6H6	ND	5	IS 5182 : Part 11
13	Benzo (a) pyrine BaP (ng/m3)	ND	1	IS 5182 : Part 12

BDL-Below Detection Limit ND-Not Detectable DL-Detection Limit BDL for SO₂ - 4 µg/m³ & NO₂ - 9.4µg/m³ μ-micro n-nano g-gram

Opinion

As per Standards mentioned in the report.

Report Status: - The sample meets the requirement as per relevant standard w.r.t

above tested parameters.

End of the Report ***

For One Earth Enviro Labs

Authorized Signatory

Murlidhar S M, Quality Manager)

Note: 1. The report shall not be reproduced wholly or in part, cannot be used as evidence in court of law. 2. The above result pertains only to the samples collected/received. 3. Samples will be destroyed after fifteen days from the date of issue of test reports unless otherwise specified. Perishable samples are not retained. 4. Any dispute arising out of this test report is subjected to Mangalore Jurisdiction only. 5. Total liability of our lab is limited to the invoice amount only. 6. Conformity statement might be affected due to measurement uncertainty.

W - 575 05



ओएनजीसी मंगलूर पेट्रोकेमिकल्स लिमिटेड

(मंगलूर रिफाइनरी एण्ड पेट्रोकेमिकल्स लिमिटेड की सहायक कंपनी)

ONGC Mangalore Petrochemicals Limited

(A Subsidiary of Mangalore Refinery and Petrochemicals Limited)

एमएसईजेड, पेर्मुदे, संगलूरु – ५७४ ५०९ MSEZ, Permude, Mangaluru - 574 509.

CIN : U40107KA2006GOI041258 दूरभाषा Tel.: 0824-2872000, फैक्स Fax: 0824-2872005. Website: www.ompl.co.in

REF: OMPL/MoEFCC/SP/2020

Date: 01-12-2020

Mede Bzenk fran

To:

The Head- Technical MSEZ!, Mangalore

Mangalore SEZ Lid. - 76 78 Documents & Contents subject to verification Received date: ().l.l.Q., QC 200 Received by M. D.S.

Dear Sir.


Sub: Submission of Half Yearly Compliance Reports of OMPL under Environmental Clearance for Phase-I, MSEZ project, (Including Aromatic Complex) for the period from April, 2020 to September, 2020

With reference to the above, please find enclosed herewith, Half Yearly Compliance Reports of OMPI, for compilation at your end and submission to the concerned Authority under intimation to our office.

Thanking You

Skivaprakash Sr. Manager- HE

CC: CEO, OMPL for info COO, OMPL for info. **DGM- Production, OMPL for info**



Compliance to Charter on Corporate Responsibility for Environmental Protection (CREP)

SI. No.	Conditions	Compliance
1	Adoption of state-of- art technology State of Art technology will be adopted for both process technology	Please note Process technology is licensed from renowned expert in the field: UOP, America for NHT platforming
	as well sound engineering practices required for control of emission, at the stage of design itself in case of new plants	units, High severity Cyclemax CCR unit for catalyst regeneration, Energy efficient column design for Xylene & BTF units, ISOMER & TADP units for getting high yield of paraxylene per unit of Naptho processed & an efficient,
		selective PAREX process for paraxylene recovery to get high purity product are considered in the design stage. Also Low NOx burner design for heaters, Low sulphur fuel including provision for usage of Natural Gas are considered.
5	Management of storm water	Please note OMPL has commissioned 2 numbers of
	For the storm water generated from process area and tank farm area during initial hours of rain. An arrangement will be made for collection and oil separation including further treatment as required. Such arrangement will include provision for buffer tank (holding	collection tanks: one at ISBL area with capacity of 12,000 m3 & the other at OSBL area with 6000 m3 capacity for collection of initial hours of rain from process area & tank farm area respectively. This is then treated in ETP with an
	tank) and monitoring of effluent quality. This will be accomplished by June 2003.	treatment capacity g_{\bullet}^{*} :50 m3/ hr. The treatment section includes Physical treatment, chemical, Biological & Tertiary treatment sections
3	Effective detoxification and waste water treatment scheme In order to control high COD and persistent organic pollution	OMPL has installed Effluent Pre-Treatment Plant at a cost of RS 11.39 crores. The units consists of Distillation column
	including toxic constituents, the industry will select appropriate unit operations for pre-treatment of effluent within inside battery limit (ISBL) before sending to the biological treatment system(BTS) for better functioning of ETPs. Action plan for the same will be submitted	& carbon adsorption beds to remove CODs, so that effluent entering BTS will be having Max. upto 20 ppm of aromatics
4	within 6 months and implemented within one year (March,2004) Control of emission from combustion The industry will submit an action plan within six months for improving thermal efficiency and control of Nox	OMPL has installed Low Nox burners for its heaters & flugas is let out just above H2SO4 dew point after heating to incoming fuel, air or Steam production in HRSG as the calmay be, for improving thermal inspection
5	Proper functioning of point source emission control systems	NA
	The industry will make efforts for proper operation of pollution control system (mostly scrubbers) and attainment of desired efficiency within six months. The will include backup of power supply to the control equipment and arrangement for frequent sampling and analysis of all critical pollution in the tail gases	
6	Leak detection and repair (LDAR) programme As a good operating, the Industry will adopt periodically leak detection and repair (LDAR) programme to check fugitive emissions within six months. The frequency of the programme will be proportionate to the risk potential of carrying fluid. Based on leak	LDAR program is ongoing process since July, 2016. Please note OMPL as first step in leak prevention, hired Beli Energy India, who carried out Dispersion Model Analysis and recommended following Online detectors which are already installed at site such as, Benzene Detectors 27 no
	detection as per LDAR programme, action will be taken to eliminate fugitive emissions, this will be a continuous activity.	Hydrocarbon Detectors 193 nos
7	Handling of halogenated organics The industry will submit an action plan within 6 months to ensure that no halogenated organics is sent to the flares in order to avoid formation of persistent organic pollutants. All HAPs had halongenated organics will be routed to the incineration system	Halogenated organic is used only for chloride dispersion an platinum catalyst and consumed. Used catalyst will b disposed to KSPCB authorised recyclers
8	having end-on pollution control facility. Control of fugitive emissions of carcinogenic compounds Fugitive emission of carcinogenic compounds (e.g Benzene) will be controlled by closed vapor collection and recovery system. Measures will be taken to monitor health of the workers	Please note double mechanical seal is provided for the purpose & periodical health check up is being carried ou as per the legal requirement through Occupational Healt Centre; stagewise
9	Management of solid waste Proper facilities will be provided for handling and storage of hazardous waste with manifest system in case transported to other	OMPL has installed Solid Waste Management facility ot estimated cost of RS 3.73 crore for handling and stora of hazardous waste until disposal & manifest system w
	places. For incinerable waste, properly designed incinerator will be installed within the premises or as a common facility. The non-incinerable hazardous waste should be disposed of in a secure-land fill.	be follwed during disposal of Hazardous Wastes. Temporary Waste Storage facility is constructed of about 2000 m2 area with impervious surface, closed shed and spillage collection (for any washings) & transfer (to ETP)



10	Proper operation of incinerator	NA
	industry will check the design and will adopt sound engineering	· .
	practices for proper operation of incinerators. Continuous	
	monitoring will be done for operational parameters and specific	
	parameters in tall gas to ensure the efficient functioning. This will be	
	implemented within 3 months.	
11	Optimising the inventory of hazardous chemicals	Agreed. Further Petroleum & Explosives Safety
	Efforts will be made to optimize the inventory, particularly of	Organization (PESO) approvals are being taken for bulk
	hazardous chemicals. Such information will be made available to the	storage of Hazardous chemicals (Petroleum) wherein
	Regulatory Agencies (SBCBs) Inspector of Factory & District Collector	requirements of the MSIHC Rules, 1989 is considered
12	Self- regulation by industry through monitoring and environmental	Environment Monitaring is ongoing process
	auditing	
	industry will go for self-assessment and regulation by conducting	
	environmental auditing regularly, besides having regular monitoring	
	of pollutants in air emission, liquid effluent and receiving environment.	
13	Organizational restructuring and accreditation of environmental manager of industry.	Agreed
	For self-evaluation, organizational restructuring will be done and the	
	environmental manager of the industry will be accredited to bring	
	professionalism in environmental management.	

Compliance to Environmental Clearance

5l. No.	Consent Condition	Compliance
	The Mangalore Special Economic Zone (MSEZ) Phase-I involves a)	info.
	MRPL Phase -III Refinery b) Aromatic Complex and e) Olefin Complex	
	are proposed to be developed by the anchor promoter of MSEZ I,e	
	M/s ONGC-MRPL in the already acquired land of about 1800 acres.	
	The proposed MSEZ is planned adjacent to the existing MRPL refinery	
	complex on north & eastern sides and proposed to connect NMPT	
	with a dedicated 70/100 meter wide road-cum-pipeline (total approx.	
	15 km long) corridor for movement of cargo, crude and products	·
	between New Mangalore Port and MSEZ. The proposed layout has	
	one main entry from the proposed Mangalore MSEZ corridor	·
	connected to the existing New Mangalore Port & National Highway	
	(NH-17). The primary, Secondary and Tertiary roads are planned to	
	give access to the industries falling in the MSEZ Phase -I. Industrial	
	Zones for locating the olefin complex, aromatic complex, D/S	
2	Petrochemicals, ISPRCL underground crude oil storage and land for	* ************************************
	MRPL Phase-III Refinery are effectively placed in the central and	
	southwest part of the proposed MSEZ premises. Further, the SEZ will	
	have necessary road alignment between NMPT, SEZ and network of	
	roads within, including service roads for inspection of pipelines on	
	elevated corridors. The pipelines shall be built at elevated corridor	
	focations. Pipelines will be laid on sleepers and pipe racks with	
	sufficient ground clearance. The preferred corridor alignment avoids	,
	Coastal Regulation Zone -1 & II portion along the Gurupur River and it	-
	will have elevated roadway over structures (railways / minor bridges)	
	and reinforced earth walls. However the corridor passes over CRZ-III	
	zone along the banks of the Kudumbur rivulet (South of ELF gas) in	
	the form of a bridge. The proposed industrial units in MSEZ phase -1	
	To meet the objective of producing paraxylene, aromatic complex has	info.
	been considered. To maximize paraxylene, broad cut heavy naptha	
	streams are selected as feedstock to NHT/ CCR. Aromatics precursors	· ·
	to new reformer include constituents that produce toluene, C8-	
	aromatics mix & C9+ aromatics. Whereas a xylene isomerization unit	
ŧI	has been considered to convert other C8 - aromatics into paraxylene,	
	a transalkylation & disproportionation (TADP) unit has also been	
	included to convert toluene & C9+ aromatics into C8-aromatics mix.	
	simulated moving bed adsorption for paraxylene recovery (PAREX)	
	has been incorporated.	
	' '	·
1	NHT/ CCR : 0.95 MMTPA	Complied. The main Product slate, Paraxylene is within
2	Isomerization Unit (ISOMER): 3.16 MMTPA	Regulatory Body approved capacity of 0.9 MMTPA
	Transalkylation & Disproportionation Unit (TADP) :1.71 MMTPA]
3	,	·
	Paraxylene Recovery (PXREC) :4.07 MMTPA] .
4	The state of the s	
4 5	Xylene Fractionation Unit : 4.64 MMTPA	-
	Aromatics Extraction Unit: 4.64 MMTPA Aromatics Extraction Unit: 0.79 MMTPA	
5	Aromatics Extraction Unit : 0.79 MMTPA Benzene Toluene Fractionation Unit : 2.2 MMTPA	
5 6	Aromatics Extraction Unit : 0.79 MMTPA	
5 6	Aromatics Extraction Unit : 0.79 MMTPA Benzene Toluene Fractionation Unit : 2.2 MMTPA	Please note that normal requirement will be in the range of 50-55 MW, but Gas Turbine is more prone to Maintainance
5 6	Aromatics Extraction Unit : 0.79 MMTPA Benzene Toluene Fractionation Unit : 2.2 MMTPA	



3. A Speci	fic Conditions:-	-
1	No objection Certificate from the Karnataka State Pollution Control Board shall be obtained before initiating the project	Please note that MZEZ has obtained Consent for Establishment (CFE) from the Karnataka State Pollution Control Board (KSPCB) letter No. CFE-CELL/MSEZ/EIA-574/08/20 dated 30th April, 2008 and OMPL on its part has obtained CFE from the KSPCB, vide letter No. PCB/559/CFE/08/252 dated 12th August, 2008 & Extension of validity of CFE vide letter No. PCB/HPI/245/2013-14/1002 dated 5th October, 2013 upto 10.8.2014 from KSPCB, Bangalore
	The MSEZ project shall be restricted to the Phase -I of the project, proposed over 1,800 acres. The phase-II of the project shall be considered by Ministry of Environment & Forests only after receipt of all requisite documents\ information as laid down in the Environment Impact Assessment Notification, 2006 and Coastal Regulation 7 me Notification, 1991 as applicable	NA .
3	All development in the Coasta! Regulation Zone area shall be in accordance with coastal regulation zone notification, 1991. No destruction of mangroves shall be undertaken except while undertaking the permissible activities in the coastal regulation zone-lareas	NA
4	The project proponent shall not take up any activity in 875 acres of coastal regulation zone land, other than those permissible under the coastal regulation zone notification 1991 such as pipeline corridors, pipelines roads on stilts	NA
	With regard to the containing the suspected contamination of the groundwater near Athurkodi area of Kuthethoor village, MRPL has given an undertaking vide letter dated 19.3.2008 which is as follows:	NA
	The project proponent shall obtain a report from the wildlife department with regard to existence of wildlife in the proposed site as claimed by the public before implementing the project	Please note report from Wildlife Department was submitted to the MoEF by MSEZ
7	The R & R package shall be strictly in accordance with the laid down norms of the state Government	NA. However, OMPL has recruited around 302 displaced people and provided employment, till date (30.09.2020)
	A marine Environment Impact Assessment and Risk Assessment along with the Disaster Management Plan shall be prepared for the outfall facilities proposed in the Coastal Regulation Zone and the marine areas	NA .
٠	Project proponent shall put up a dedicated website and a display panel to inform the public regarding the Ambient Air Quality along with SO2, Nox and other parameters as prescribed by central Pollution Control Board (CPCB)	OMPL has put up a dedicated website 'www.ompl.co.in', wherein Environment Monitoring Parameters are uploaded and also has Installed a display panel at the entrance of Main Gate for public information
	The gaseous emissions (SO2, Nox, HC, VOC and Benzene) from various process units shall conform to the standards prescribed by the concerned State Pollution Control Board. All the measures detailed in the EMP and response to the Public Hearing shall be taken to control the point / stack and fugitive gaseous emissions from the proposed facilities, processes and storage units etc, for ensuring that the ambient air quality around the Refinery due to the expansion is maintained at the predicted 24 hourly average maximum concentration	parameters are installed for stacks and the readings are made available at DCS, for continuous monitoring, further uplinked to CPCB server. Corrective action will be taken for any deviation, however, plant will be run as per Standard Operating Process (SOP), prepared considering, Standards prescribed by the Regulatory Body. Further Online detectors are ovailable for HC, benzene, and to take up 'Containment work' and 'Repair work' on detection of leak, on priority basis.
	The emission levels of the other pollutants shall also remain within the permissible levels	Please note apart from the relevant parameters as from SI. No. '10', online instruments such as for CO & SPM are also Installed to stacks, so as to ensure pollutants within the permissible limits
	The Industrial units in the SEZ and the associated facilities shall be strictly in accordance with the norms laid down by the Karnataka State Government and CPCB	Agreed

- :-

.

	Fr	
13	The project proponent shall ensure that the greenery of the area is maintained. Further, 33 % of the project area shall be dedicated for	Karnataka Forest Dept., GOK has executed Green Belt Development program at OMPL, with WO value of RS 1.2
	green belt development of which atleast 5 % shall be for mangrove	l i
	<u> </u>	Crore. Development & Maintenance phase of GBD for 4
1	purpose and requisite budget earmarked	years upto 2020, completed. Around 13, 050 plants are planted by Karnataka Forest Department and watered
	barbose and reduisite pudget earmarked	· · · ·
		through Drip Irrigation. The species selected for Green Belt
İ		are having good amount of 'Crown Width' as recommended
		in EIA by NEERI, that was subsequently approved by MoEF
	·	while giving Environment Clearance.Some of the species
		recommended are, Acacia ferruginea DC (Mimosaceae),
		Acacia nilotica* (Mimosaceae), Allanthus excelsa*
1		(Simaroubiaceae), Albizia amara (Mimosaceae)
		Albizia labbeck* (Mimosaceae), Albizia
İ		doratissima(Mimosaceae), Aistonia scholaris*
		(Apocynaceae)
		Annogeissus latifolia (Combre ncea), Artocarpus
		integrifolia (Moraceae), Artocarpus lacucha (Moraceae),
	·	Azadirachto indica# (Meliaceae), Bauhinia malabarica
		(Fabaceae), Bauhinia racemosa* (Caesalpiniaceae), Butea
		monosperma (Fabaceae), Caesalpínia pulcherrima*
		(Caesalpiniaceae), Calophylum tomentosum, Cane sp.
	,	(Palmae), Canna orientalis (Cannaceae)
		Cassia fistula# (Caesalpiniaceae), Cassia
		siamea(Caesalpiniaceae), Casuarina equisetifolia#
		(Casurinaceae), Chlorophytum tuberosum (Liliaceae)
İ		Dalbergia sissoo (Fabaceaae), Dalbergia latifolia#
	· •	(Fabaceaae)
14	The project proponent shall ensure that the water requirement of the	Please note, OMPL, on its part has taken up following
	Mangaiore city does not get affected due to the SEZ operation.	measures to conserve water. 1. UF
]	Adequate provision shall be made in the reservoirs to provide for the	RO plant is specifically incorporated to recycle treated
	water requirement of the cities	water. 2. The
		complex Cooling Tower system is designed to use STP water,
		as make up from MSEZ, apart from the river water.
		3. Chemical Treatment Program with Modern Technology
		has been institutionalised to save water in Cooling Tower
		Plant 4.
		Condensate Recovery unit is being installed to conserve
		water and resources such as chemicals
		5. OMPL has under taken rain water harvesting measures
		for its buildings 6
		Further, treated CRWS will be explored for usage into CT
		system . The current ~ Average water consumption is
		157.22 m3/ hr as against design of 571 m3/ hr
] ,		
15	The project proponent shall ensure that during construction and	Please note OMPL site is at a distance of ~ 15 KM from the
	operation of the project the traffic in the city is not affected	Highway. Hence inconvenience to traffic movement in the
	· ·	city doesn't arise



16	All precautions of the highest standards shall be incorporated in the design of the project to ensure that there is no chance of emission/leakage of hazardous chemicals including Benzene. Detailed monitoring programme shall be designed and the information provided to the public through display and dedicated website by means of online monitoring	Please note following measures are taken to have a check on Emission/ leakage as, *All heaters are installed with LOW NOx Burners *Heaters stacks are fitted with following Online analyzers Carbon monoxide. Sulphur Dioxide Nitrogen Oxides Suspended Particulate matters (SPM) *Benzene Tanks — Internal Floating Roof Tank with Nitrogen Blanket *Paraffinic Raffinate (Volatile material) designed with Vapor recovery unit to recover vapor *Dispersion Model Analysis was done by Bell Energy India and following Online detectors are being installed Benzene Detectors 27 H2S Detector 21 Hydrocarbon Detectors 193 Hydrogen Detectors 68 Firc Detectors (In case of Fire) 26 *Sample Points are closed system to stop local venting and draining *Hydrocarbons drains are connected to closed Blow down system to recover hydrocarbon. *OMPL has put up a dedicated website 'www.ompl.co.in' and installed a display panel at the entrance of Main Gate for public information
17	Low sulphur Internal fuel oil and fuel gas shall be fired in process heaters and boilers	OMPL has gone for Low Sulphur content fuels in LSHS, HSD. & FG fuels. Please note 'SO2' emmission from EIA report for the project is estimated as 13.68 TPD. However, Avg SOx emmission per day is 1.3 MT/Day
18	Quarterly monitoring of fugitive emissions shall be carried out by Fugitive Emission Detectors (GMI) leak Surveyor. Guidelines of CPCB will be followed for monitoring fugitive emissions. For control of fugitive emissions, all unsaturated hydrocarbons shall be routed to the flare system. The flare system shall be designed for smokeless burning. Flare gas recovery system shall be installed for reduction of Hydrocarbon loss and emission of VOCs, NOx, N2O, SOx & CO2 to the environment	Please note Quarterly monitoring of fugitive emissions is being carried out by M/s Netel India Ltd, since 2016. Further based on, Dispersion Model Analysis by Bell Energy India, following Online detectors are installed Benzene Detectors 27 Hydrocarbon Detectors 193 *Flare system is designed for smokeless burning by M/s AirOil
19	Regular Ambient Air Quality Monitoring shall be carried out. The Location and results of existing monitoring stations shall be reviewed in consultation with the concerned State Pollution Control Board based on the occurance of maximum ground level concentration and downwingd direction of wind. Additional stations shall be set up, if required. It shall be ensured that at least one monitoring station is set up in up-wind & in Down - wind direction along with those in other directions	AAQM monitoring is carried out as per NAAQM rules, 2009 at 5 locations (since Jan, 2015), at a frequency of weekly twice per location, all the year round and Monitoring is done for all parameters as per the rules, as suggested by KSPCB & Monthly Reports are submitted to KSPCB. The values are found to be within the NAAQM Norms.
20	on-line data for air emissions shall be transferred to the CPCB and SPCB regularly. The instruments used for ambient air quality monitoring shall be calibrated regularly. The monitoring protocol shall ensure continuous monitoring of all the parameters	Online monitoring Devices have been installed to measure Heater Stack emmissions to all 10 number of stacks & are uplinked to CPCB server since April, 2016
21	The practise of acoustic plant design shall be adopted to limit noise exposure for personnel to an 8 hour time weighted average of 90 db(A)	Please note, as a first step, identified the sources of noise & then taken up Attenuation measures, at the design stage <u>Sources:</u> Pumps, Compressors & Turbines. <u>Attenuation measures:</u> It is ensured at design stage that Noise level at a distance of 1 mt from the equipment is < 90 db (A) & at plant boundry, it is less than 75 dB in daytime & 70 dB in night time as per the Legal requirement.


22	All the pumps and other equipments, where there is a likihood of HC leakages, shall be provided with appropriate indicators and detectors. Provision for immediate isolation of such equipment, in case of a leakage shall also be made. The company shall adopt leak detection and repair (LDAR) programme for quantification and control of fugitive emissions	Please note OMPL, as a first step in leak prevention, hired Bell Energy India, who carried out Dispersion Model Analysis and recommended following Online detectors which are installed at site such as, Benzene Detectors 27 nos Hydrocarbon Detectors 193 nos * Incase of leak, the first step is to contain the leak & simultaneously leak arresting work is carried out * Please note Quarterly monitoring of fugitive emissions are being carried out by M/s Hubert Enviro CareLtd, Bykampady
23	The product loading gantry shall be connected to the product sphere in closed circuit through the vapor arm connected to the tanker. Data on fugitive emissions shall be regularly monitored and records shall be maintained	<i>NA</i>
24	ine company shall ensure that no halogenated organic is sent to the flares. If any of the halogenated organic are present, then the respective streams may be incinerated, if there are no technically feasible or economically viable reduction / recovery options. Any stream containing organic carbon, other than halogenated shall be connected to proper flaring system, if not to a recovery device or an incinerator	Haloganated organic is used only for chloride dispersion on platinum catalyst and consumed. Halogenated compound is not sent to Flare Stack Chimney. Used catalyst will be disposed to KSPCB authorised recyclers
25	The new standards/ norms that are being proposed by the CPCB for Petrochemical Plants and Refineries shall be applicable for the proposed expanson unit. The company shall conform to the process vent standards for organic chemicals including non-VOCs and all possible VOCs i,e TOCs standards and process vent standards for top priority chemicals. Regular monitoring will be carried out for VOC and HC and on line monitors for VOC measurements may be installed	The new standards/ norms that are being proposed by the CPCB for Petrochemical Plants are complied. 1. Online Monitoring system is provided to heater stacks 2. Online Detectors of HC, Benzene are installed, to check any fugitive emissions 3. The process vents are connected to flares through safety pop -up valves 4.HC sampling points closed loop systems 5. Storage of HC is in Floating roof tanks (as applicable) with double mechanical seals and Nitrogen blanketing
26	Regular monitoring of relevant parameters for the under ground water in the surrounding areas shall be undertaken and the results shall be submitted to the relevant States Pollution Control Board	Please note Regular monitoring of groundwater is carried out at four locations surrounding the plant as advised by KSPCB & the reports are submitted to KSPCB. The frequency of sampling is once in a month, all the year round, at a location & compared with WHO Drinking Water Standards/ IS 10500 Norms. The values are found to be within Drinking water standards/ Norms.
27	Solid Waste generated as pretreater and Reformer catalysts, Sulphur guard absorbent and alumina Balls shall be disposed off as per the authorization from the State Polllution Control Board	Please note that the industry has in place proper Solid Waste handling system to collect, treat and dispose off all solid waste generated from the process including Hazardous wastes and the basic Engineering by Toyo Engineering. Please note OMPL has obtained 'Authorization under Handling Hazardous Wastes' and is being disposed accordingly. Temporary Waste Storage facility is constructed of about ~ 2000 m2 area with impervious surface, closed shed and spillage collection (for any washings) & transfer (to ETP) system
28	Oily sludge shall be sent to melting pit treatment for recovery of oil. The recovered oil shall be recycled into the refinery system. The residual sludge will be stored in HDPE lined pit for disposal after treatment. The sludge shall be incinerated in the premises only	No oily sludge is handled in OMPL
29	The company shall strictly follow all the recommendations mentioned in the charter on Corporate Responsibility for Environmental Protection (CREP)	Please refer compliance details for CREP enclosed herewith (ref.: Annexure- 1)
30	The company shall harvest surface as well as rainwater from the rooftops of the buildings proposed in the expansion project and storm water drains to recharge the ground water and use the same water for the various activities of the project to conserve fresh water	Rain water harvesting system is implemented for rooftop buildings. During initial project stage, all surface rain water was collected into open wells and the same was utilised for construction purpose



		le			
31	Occupational Health Surveillance of the workers should be done on a regular basis and records maintained as per the Factories Act	Complied and is angoing process			
32	The company shall implement all the recommendations made in the Environmental impact Assessment / EMP report and risk assessment report	Complied .			
33	The company will undertake all relevant measures, as indicated during the Public Hearing for improving the socio-economic conditions of the surrounding area	Complied			
34	With regard to R & R colony the project proponent shall obtain all requisite clearences as prescribed by the concerned agencies	NA			
R General	B General Conditions :				
1	The project authorities shall strictly adhere to the stipulations made by the concerned State Pollution Control Board (SPCB) and the State Government	KSPCB stipulations will be adhered to			
2	No further expansion or modifications in the plant shall be carried out without prior approval of the Ministry of Environment and Forests	Agreed			
·3	At no time, the emisions shall be allowed to go beyond the precribed standards. In the event of failure of any pollution control system adopted by the units, the respective unit should be immediately put out of operation and should not be restarted until the desired efficiency has been achieved	Agreed ·			
4	Adequate number of influent and effluent quality monitoring stations shall be set up in consultation with the SPCB, Regular monitoring shall be carried out for relevant parameters for both surface and ground water	Influent parameters & Effluent parameters will be measured through online measuring instruments installed at Inlet & outlet of ETP. They include TOC, pH, COD, Oil, DO, Phenol, Benzene. Further regular Surface & Ground water is being monitored as advised by KSPCB. The Ground Water is monitored once in month, at four locations, for all the year round and compared with WHO Drinking Water Standards.			
5	industrial Waste water shall be properly collected and treated so as to conform to the standards prescribed under GSR 422 (E) dated 19th May 1993 and 31st December, 1993 or as amended from time to time. The treated wastewater shall be utilized for plantation purpose	Industrial Waste Water is collected in Slop Tank and then Initially treated in EPTP plant to bring down Aromatics to < 20 ppm & Benzene to < 10 ppm, through Distillation & Adsorption methodology. It is treated in ETP comprising of Physical, Chemical, Biological & Tertiary Treatment Section. Treated water is recycled to cooling tower & the remaining, after ensuring Conformance to MINAS standards, will be disposed to sea through MSEZ CETP collection & Disposal system			
6	The overall noise levels in and around the plant area shall be limited within the prescribed standards (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels should conform to the standards prescribed under EPA rules, 1989 viz. 75 dBA (Day time) and 70 dBA (night time)	Sources: Pumps, Compressors & Turbines. Attenuation measures: It is ensured at design stage that Noise level at a distance of 1 mt from the equipment is < 90 db (A) by providing acoustic hoods, silencers, enclosures etc. as appropriate & at plant boundry is less than 75 dB in daytime & 70 dB in night time as per the Legal requirement			
7	The project authorities shall strictly cmply with the provisions made in manufacture, storage and import of Hazardous chemicals rules 1989 as amended in 2000 for handling of hazardous chemicals etc Necessary approvals from Chief Controller of Explosives must be obtained before commission of the expansion project. Requisite Onsite and Off site Disaster Management Plans will be prepared and implemented	Piease note that necessary license/ clearance from statutory agencies have been taken such as Approval from Petroleum and Explosives Safety Organization, dated 16th June 2011, Clearance from Department of Factories of Karnataka, dated 19th June 2010. Requisite On-site and Off - site Disaster Management Plans will be adhered to as per Factories Act			
8	Authorization from the State Pollution Control Board must be obtained for collections/ treatment/ storage/ disposal of Hazardous wastes	Please note OMPL has obtained 'Authorization under Handling Hazardous Wastes' is valid upto 30/6/2021			

9	The project authorities shall provide adequate funds both recuring and non-recurring to implement the conditions stipulated by the Ministry of Environment and Forests as well as the State Government along with the implementation schedule for all the conditions stipulated herein. The funds so provided shall not be diverted for any other purposes	Agreed. Further the Amount spent/budgeted on Environment Management requirement is approximated to RS 1.43 Crore for the year 2020-2021
10	The stipulated conditions shall be monitored by the concerned Regional office of this Ministry / Central Pollution Control Board / State Pollution Control Board. A six monthly compliance report and the monitored data shall be submitted to them regularly. It shall also be displayed on the website of the company	Please note biannually compliance report is submitted on regular basis through MSEZ. The Environment monitored data are being uploaded in the OMPL website
11	The project proponent shall inform the public that the project has been accorded environmental clearance by the Ministry and copies of the clearence letter are available with the State Pollution Control Board/ Committee and may also be seen at website of the MoEF at http://www.envfor.nic.in. This should be advertised within seven the date of Issue of clearance letter at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locality concerned and a copy of the same should be forwarded to the concerned Regional office of this Ministry	
12	The date of Financial closure and final approval of the project by the concerned authorities and the date of commencing the land development work as well as the commissioning of the project shall be informed to the Ministry and its Regional Office	NA .
13	Proper House keeping and adequate occupational health programmes shall be taken up. Regular Occupational Health Surveillance Programme for the relevant diseases shall be carried out and the records shall be maintained properly for atleast 30-40 years. Sufficient preventive measures shall be adopted to avoid direct exposure to emission and other hydrocarbons etc	Agreed
14	A separate environment management cell with full fledge laboratory facilities to carry out various management and monitoring functions shall be set up under the control of a Senior Executive	Complied
15	The Ministry may revoke or suspend the clearence, if implementation of any of the above condition is not satisfactory	Info.
16	The Ministry reserves the right to stipulate additional conditions if found necessary. The company shall implement these conditions in a time bound manner	info.
17	The above conditions will be enforced, inter - alia under the provisions of the Water (Prevention & Control of Poliution) Act, 1974, the Air Act, 1981, The Environment Act, 1986, The Public Liability insurance Act, 1991, Hazardous Waste Rules 1989 and Manufacture, Storage and Import of Hazardous Chemicais Rules, 1989 along with their Amendments and Rules	info.







ओएनजीसी मंगलूर पेट्रोकेमिकल्स लिमिटेड

(मंगलर रिफाइनरी एण्ड पेट्रोकेमिकल्स लिमिटेड की सहायक कंपनी)

ONGC Mangalore Petrochemicals Limited

(A Subsidiary of Mangalore Refinery and Petrochemicals Limited)

एमएसईज़ेड, पेर्मुदे, मंगलूरु - ५७४ ५०९. MSEZ, Permude, Mangaluru - 574 509.

CIN: U40107KA2005GOI041258 दुरभाषा Tel.: 0824-2872000, फैक्स Fax: 0824-2872005. Website: www.ompl.co.in

REF: OMPL/PCB/SP/2020-21/

Off

Date: 12/11/2020

To:

The Environmental Officer

Regional Office

KSPCB

Baikampady, Mangalore-11

Dear Sir,

Mangalore SEZ Ltd. 7589.
Documents & Contents subject to verification.

Received date 12.11.2020

Received by 1723414

Sub: Submission of Environmental Monitoring Report for the Month of October, 2020

Ref: KSPCB Combined Consent Order No. AW-301949 dated 27th January, 2017

With respect to the above subject; we are herewith submitting the following Environmental Monitoring Reports and Production Report for the Month of October, 2020 respectively, enclosed herewith.

- Ambient Air Quality Monitoring at 5 different locations in and around OMPL, enclosed as Annexure- A
- 2. Water Analysis Reports at 9 different locations in and around OMPL, as Annexure-B
- 3. Noise Level Monitoring Report at OMPL, as Annexure-C
- 4. Treated Effluent Analysis Report, Annexure-D
- 5. Returns Regarding Water Consumed, for the Month of October, 2020, as Annexure-E
- 6. Production Report as Annexure-F

Thanking You,

r. Manager- Env

CC: Member Secretary, KSPCB, Bangalore

CC: Head (Technical), MSEZ

CC: CEO, OMPL for info

CC: COO, OMPL for info.

CC: DGM- Production

Vinay Kurran

Jan 12020

H.O.: # 18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509
Sample Description	Ambient Air Quality Monitoring (AAQ)
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Sampling Location	OMPL - East Side
Report Date	04.11,2020
Report No	HECS/AA/001-008/041120

AMBIENT AIR QUALITY MONITORING: CONSOLIDATED TEST RESULTS - OCTOBER 2020

OCTOBER 2020 - Week		41-Week		42-Week		43-Week		44-Week		Avg.
Parameters	NAAQ	05.10.20	08.10.20	12.10,20	15.10.20	19.10.20	22.10.20	26.10,20	29.10.20	Value
PM _{2.5} (μg/m ³)	60*	18.2	18.6	18.1	18.7	18.5	18.2	18,9	19.1	18.5
PM ₁₀ (μg/m ³)	100*	38.6	38.9	39.5	38.6	39.5	38.7	39.8	40.2	39.2
$SO_2 (\mu g/m^3)$. 80*	8.4	8,2	7.7	8.1	8,5	8.6	7.9	8.9	8.3
NO ₂ (μg/m³)	80*	9,5	9.4	9.6	9.9	9.5	9,6	8.9	9.1	9.4
CO (mg/m ³)	2**	BDL.	B DL	BDL	BDŁ	BDL	BDL.	BDL	BDL	
O ₃ (μg/m ³)	100**	BDL	BDL :	8DL	BDL	8DL	BDL .	BDL	BDL	BDL
NH ₃ (μg/m ³)	400*	BDL	8DL	BDI,	BDL	BDL	BDL	BDL	BDL	BOL
Pb (μg/m³)	1*	BDL	BDL	8DL	BDL BDL	BDL	BDL	BOL	BDL	BDL
As (ng/m³)	6***	BDL	BDL	BDI,	BDL	BDL	BDL	BDL	BDL BDL	BDL
Ni (ng/m³)	20***	BDL	BDL	BDL	BDL	BDL	BDL	BDL	BDL	BDL
Benzene (μg/m³)	5***	BDL	BDL	BDL	BOL	BDL	BDL	BDL		BDL
B(α)P (ng/m³)	1***	BDL	BOL	BDL	BOL	BDL	BDL	8DL	BDI.	BDL

Note:

24 hours average;

:8 hours average;

: Annual average

Test Methods Followed:

PM ₁₀: IS 5182 (Pt 23): 2006 (RA 2017) (Gravimetric)

PM 2.5: HECS/AIR/SOP/002 Issue 02 dt. 13.06.2018 based on CPCB guidelines vol. I (2011)

SO₂: IS 5182 (Pt 2): 2001 (RA 2017) (Improved west and Geake method)

NO₂ IS 5182 (Pt 6): 2006 (RA 2017) (Jacob and Hochheiser modified method)

 O_3 : HECS/AIR/SOP/005 Issue 02 dt. 13.06.2018 based on CPCB guidelines vol. I (2011)

NH₃: HECS/AIR/SOP/006 Issue 02 dt. 13.06.2018 as per CPCB guidelines vol. I (2011)

CO: IS 5182 (Pt 10): 1999 (RA 2013)

Pb, As, Ni: In-house method based on CPCB guidelines vol. I (2011)

 C_6H_6 : GC FID/ GC MS based on IS: 5182 (Pt 11): 2006 based on CPCB guidelines vol. I (2011)

 $B(\alpha)P$: In-house validated method based on CPC8 guidelines vol. I (2011) & IS: 5182 (Pt 12): 2004

BDL =Below detection limit; DL - Detection Limit; PM_{2.5}-Particulate matter size less than 2.5 Micron (DL 10 $\mu g/m^3$); PM₁₀-Particulate matter size less than10 Micron (DL 5 $\mu g/m^3$); SO₂ Sulphur dioxide (DL 5 $\mu g/m^3$); NO₂ — Nitrogen-dioxide (DL 6 $\mu g/m^3$); CO - Carbon Mono Oxide (DL 0.05 $m g/m^3$); O₃-Ozone(DL 10 $\mu g/m^3$); NH₃-Ammonia (DL 5 $\mu g/m^3$); Pb-Lead (DL 0.05 $\mu g/m^3$); As-Arsenic (DL 2 $n g/m^3$); Ni-Nickel (DL 10 $n g/m^3$); Benzene-(DL 1 $\mu g/m^3$); Benzo - α -pyrene (DL 1 $n g/m^3$); $n g/m^3$: nanogram per cubic meter; $\mu g/m^3$ - microgram per cubic meter.

CONCLUSION: ALL THE PARAMETERS MEET THE NAME THE

*****End of Report *****

Authorized Signatory Or K Ganesar - Lab Manager)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization. Z. Samples are not drawn by HECS unless or otherwise mentioned. 3. Unless specifically requested by customer the tast items will not be retained more than 15 days from the date of Isaue of test report. 4. Under no circumstances lab accepts any liability or loss / damage caused by use or misuse of test report after involcing or issue of test report. 5. The test results relate only to the test items. 6.#not under scope of accreditation.

H.O.: # 18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Balkampady, Mangaiore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)	
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509	
Sample Description	Ambient Air Quality Monitoring (AAQ)	
Sample Collected by	Hubert Enviro Care Systems (P) Ltd	
Sampling Location	Shantigudda	
Report Date	04.11.2020	
Report No	HECS/AA/009-016/041120	

AMBIENT AIR QUALITY MONITORING: CONSOLIDATED TEST RESULTS - OCTOBER 2020

OCTOBER 2020- Week		41-V	41-Week		42-Week		43-Week		44-Week	
Parameters	NAAQ	05.10.20	08.10.20	12.10.20	15.10.20	19.10.20	22.10.20	26.10.20	29.10.20	Value
PM _{2,5} (μg/m ³)	60*	19.1	18.5	18.7	18.2	17.9	18.2	18.3	18.9	18.5
PM ₁₀ (μg/m ³)	100*	39.1	39.5	39.8	38,8	38.6	38.8	39.4	39.6	39.2
SO ₂ (μg/m³)	80*	8.2	8.3	7.9	8.2	8.5	8.3	8.1	8.2	8.2
NO _z (µg/m³)	80*	9.9	9.5	9.9	9.5	9.8	9.9	10.1	9.2	9.7
CO (mg/m³)	2**	BDL	BDL	BDL	BDL	BDL	BDL	BDL	BDL	BDL
$O_3 (\mu g/m^3)$	100**	BDL	BDL	BDL	BDL	8DL	BDL	BDL	BOL	BDŁ
NH ₃ (µg/m ³)	400*	BOL	BDL	8DL	BOL	BDL	BDL	BDŁ.	BDL	BDL
Pb (μg/m³)	, 1 _*	8DL	BDL	BDL	BDL -	BDL	BDL	BDŁ	BDL	BĐL
As (ng/m³)	6***	BDL	BDL	BDL	₿DL	BDL	BOL	BDL	BDL	BDL
Ni (ng/m³)	20***	BDL	8DL	BDL	BDL	BDL	BDL	BDL	BDL	BDL
Benzene (µg/m³)	5***	BDL	BDL	8DL	BÐL	8DL	BDL	BDL	BDL	BDL
B(α)P (ng/m³)	1***	BDL	BDU	BDL	BDL	BOL	BDL	BDL	BDL	BDL
		Note	A hours me		0 harry	4+11		l <u></u>		L

Note

24 hours average;

:8 hours average;

: Annual average

Test Methods Followed:

PM 10: IS 5182 (Pt 23): 2006 (RA 2017) (Gravimetric)

PM _{2.5}: HECS/AIR/SOP/002 Issue 02 dt. 13.06.2018 based on CPCB guidelines vol. I (2011)

SO₂: IS 5182 (Pt 2): 2001 (RA 2017) (Improved west and Geake method)

NO2: IS 5182 (Pt 6): 2006 (RA 2017) (Jacob and Hochheiser modified method)

O₃: HECS/AIR/SOP/005 issue 02 dt. 13.06.2018 based on CPCB guidelines vol. I (2011)

NH₃: HECS/AIR/SOP/006 Issue 02 dt. 13.06.2018 as per CPCB guidelines vol. I (2011)

CO: IS 5182 (Pt 10): 1999 (RA 2013)

Pb, As, Ni: In-house method based on CPCB guidelines vol. I (2011)

 C_6H_6 : GC FID/ GC MS based on IS: 5182 (Pt 11): 2006 based on CPCB guidelines vol. I (2011)

B(α)P: In-house validated method based on CPCB guidelines vol. I (2011) & IS: 5182 (Pt 12): 2004

BDL =Belo detection limit; DL - Detection Limit; PM_{2.5}-Particulate matter size less than 2.5 Micron (DL 10 $\mu g/m^3$), PM₁₀-Particulate matter size less than10 Micron (DL 5 $\mu g/m^3$); SO₂ Sulphur dioxide (DL 5 $\mu g/m^3$); NO₂ - Nitrogen-dioxide (DL 6 $\mu g/m^3$); CO - Carbon Mono Oxide (DL 0.05 $m g/m^3$); O₃-Ozone(DL 10 $\mu g/m^3$); NH₃-Ammonia (DL 5 $\mu g/m^3$); Pb-Lead (DL 0.05 $\mu g/m^3$); As-Arsenic (DL 2 $n g/m^3$); Ni-Nickel (DL 10 $n g/m^3$); Benzene-(DL 1 $\mu g/m^3$); Benzo - α -pyrene (DL 1 $n g/m^3$); $n g/m^3$: nanogram per cubic meter; $\mu g/m^3$ - microgram per cubic meter.

CONCLUSION: ALL THE PARAMETERS MEET THE NAAQ STANDARDS

*****End of Report *****

Authorized Signatory

1. The report in full or part shall not be used for any promotional or publicity purpose without written consent by NECS from the date of lastic or the report in full or part shall not be used for any promotional or publicity purpose without written consent by NECS from the date of lastic or the part of the report in full or part shall not be used for any promotion or the state of lastic or the report of the re

H.O.: # 18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by McEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509
Sample Description	Ambient Air Quality Monitoring (AAQ)
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Sampling Location	Tenka Ekkar
Report Date	04.11,2020
Report No	HECS/AA/017-024/041120

AMBIENT AIR QUALITY MONITORING: CONSOLIDATED TEST RESULTS - OCTOBER 2020

OCTOBER 20	20 - Week	41-W	/eek	42-Week		43-Week		44-Week		Avg.	
Parameters	NAAQ	05.10.20	08.10.20	12.10.20	15.10.20	19.10.20	22,10.20	26.10.20	29.10.20	Value	
PM _{2.5} (μg/m ³)	60*	18.9	19.1	19.8	19.6	19.8	18.7	19.7	19.9	19.4	
PM ₁₀ (µg/m ³)	100*	39,5	37.6	39.6	39.5	37,8	36.8	37.8	38.9	38.4	
5O ₂ (μg/m³)	80*	7.8	7.6	7.5	7.7	8.2	8,1	8.0	7.8	7.8	
NO ₂ (µg/m³)	80*	9.2	9.1	8.9	9.1	9.0	9.1	9.2	8,9	9.1	
CO (mg/m³)	2**	BDL	BDL	BDL	BDL	BDL	BDL	BOL	BDL	BDL	
O ₃ (μg/m ³)	100**	BDL									
NH ₃ (μg/m³)	400*	BDL	8DL	BDL	BDL	BDL	BDL	BDL,	BDL	BDL	
Pb (µg/m³)	1*	BDL	BDL	BDL	8DL	BDL	BDL	BDL	BDL	8DL	
As (ng/m³)	6***	BDL	BDL	BDL	BDL	8DL	BDL	BDL	BDL	BDL	
Ni (ng/m³)	20***	BDL	BDL	BDL	BDL	BDL	8DL	BDL	BDL	BDL	
Benzene (µg/m³)	5***	BDL	BÐL	BDL	BDŧ.	BDL	BDL	BDL	BDL	BDL	
B(a)P (ng/m³)	1***	BDL	BDt.	BDL	BDL	BDL	BDL	BDL	BOL	BDL	

Note:

24 hours average:

:8 hours average:

: Annual average

Test Methods Followed:

PM 10: IS 5182 (Pt 23): 2006 (RA 2017) (Gravimetric)

PM _{2.5}: HECS/AIR/SOP/002 Issue 02 dt. 13.06.2018 based on CPCB guidelines vol. I (2011)

SO₂: IS 5182 (Pt 2): 2001 (RA 2017) (Improved west and Geake method)

NO₂; IS 5182 (Pt 6): 2006 (RA 2017) (Jacob and Hochheiser modified method)

O3: HECS/AIR/SOP/005 Issue 02 dt. 13.06.2018 based on CPCB guidelines vol. (2011)

NH₃: HECS/AIR/SOP/006 Issue 02 dt. 13.06.2018 as per CPCB guidelines vol. I (2011)

CO: IS 5182 (Pt 10): 1999 (RA 2013)

Pb, As, Ni: In-house method based on CPCB guidelines vol. I (2011)

 C_6H_6 : GC FID/ GC MS based on IS: 5182 (Pt 11): 2006 based on CPCB guidelines vol. I (2011)

B(α)P: In-house validated method based on CPCB guidelines vol. I (2011) & IS: 5182 (Pt 12): 2004

BDL =Below detection limit; DL - Detection Limit; PM_{2.5}-Particulate matter size less than 2.5 Micron (DL 10 μ g/m³); PM₁₀-Particulate matter size less than10 Micron (DL 5 μ g/m³); SO₂ Sulphur dioxide (DL 5 μ g/m³); NO₂ - Nitrogen-dioxide (DL 6 μ g/m³); CO - Carbon Mono Oxide (DL 0.05 μ g/m³); O₃-Ozone(DL 10 μ g/m³); NH₃-Ammonia (DL 5 μ g/m³); Pb-Lead (DL 0.05 μ g/m³); As-Arsenic (DL 2 μ g/m³); Ni-Nickel (DL 10 μ g/m³); Benzene-(DL 1 μ g/m³); Benzene-(DL 1 μ g/m³); ng/m³: nanogram per cubic meter; μ g/m³ - microgram per cubic meter.

CONCLUSION: ALL THE PARAMETERS MEET THE NAAQ STANDARDS

*****End of Report *****

Authofiùed Signa Dr K Ganesan -\tab Mana)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are in the property of the promotion of the samples are in the property of the property of the samples are in the property of the property of the samples are in the property of the property of the samples are in the prope

H.O.: # 18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011.

Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509
Sample Description	Ambient Air Quality Monitoring (AAQ)
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Sampling Location	Permude Village
Report Date	04.11.2020
Report No	HECS/AA/025-032/041120

AMBIENT AIR QUALITY MONITORING: CONSOLIDATED TEST RESULTS - OCTOBER 2020

OCTOBER 2020- Week		41-Week		42-Week		43-Week		44-Week		Avg.				
Parameters	NAAQS	05.10.20	08,10,20	12,10.20	15.10.20	19.10.20	22.10,20	26.10.20	29.10.20	Value				
PM $_{2.5}$ (µg/m 3)	60*	18.9	18.8	18.6	18.9	18,8	19.6	19.7	19.8	19.1				
PM ₁₀ (μg/m³)	100*	37.7	38.2	37.5	38,5	37.6	36.9	37.5	38.8	37.8				
SO ₂ (μg/m ³)	80*	8.2	7.9	8.1	7.9	7.9	7.6	8.1	7.7	7.9				
NO _z (µg/m³)	80*	9.5	9.8	9.5	9.7	9.2	8.9	9.5	9.6	9.5				
CO (mg/m³)	2**	8DL	BDL	BDL	BDL	₿DL.	BDL	BDL	BDL	BDL				
$O_3 (\mu g/m^3)$	100**	8DL	BDL	BDŁ	BDL	8D£	BDL	BOL	BDL	BDL				
NH ₃ (μg/m ³)	400*	BDL	BDL	BDL	BDL	BDL	BOL	BDL	BDL	BDL				
Pb (μg/m³)	1*	BDL	BDL	BDL	BDL	· BDL	BÐL	BDL	BDL	BDL				
As (ng/m³)	6***	BDL	8DL	BDL Ni (ng/m³)	20***	BDL	8DL	BDL	BDL	BD1.	BDL,	BDL	BDL	BDL
Benzene (µg/m³)	5***	BDL	BDL.	BOL	BDL	BDL	,BDL	BDL	BDL	BDL				
B(α)P (ng/m³)	1***	BDL	BDL	BÐL	BDL	BDL	BDL	BDL	BDL	BDL				

Note:

24 hours average;

:8 hours average;

: Annual average

Test Methods Followed:

PM 10: IS 5182 (Pt 23): 2006 (RA 2017) (Gravimetric)

PM 2.5: HECS/AIR/SOP/002 issue 02 dt. 13.06.2018 based on CPCB guidelines vol. I (2011)

SO₂: IS 5182 (Pt 2): 2001 (RA 2017) (Improved west and Geake method)

NO_{2:} IS 5182 (Pt 6): 2006 (RA 2017) (Jacob and Hochheiser modified method)

O₃: HECS/AIR/SOP/005 Issue 02 dt. 13.06.2018 based on CPCB guidelines vol. I (2011)

NH₃: HECS/AIR/SOP/006 Issue 02 dt. 13.06.2018 as per CPCB guidelines vol. I (2011)

CO: IS 5182 (Pt 10): 1999 (RA 2013)

Pb, As, Ni: In-house method based on CPCB guidelines vol. | (2011)

 C_8H_6 : GC FID/ GC MS based on iS: 5182 (Pt 11) : 2006 based on CPCB guidelines vol. I (2011)

B(α)P: In-house validated method based on CPCB guidelines vol. I (2011) & IS: 5182 (Pt'12): 2004

BDL =Below detection limit; DL - Detection Limit; PM_{2.5}-Particulate matter size less than 2.5 Micron (DL 10 μ g/m³), PM₂₀-Particulate matter size less than10 Micron (DL 5 μ g/m³); SO₂ Sulphur dioxide (DL 5 μ g/m³); NO₂ - Nitrogen-dioxide (DL 6 μ g/m³); CO - Carbon Mono Oxide (DL 0.05 μ g/m³); O₃-Ozone(DL 10 μ g/m³); NH₃-Ammonia (DL 5 μ g/m³); Pb-Lead (DL 0.05 μ g/m³); As-Arsenic (DL 2 μ g/m³); Ni-Nickel (DL 10 μ g/m³); Benzene-(DL 1 μ g/m³); Benzene (DL 1 μ g/m³); ng/m³: nanogram per cubic meter; μ g/m³ - microgram per cubic meter.

CONCLUSION: ALL THE PARAMETERS MEET THE NAAQ STANDARDS

*****End of Report *****

Authorized Signatory (Dr K Ganesan Lab Manager)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HEGS organization. 2. Samples are not drawn by HECS unless or otherwise manifemed. 3. Unless specifically requested by customer the test items will not be retained more than 18 days from the date of issue of test report. 4. Under no circumstances jab accepts any Nability or loss / damage caused by use or misuse of test report after involving or issue of test report. 5. The test results relate only to the test items. 6.# not under scope of accreditation.

H.O.: # 18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax: 42985500 E-mail: labsates@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011.

Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing) Recognized by MoEF, BIS **FSSAI Notified Laboratory** ISO 9001, 14001 & OHSAS 18001 Certifled.

Name of the industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore – 574509
Sample Description	Ambient Air Quality Monitoring (AAQ)
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Sampling Location	OMPL - West Side
Report Date	04.11.2020
Report No	HECS/AA/033-040/041120

AMBIENT AIR QUALITY MONITORING: CONSOLIDATED TEST RESULTS - OCTOBER 2020

OCTOBER 2020- Week		41-Week		42-Week		43-Week		44-Week		Avg.		
Parameters	NAAQ	05.10.20	08.10.20	12.10.20	15.10.20	19.10.20	22.10.20	26.10.20	29.10.20	Value		
PM _{2.5} (μg/m ³)	60*	18,1	18.9	18.7	18.5	18.5	18.6	18.8	18,9	18.6		
PM ₁₀ (μg/m ³)	100*	37.8	38.6	37.5	36.8	37.6	37.8	38,8	37.8	37.8		
SO ₂ (μg/m ³)	80*	7.8	8.5	7.9	7.8	7.9	7.2	7.6	7.8	7.8		
NO ₂ (μg/m³)	80*	9.8	9,9	9.5	9.2	9,8	9,0	9.5	9.2	9.5		
CO (mg/m³)	2**	BDL	8DL	BDL	BDL	BDL	BDL :	BDL	8DL	BDL		
$O_3 (\mu g/m^3)$	100**	BDL	BDL	BDL	BDL	BDL	BOL	BDL	BDL	BDL		
NH ₃ (μg/m³)	400*	BDL	BDL	BOL	BDL	BDL	BDL	BDL	BDL	BDL		
Pb (μg/m³)	1*	BDL	BOL	8DL	BDL	BDL	BDL	BDL	BDL	BDL		
As (ng/m³)	6***	BDL Ni (ng/m³)	. 20***	BDL.	BDL	BDL	BDL	BDL	BD£	BDL	BOL	BOL
Benzene (µg/m³)	5***	BDL B(α)P (ng/m³)	1***	BDL "24 hours average:								

:8 hours average;

: Annual average

Test Methods Followed:

PM 10: IS 5182 (Pt 23): 2006 (RA 2017) (Gravimetric)

PM 2.5: HECS/AIR/SOP/002 Issue 02 dt. 13.06.2018 based on CPCB guidelines vol. I (2011)

SO₂: IS 5182 (Pt 2): 2001 (RA 2017) (Improved west and Geake method)

NO_{2:} IS 5182 (Pt 6): 2006 (RA 2017) (Jacob and Hochheiser modified method)

O₃: HECS/AIR/SOP/005 Issue 02 dt. 13.06.2018 based on CPCB guidelines vol. I (2011)

NH₃: HECS/AIR/SOP/006 Issue 02 dt. 13.06.2018 as per CPCB guidelines vol. I (2011)

CO: IS 5182 (Pt 10): 1999 (RA 2013)

Pb, As, Ni: In-house method based on CPCB guidelines vol. I (2011)

C₆H₅: GC FID/ GC MS based on IS: 5182 (Pt 11): 2006 based on CPCB guidelines vol. I (2011)

B(α)P: In-house validated method based on CPCB guidelines vol. I (2011) & IS: 5182 (Pt 12): 2004

BDL =Below detection limit; DL - Detection Limit; PM_{2.5}-Particulate matter size less than 2.5 Micron (DL 10 µg/m³). PM_{10} -Particulate matter size less than 10 Micron (DL 5 $\mu g/m^3$); SO_2 Suiphur dioxide (DL 5 $\mu g/m^3$); NO_2 – Nitrogen-dioxide (DL 6 μg/m³); CO - Carbon Mono Oxide (DL 0.05 mg/m³); O₃-Ozone(DL 10 μg/m³); NH₃-Ammonia (DL 5 μg/m³); Pb-Lead (DL 0.05 μ g/m³); As-Arsenic (DL 2 ng/m³); Ni-Nickel (DL 10 ng/m³); Benzene-(DL 1 μ g/m³); B(α)P- Benzo - α pyrene (DL 1 ng/m³); ng/m³: nanogram per cubic meter; μg/m³ - microgram per cubic meter.

CONCLUSION: ALL THE PARAMETERS MEET THE NAAQ STANDARDS

*****End of Report *****

(Dr K Ganesa:

1. The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are not drawn by MECS unless or otherwise mentioned 3. Unless specifically requested by customer the last items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances is accepts any liability or loss / damage caused by use or misuse of test report after invoicing or issue of test report. 5. The test results relate only to the test items. 6.#not underscope of accreditation.

H.O.: #18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax: 42985500 E-mail: iabsales@hecs.in

C-45, Industrial Estate, Balkampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in

Laboratory Services Division

(Chemical & Biological Testing) Recognized by MoEF, BIS FSSAI Notified Laboratory ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509
Sample Description	GW1 - Ground Water collected from Narayana Guru Community Hall, Permude
Sample drawn by	HECS
Date of Sampling	07.10.2020
Qty. of sample received	2 L in HDPE Can + 100 sterile container
Date of sample received	07.10.2020
Date of Analysis start & completion	07.10.2020 & 12.10.2020
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Report Date	13.10.2020
Report No	HECS/W/001/071020

GROUND WATER QUALITY MONITORING RESULTS - OCTOBER 2020

S.No.	Parametersmonitored	Test method followed	Units	Results	IS10500:2012 Permissible Limit
1.	pH (at 25°C)	IS 3025 (Pt -11) 1983	-	7.16	6.5-8.5
2.	Colour	IS 3025 (Pt -4) 1983	Hazen unit	Colourless	15
3,	Turbidity	IS 3025 (Pt -10) 1984	NTU	0.5	5 max
4.	Odour	IS 3025 (Pt -5) 1983	:	Agreeable	Agreeable
5.	Taste	IS 3025 (Pt -8) 1984	-	Agreeable	Agreeable
6.	Total Hardness as CaCoa	IS 3025 (Pt -21) 1983	mg/L	49,1	600 max
7.	Calcium as Ca	IS 3025 (Pt -40) 1991	mg/L	12.1	200 max
8.	Total Alkalinity as CaCO ₃	IS 3025 (Pt -23) 1986	mg/L	43.7	200 max
9.	Chloride as Cl	IS 3025 (Pt -32) 1988	mg/L	12.9	1000 max
10.	Magnesium as Mg	IS 3025 (Pt -46) 1994	. mg/L	4.6	100 max
11.	Total Dissolved Solids	IS 3025 (Pt -16) 1984	mg/L	75.2	2000 max
12.	Sulphate as SO₄	IS 3025 (Pt -24) 1986	mg/L	6.8	400 max
13.	Fluoride	IS 3025 (Pt -60) 2008	mg/L	0.57	1.5 max
14.	Nitrate as NO ₃	ASTM (Pt -31) 1978	mg/L	7.9	45 max
15.	Iron as Fe	IS3025 (Pt -53) 2003	mg/L	0.21	0.3 max
16.	Hexavalent Chromium Cr ⁶⁺	IS3025 (Pt -52) 2003	mg/L	BDL (DL 0.01)	0.05 max
17.	Total coli form Bacteria	IS1622:1981(RA 2009)	MPN/100mL	Absent	Not Detectable
18.	Escherichia coli	IS1622:1981(RA 2009)	Per 100mL	Absent	Not Detectable

Note:-BDL - Below Detection Limit; D.L- Detection Limit; NTU-Nephelometric Turbidity Unit; mg/L - Milligrams per Liter; MPN- Most Probable Number; mL-Milliliter

CONCLUSION: GROUND WATER AS ABOVE PARAMETERS MEETS DRINKING WATER GUIDELINES OF IS 10500: 2012

End of Report

Authorized Enatory (Dr. Oganesan - Latylanager)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization. 2. Samples at a not drawn by HECS unless or otherwise mentioned. 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances tab accepts any liability or loss/damage caused by use or misuse of test report after invoicing or issue of test report. 6. The test results relate only to the test litems. 6.# not under scope of accreditation.

H.O.: #18, 92nd Street, Ashok Nagar, Chennal - 600 083. Ph: 42985555 Fax: 42985500 E-mail: labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)		
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509		
Sample Description	GW2 - Ground Water collected from Gagtel Labour Colony		
Sample drawn by	HECS		
Date of Sampling	07.10.2020		
Qty. of sample received	2 L in HDPE Can + 100 sterile container		
Date of sample received	07.10.2020		
Date of Analysis start & completion	07.10.2020 & 12.10.2020		
Sample Collected by	Hubert Enviro Care Systems (P) Ltd		
Report Date	13.10.2020		
Report No	HECS/W/002/071020		

GROUND WATER QUALITY MONITORING RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	As per IS10500:2012 Permissible Limit
1.	pH (at 25°C)	IS 3025 (Pt -11) 1983	-	7.25	6.5-8.5
2.	Colour	iS 3025 (Pt -4) 1983	Hazen unit	1	15
3.	Turbidity	IS 3025 (Pt -10) 1984	NTU	0.6	5 max
4.	Odour	IS 3025 (Pt -5) 1983	-	Agreeable	Agreeable
<u>5</u> .	Taste	IS 3025 (Pt -8) 1984	-	Agreeable	Agreeable
6.	Total Hardnéss as CaCo ₃	IS 3025 (Pt -21) 1983	mg/L	49.1	600 max
7.	Calcium as Ca	IS 3025 (Pt -40) 1991	mg/L	18.1	200 max
8.	Total Alkalinity as CaCO ₃	IS 3025 (Pt -23) 1986	mg/L	48.0	200 max
9.	Chloride as Cl	IS 3025 (Pt -32) 1988	mg/L	14.8	1000 max
10.	Magnesium as Mg	IS 3025 (Pt -46) 1994	mg/L	BDL (DL 2)	100 max
11.	Total Dissolved Solids	IS 3025 (Pt -16) 1984	mg/L	76	2000 max
12.	Sulphate as SO ₄	IS 3025 (Pt -24) 1986	mg/L	5.6	400 max
13.	Fluoride	IS 3025 (Pt -60) 2008	mg/L	0.74	1.5 max
14.	Nitrate as NO₃	ASTM (Pt -31) 1978	mg/L	7.6	45 max
15.	Iron as Fe	IS3025 (Pt -53) 2003	mg/L	0.21	0.3 max
16.	Hexavalent Chromium Cr6+	IS3025 (Pt -52) 2003	mg/L	BDL (DL 0.01)	0.05 max
17.	Total coli form Bacteria	IS1622 1981 (RA 2009)	MPN/100mL	Absent	Not Detectable
18.	Escherichia coli	IS1622 1981 (RA 2009)	Per 100mL	Absent	Not Detectable

Note:-BDL - Below Detection Limit; D.L- Detection Limit; NTU-Nephelometric Turbidity Unit; mg/L - Milligrams per Liter;
MPN- Most Probable Number; mL-Milliliter

CONCLUSION: GROUND WATER AS ABOVE PARAMETERS MEETS DRINKING WATER GUIDELINES OF IS 10500:2012

End of Report .

Authorized Signatory (Di & Ganesan - Lais Planager)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are not drawn by HECS unless or otherwise mentioned 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances leb accepts any liability or loss / demage caused by use or misuse of test report after involving or issue of test report. 5. The test results relate only to the test items. 6.# not under scope of accreditation.

H.O.: # 18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangatore SEZ, Premude Village, Mangalore – 574509
Sample Description	GW3 - Ground Water collected from L&T New Labour Colony
Sample drawn by	HECS
Date of Sampling	07.10.2020
Qty. of sample received	2 L in HDPE Can + 100 sterile container
Date of sample received	07.10.2020
Date of Analysis start & completion	07.10.2020 & 12.10.2020
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Report Date	13.10.2020
Report No	HECS/W/003/071020

GROUND WATER QUALITY MONITORING RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	As per IS10500:2012 Permissible Limit
1.	pH (at 25°C)	IS 3025 (Pt -11) 1983	-	6.89	6.5-8.5
2.	Colour	IS 3025 (Pt -4) 1983	Hazen unit	1	15
3.	Turbidity	IS 3025 (Pt -10) 1984	NTU	0.7	5 max
4.	Odour	IS 3025 (Pt -5) 1983		Agreeable	Agreeable
5.	Taste	IS 3025 (Pt -8) 1984	_	Agreeable	Agreeable
6.	Total Hardness as CaCo ₃	IS 3025 (Pt -21) 1983	mg/L	52.9	600 max
7.	Calcium as Ca	IS 3025 (Pt -40) 1991	mg/L	12.1	200 max
8.	Total Alkalinity as CaCO ₃	IS 3025 (Pt -23) 1986	mg/L	48.0	200 max
9.	Chloride as Cl	IS 3025 (Pt -32) 1988	mg/L	12.9	1000 max
10.	Magnesium as Mg	IS 3025 (Pt -46) 1994	mg/L	5.5	100 max
11.	Total Dissolved Solids	IS 3025 (Pt -16) 1984	mg/L	78	2000 max
12.	Sulphate as SO ₄	IS 3025 (Pt -24) 1986	mg/L	5.6	400 max
13.	Fluoride	IS 3025 (Pt -60) 2008	mg/L	BDL (DL 0.2)	1.5 max
14.	Nitrate as NO₃	ASTM (Pt -31) 1978	mg/L	7,2	45 max
15.	Iron as Fe	IS3025 (Pt ~53) 2003	mg/L	0.18	0.3 max
16.	Hexavalent Chromium Cr ⁶⁺	IS3025 (Pt -52) 2003	mg/L	BDL (DL 0.01)	0.05 max
17.	Total coli form Bacteria	IS1622:1981(RA 2009)	MPN/100mL	Absent	Not Detectable
18.	Escherichia coli	IS1622:1981(RA 2009)	Per 100ml	Absent	Not Detectable

Note:-BDL - Below Detection Limit; D.L- Detection Limit; NTU-Nephelometric Turbidity Unit; mg/L - Milligrams per Liter; MPN- Most Probable Number; mL-Milliliter

CONCLUSION: GROUND WATER AS ABOVE PARAMETERS MEETS DRINKING WATER GUIDELINES OF IS 10500:2012

End of Report

Authorized/Stanatory (Dr K Garlesan - Lab Dyanager)

^{1.} The report is full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are not drawn by HECS unless or otherwise mentioned 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances lab accepts any liability or loss / damage caused by use or misuse of test report after involving or issue of test report. 5. The test results rejate only to the test items. 6. Final under acopt of accreditation.

H.O.: #18, 92nd Street, Ashok Nagar, Chennal - 600 083. Ph: 42985555 Fax: 42985500 E-mail: labsales@hecs.in

C-45, Industrial Estate, Balkampady, Mangalore, Karnataka - 575011.

Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Blological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)		
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509		
Sample Description	GW4 - Ground Water collected Near OMPL - ETP		
Sample drawn by	HECS		
Date of Sampling	12.10,2020		
Qty. of sample received	2 L in HDPE Can + 100 sterile container		
Date of sample received	12.10.2020		
Date of Analysis start & completion	12.10.2020 & 16.10.2020		
Sample Collected by	Hubert Enviro Care Systems (P) Ltd		
Report Date	17.10.2020		
Report No	HECS/W/004/121020		

GROUND WATER QUALITY MONITORING RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	As per IS10500:2012 Permissible Limit
1.	pH (at 25°C)	IS 3025 (Pt -11) 1983	-	6.72	6.5-8,5
2	Colour	IS 3025 (Pt -4) 1983	Hazen unit	Colourless	15
3.	Turbidity	IS 3025 (Pt -10) 1984	NTU	1.7	5 max
4	Odour	IS 3025 (Pt -5) 1983		Agreeable	Agreeable
5.	Taste	i5 3025 (Pt -8) 1984		Agreeable	Agreeable
6.	Total Hardness as CaCo₃	IS 3025 (Pt -21) 1983	mg/L	41.5	600 max
7.	Calcium as Ca	IS 3025 (Pt -40) 1991	mg/L	10.6	200 max
8.	Total Alkalinity as CaCO ₃	IS 3025 (Pt -23) 1986	mg/L	26.2	200 max
9.	Chloride as Cl	IS 3025 (Pt -32) 1988	mg/L	20.4	1000 max
10.	Magnesium as Mg	IS 3025 (Pt -46) 1994	mg/L	3.6	100 max
11.	Total Dissolved Solids	IS 3025 (Pt -16) 1984	mg/L	58	2000 max
12.	Sulphate as SO ₄	IS 3025 (Pt -24) 1986	mg/L	5.59	400 max
13.	Fluoride	IS 3025 (Pt -60) 2008	mg/L	0.39	1.5 max
14.	Nitrate as NO₃	ASTM (Pt -31) 1978	mg/L	7,5	45 max
1 5.	Iron as Fe	IS3025 (Pt -53) 2003	mg/L	0.05	0.3 max
16.	Hexavalent Chromium Cr ⁶⁺	IS3025 (Pt -52) 2003	mg/L	BDL (DL 0.01)	0.05 max
17.	Total coli form Bacteria	IS1622:1981(RA 2009)	MPN/100mL	Absent	Not Detectable
18.	Escherichia coli	IS1622:1981(RA 2009)	Per 100mL	Abşent	Not Detectable

Note:-BDL - Below Detection Limit; D.L- Detection Limit; NTU-Nephelometric Turbidity Unit; mg/L - Milligrams per Liter; MPN- Most Probable Number; mL-Milliller

CONCLUSION: GROUND WATER AS ABOVE PARAMETERS MEETS DRINKING WATER GUIDELINES OF IS 10500:2012

End of Report



^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization. 2. Samples are not drawn by HECS unless or otherwise mentioned. 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances lab accepts any liability or loss/ damage caused by use or misuse of test report after invoicing or issue of test report. 5. The test results relate only to the test items. 6. #not under acops of accreditation.

H.O.: # 18, 92nd Street, Ashok Nagar, Chennal - 600 083. Ph: 42985555 Fax: 42985500 E-mail: labsales@hecs.in

C-45, industrial Estate, Balkampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509
Sample Description	OW1- Open Well Water collected from TenkaEkkar
Sample drawn by	HECS
Date of Sampling	07.10.2020
Qty. of sample received	2 L in HDPE Can + 100 sterile container
Date of sample received	07.10.2020
Date of Analysis start & completion	07.10.2020 & 12:10.2020
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Report Date	13.10.2020
Report No	HECS/W/005/071020

OPEN WELL WATER QUALITY MONITORING RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	As per IS10500:2012 Permissible Limit
1.	pH (at 25°C)	IS 3025 (Pt -11) 1983	-	6.74	6.5-8.5
2.	Colour	IS 3025 (Pt -4) 1983	Hazen unit	Colourless	15
3.	Turbidity	IS 3025 (Pt -10) 1984	NTU	BDL (DL 0.1)	5 max
4.	Odour	IS 3025 (Pt -5) 1983		Agreeable	Agreeable
5.	Taste	IS 3025 (Pt -8) 1984	-	Agreeable	Agreeable
6.	Total Hardness as CaCo ₃	IS 3025 (Pt -21) 1983	mg/L	18.9	600 max
7,	Calcium as Ca	IS 3025 (Pt -40) 1991	mg/L	3.0	200 max
8.	Total Alkalinity as CaCO ₃	IS 3025 (Pt -23) 1986	mg/L	13.1	200 max
9.	Chloride as Cl	IS 3025 (Pt -32) 1988	mg/L	11.1	1000 max
10.	Magnesium as Mg	IS 3025 (Pt -46) 1994	mg/L	2.7	100 max
11,	Total Dissolved Solids	IS 3025 (Pt -16) 1984	mg/L	34	2000 max
12.	Sulphate as SO ₄	IS 3025 (Pt -24) 1986	mg/L	BDL (DL 5)	400 max
13.	Fluoride	IS 3025 (Pt -60) 2008	mg/L	0.49	1.5 max
14.	Nitrate as NO ₃	ASTM (Pt -31) 1978	mg/L	5.7	45 max
15.	Iron as Fe	IS3025 (Pt -53) 2003	mg/L	0.11	0.3 max
16.	Hexavalent Chromium Cr ⁶⁺	IS3025 (Pt -52) 2003	mg/L	BDL (DL 0.01)	0.05 max
17.	Total coli form Bacteria	IS1622:1981(RA 2009)	MPN/100mL	Absent	Not Detectable
18.	Escherichia coli	IS1622:1981(RA 2009)	Per 100mL	Absent	Not Detectable

Note:-BDL - Below Detection Limit; D.L- Detection Limit; NTU-Nephelometric Turbidity Unit; mg/L - Milligrams per Liter;
MPN- Most Probable Number; mL-Milliliter

CONCLUSION: OPENWELL WATER AS ABOVE PARAMETERS MEETS DRINKING WATER GUIDELINES OF IS 10500:2012

End of Report

Authorized Signatory (Dr.K.-Ganesan - Lab Manager)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization: 2. Samples are not drawn by HECS unless or otherwise mentioned: 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no dircumstances lab accepts any liability or loss / damage caused by use or misuse of test report after invalcing or issue of test report. 5. The test results relate only to the test items. 6.# not under scope of accreditation.

H.O.: # 18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax : 42985500 E-mall : labsales@hecs.in

C-45, Industrial Estate, Balkampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the industry	Mangalore SEZ, Premude Village, Mangalore - 574509
Sample Description	OW2 - Open Well Water collected from Shantigudda Village
Sample drawn by	HECS
Date of Sampling	07.10.2020
Qty. of sample received	2 L in HDPE Can + 100 sterile container
Date of sample received	07.10.2020
Date of Analysis start & completion	07.10.2020 & 12.10.2020
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Report Date	13.10.2020
Report No	HECS/W/006/071020

OPEN WELL WATER QUALITY MONITORING RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	As per IS10500:2012 Permissible Limit
1.	pH (at 25°C)	IS 3025 (Pt -11) 1983	-	6.80	6.5-8.5
2.	Colour	IS 3025 (Pt -4) 1983	Hazen unit	Colourless	15
3	Turbidity	IS 3025 (Pt -10) 1984	NTU	BDL (DL 0.1)	5 max
4.	Odour	IS 3025 (Pt -5) 1983	-	Agreeable	Agreeable
5.	⊤aste	IS 3025 (Pt -8) 1984	-	Agreeable	Agreeable
6.	Total Hardness as CaCo ₃	IS 3025 (Pt -21) 1983	mg/L	34.0	600 max
7.	Calcium as Ca	IS 3025 (Pt -40) 1991	mg/L	13.6	200 max
8.	Total Alkalinity as CaCO ₃	IS 3025 (Pt -23) 1986	mg/L	30.5	200 max
9.	Chloride as Cl	IS 3025 (Pt -32) 1988	mg/L	20.4	1000 max
10.	Magnesium as Mg	IS 3025 (Pt -46) 1994	mg/L	BDL (DL 2)	100 max
11.	Total Dissolved Solids	IS 3025 (Pt -16) 1984	mg/L	72	2000 max
12.	Sulphate as SO ₄	IS 3025 (Pt -24) 1986	mg/L	8DL (DL 5)	400 max
13.	Fluoride	IS 3025 (Pt -60) 2008	mg/L	0.39	1.5 max
14.	Nitrate as NO ₃	ASTM (Pt -31) 1978	mg/L	6.8	45 max
15.	Iron as Fe	IS3025 (Pt -53) 2003	mg/L	0.2	0.3 max
16,	Hexavalent Chromium Cr ⁶⁺	IS3025 (Pt -52) 2003	mg/L	BDL (DL 0.01)	0.05 max
17.	Total coli form Bacteria	IS1622:1981(RA 2009)	MPN/100mL	Absent	Not Detectable
18.	Escherichia cali	IS1622:1981(RA 2009)	Per 100mL	Absent	Not Detectable

Note:-BDL - Below Detection Limit; D.L- Detection Limit; NTU-Nephelometric Turbidity Unit; mg/L - Milligrams per Liter; MPN- Most Probable Number; mi-Milliliter

CONCLUSION: OPENWELL WATER AS ABOVE PARAMETERS MEETS DRINKING WATER GUIDELINES OF IS 10500:2012

End of Report

(Dr K danesan - Lab Marager)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization. 2. Samples are not drawn by HECS unless or otherwise mentioned. 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of lesue of test report. 4. Under no circumstances in accepts any Hability or loss / damage caused by use or misuse of test report after invoicing or issue of test report, 5. The test results relate only to the test items. 6.# not under scope of accreditation.

H.O.; # 18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore – 574509
Sample Description	OW3 - Open Well Water collected from Permude Village
Sample drawn by	HECS
Date of Sampling	07.10.2020
Qty. of sample received	2 L in HDPE Can + 100 sterile container
Date of sample received	07.10.2020
Date of Analysis start & completion	07.10.2020 & 12.10.2020
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Report Date	13.10.2020
Report No	HECS/W/007/071020

OPEN WELL WATER QUALITY MONITORING RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	As per IS10500:2012 Permissible Limit
1.	pH (at 25°C)	IS 3025 (Pt -11) 1983	-	6.78	6.5-8.5
2.	Colour	IS 3025 (Pt -4) 1983	Hazen unit	1	15
3.	Turbidity	IS 3025 (Pt -10) 1984	NŢŲ	BDL (DL 0.1)	5 max
4.	Odour	IS 3025 (Pt -5) 1983	_	Agreeable	Agreeable
5.	Taste	IS 3025 (Pt -8) 1984		Agreeable	Agreeable
6.	Total Hardness as CaCo ₃	IS 3025 (Pt -21) 1983	mg/L	37.8	600 max
7.	Calcium as Ca	iS 3025 (Pt -40) 1991	mg/L	10.6	200 max
8.	Total Alkalinity as CaCO ₃	IS 3025 (Pt -23) 1986	mg/L	34.9	200 max
9.	Chloride as Cl	IS 3025 (Pt -32) 1988	mg/L	20.4	1000 max
10.	Magnesium as Mg	IS 3025 (Pt -46) 1994	mg/L	2.7	100 max
11.	Total Dissolved Solids	IS 3025 (Pt -16) 1984	mg/L	75.2	2000 max
12,	Sulphate as SO ₄	IS 3025 (Pt -24) 1986	mg/L	BDL (DL 5)	400 max
13.	Fluoride	IS 3025 (Pt -60) 2008	mg/L	0.49	1.5 max
14.	Nitrate as NO₃	ASTM (Pt -31) 1978	mg/L	7.5	45 max
15.	iron as Fe	IS3025 (Pt -53) 2003	mg/L	0.1	. 0.3 max
16.	Hexavalent Chromium Cr ⁶⁺	IS3025 (Pt -52) 2003	mg/L	BDL (DL 0.01)	0.05 max
17.	Total coli form Bacteria	IS1622:1981(RA 2009)	MPN/100mL	Absent	Not Detectable
18.	Escherichia coli	IS1622:1981(RA 2009)	Per 100mL	Absent	Not Detectable

Note:-BDL - Below Detection Limit; D.L- Detection Limit; NTU-Nephelometric Turbidity Unit; mg/L - Milligrams per Liter; MPN- Most Probable Number; mL-Milliliter

CONCLUSION: OPENWELL WATER AS ABOVE PARAMETERS MEETS DRINKING WATER GUIDELINES OF IS 10500:2012

End of Report



^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are not drawn by HECS unless or otherwise mentioned 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances lab accepts any liability or loss / damage caused by use or misuse of test report after invoicing or issue of test report. 5. The test results relate only to the test items. 6.#not under scape of accreditation.

H.O.: #18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax: 42985500 E-mall: labsales@necs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)	
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509	
Sample Description	SW1 - Surface Water collected Near OMPL - Flare Area	
Sample drawn by	HECS	=
Date of Sampling	12.10.2020	
Qty. of sample received	2 L in HDPE Can + 100 sterile container	
Date of sample received	12.10.2020	
Date of Analysis start & completion	12.10.2020 & 16.10.2020	\dashv
Sample Collected by	Hubert Enviro Care Systems (P) Ltd	
Report Date	17.10.2020	-
Report No	HECS/W/008/121020	

SURFACE WATER QUALITY MONITORING RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	As per IS10500:2012 Permissible Limit
1.	pH (at 25°C)	IS 3025 (Pt -11) 1983	-	6.92	6.5-8.5
2,	Colour	IS 3025 (Pt -4) 1983	Hazen unit	Colourless	15
3.	Turbidity	IS 3025 (Pt -10) 1984	NTU	3.0	5 max
4.	Odour -	IS 3025 (Pt -5) 1983	-	Agreeable	Agreeable
5.	Taste	IS 3025 (Pt -8) 1984	-	Agreeable	Agreeable
6.	Total Hardness as Ca CO ₃	IS 3025 (Pt -21) 1983	mg/L	37.8	600 max
7.	Calcium as Ca	IS 3025 (Pt -40) 1991	mg/L	13.6	200 max
8.	Total Alkalinity as CaCO ₃	IS 3025 (Pt -23) 1986	mg/L	21.8	200 max
9.	Chloride as Cl	IS 3025 (Pt -32) 1988	mg/L	12.9	1000 max
10.	Magnesium as Mg	IS 3025 (Pt -46) 1994	mg/L	BDL (DL 2)	100 max
11.	Total Dissolved Solids	IS 3025 (Pt -16) 1984	mg/L	71.2	2000 max
12.	Sulphate as SO ₄	IS 3025 (Pt -24) 1986	mg/L	37.6	400 max
13.	Fluoride	IS 3025 (Pt -60) 2008	mg/L	0.35	1.5 max
14.	Nitrate as NO₃	ASTM (Pt -31) 1978	mg/L	6.4	45 max
15.	Iron as Fe	IS3025 (Pt -53) 2003	mg/L	0.06	0.3 max
16.	Hexavalent Chromium Cr ⁵⁺	IS3025 (Pt -52) 2003	mg/L	BDL (DL 0.01)	0.05 max
17.	Total coli form Bacteria	S1622:1981(R.aff 2009)	MPN/100mL	Absent	Not Detectable
18.	Escherichia coli	IS1622:1981(R.aff 2009)	Per 100mt.	Absent	Not Detectable

Note:-BDL - Below Detection Limit; D.L- Detection Limit; NTU-NephelometricTurbidity Unit; mg/L - Milligrams per liter; NA-Not Available

CONCLUSION: SURFACE WATER AS ABOVE PARAMETERS MEETS DRINKING WATER GUIDELINES OF IS 10500:2012

End of Report

Authorized signatory (Dr K Sanesan - Late Manager)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization. 2. Samples are not drawn by HECS unless or otherwise mentioned. 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances lab accepts any liability or loss / damage caused by use or misuse of test report after invoicing or issue of test report. 5. The test results relate only to the test items. 6.8 not under scope of accreditation.

H.O.: # 18, 92nd Street, Ashok Nagar, Chennal - 600 083. Ph: 42985555 Fax: 42985500 E-mail: labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)			
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore – 574509			
Sample Description	SW2 - Surface Water collected Near OMPL - Near Central Warehouse			
Sample drawn by	HECS			
Date of Sampling	12.10.2020			
Qty. of sample received	2 L in HDPE Can + 100 sterile container			
Date of sample received	12.10.2020			
Date of Analysis start & completion	12.10.2020 & 16.10.2020			
Sample Collected by	Hubert Enviro Care Systems (P) Ltd			
Report Date	17.10.2020			
Report No	HECS/W/009/121020			

SURFACE WATER QUALITY MONITORING RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	As per IS10500:2012 Permissible Limit
1.	pH (at 25°C)	IS 3025 (Pt -11) 1983	-	6.81	6.5-8.5
2.	Colour	IS 3025 (Pt -4) 1983	Hazen unit	Colourless	15
3.	Turbidity	IS 3025 (Pt -10) 1984	NTU	3.5	5 max
4.	Odour	IS 3025 (Pt -5) 1983		Agreeable	Agreeable
5.	Taste	IS 3025 (Pt -8) 1984	-	Agreeable	Agreeable
6.	Total Hardness as CaCo ₃	IS 3025 (Pt -21) 1983	mg/L	45.3	600 max
7.	Calcium as Ca	IS 3025 (Pt -40) 1991	mg/L	13.6	200 max
8.	Total Alkalinity as CaCO ₃	IS 3025 (Pt -23) 1986	mg/L	17.4	200 max
9.	Chloride as Cl	IS 3025 (Pt -32) 1988	mg/L	14,8	1000 max
10.	Magnesium as Mg	IS 3025 (Pt -46) 1994	mg/L	2.7	100 max
11.	Total Dissolved Solids	IS 3025 (Pt -16) 1984	mg/L	71,2	2000 max
12.	Sulphate as SO ₄	IS 3025 (Pt -24) 1986	mg/L	27.6	400 max
13.	Fluoride	IS 3025 (Pt -60) 2008	mg/L	0.45	1.5 max
14.	Nitrate as NO ₃	ASTM (Pt -31) 1978	mg/L	7.1	45 max
15.	Iron as Fe	IS3025 (Pt -53) 2003	mg/L	0.091	0.3 max
16.	Hexavalent Chromium Cr ⁶⁺	IS3025 (Pt -52) 2003	mg/L	BDL (DL 0.01)	0.05 max
17.	Total coli form Bacteria	IS1622:1981(RA 2009)	MPN/100mL	Absent	Not Detectable
18.	Escherichia coli	IS1622:1981(RA 2009)	Per 100mL	Absent	Not Detectable

Note:-BDL - Below Detection Limit; D.L- Detection Limit; NTU-Nephelometric Turbidity Unit; mg/L - Milligrams per liter

CONCLUSION: SURFACE WATER AS ABOVE PARAMETERS MEETS DRINKING WATER GUIDELINES OF IS 10500:2012

End of Report

Authorizeta gnatory
(Dr Kanesan - Lab Manager)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are not drawn by HECS unless or otherwise manifoned 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances jab accepts any items of test report after invoicing or issue of test report. 5. The test results relate only to the test items, 6.# not under acops of accreditation.

MNNDAURE- C

Hubert Enviro Care Systems (P) Ltd.

H.O.: # 18, 92nd Street, Ashok Nagar, Chennal - 600 083. Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Balkampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in

Laboratory Services Division (Chemical & Biological Testing) Recognized by MoEF, BIS FSSAI Notified Laboratory ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)		
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509		
Sample Description	Noise Monitoring		
Sample Collected by	Hubert Enviro Care Systems (P) Ltd		
Sampling Location	OMPL - North, South, East and West sides		
Sampling Date	09.10.2020		
Report Date	15,10,2020		
Report No.	HECS/N/001/091020		

NOISE MONITORING - OCTOBER 2020 RESULTS

S.No.	Campuling Lagration	MoEFCC requirements in dB		Avg. Noise level observed in dB		
	Sampling Location	Day	Nìght	Day	Night	
1.	OMPL-North			69.7	58.3	
2.	OMPL-South] .		67.5	57.7	
3.	OMPL-East	75	70	69.2	58.6	
4.	OMPL-West		Ī	68.4	58.8	

Note: dB: Decibel

Limits: Industrial Area: Day Time -75 dB (A), Night Time -70 dB (A). Commercial Area: Day Time-65 dB (A), Night Time-55 dB (A), Residential Area: Day Time-55 dB (A), Night Time-45 dB (A). Silence Zone: Day Time-50 dB (A), Night Time-40 dB (A).

Note: Leq- Equivalent Noise Level (hourly); Reference: The Noise Pollution (Regulation and Control) Rules, 2000, CPCB, New Delhi

INFERENCE: The observed noise levels are within the limits as per The Noise Pollution (Regulation and Control) Rules, 2000 under the Environment (Protection) Act, 1986

*****End of Report *****



^{1.} The report in tall or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are not drawn by HECS unless or otherwise mentioned 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no obcumulances lab accepts any liability or loss / damage caused by use or misuse of test report after invoicing or issue of test report. 5. The test results relate only to the test items. 6.8 not under scope of accreditation.

H.O.: # 18, 92nd Street, Ashok Nagar, Chennal - 600 083. Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

TEST REPORT

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509
Sample Description	Guard Pond Pump Discharge (ETP Effluent)
Sample drawn by	HECS
Date of Sampling	12.10.2020
Qty. of sample received	2 L in HDPE Can + 1 L amber glass bottle
Date of sample received	12.10.2020
Date of Analysis start & completion	12.10.2020 & 19.10.2020
Sample Collected by	Hubert Enviro Care Systems (P) Ltd
Report Date	20.10.2020
Report No	HECS/WW/006/121020

ETP EFFLUENT WATER RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	Permissible Limit
1.	Colour	IS 3025 (Pt 4)1983(RA 2006)	Hazen Units	3	All efforts should be made to remove
2.	Odour	IS 3025 (Pt 5)-1983,RA 2006		Agreeable	colour and unpleasant odour as far as practicable
3,	Total Suspended Solids	2540D APHA 23 rd Edn 2012	mg/L	5.2	100
4.	Нα	IS 3025 (Pt 11):1983(RA 2006)	-	6.65	6.0-8.5
5.	Temperature	IS 3025 (Pt 9):1983(RA:2006)	°C	29	Shall not exceed 5 degree Centigrade above the receiving water temperature
6.	Oil & Grease	IS 3025,4(Pt 39):2000 (RA 2009)	mg/L	2.2	5
7.	Total Residual Chlorine as Cl ₂	IS 3025 (Pt26)1986(RA 2009)	mg/L	BDL (DL 0.1)	1
8.	Ammonical Nitrogen as N	IS 3025 Pt (34)1988	mg/L	7.5	50
9.	Total Kjeldhal Nitrogen as N	IS 3025 Pt (34)1988	mg/L	26.2	100
10.	Free Ammonia as NH₃	IS 3025 (Pt 34)1998 RA, 2003	mg/L	BDL (DL 0.02)	5
11.	BOD, 3 days @ 27°C as O ₂	IS 3025 (Pt 44)1993(RA 2009)	mg/L	BDL (DL 2)	30
12.	COD as O ₂	IS 3025 Pt (58)2006	mg/L	7.32	125
13.	Lead as Pb	IS 3025 (Pt 47)1994(RA 2009)	mg/L	BDL (DL 0.1)	0.1
14.	Chromium (Hexavalent) as Cr ⁶⁺	IS 3025 Pt (52):2003	mg/L	BDL (DL 0.01)	0.1
15.	Total Chromium as Cr	IS 3025(Pt52):2003 (RA 2009)	mg/L	BDL (DL 0.01)	2.0
16.	Copper as Cu	IS 3025 5,(Pt 42)1992(RA 2009)	mg/L	BDL (DL 0.05)	1.0
17.	Zinc as Zn	IS 3025 (Pt 49)1994(RA 2009)	mg/L	BDL (DL 0.1)	5.0



^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization. 2. Samples are not drawn by HECS unless or otherwise mentioned. 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances lab accepts any liability or loss? damage caused by use or misuse of test report after invoicing or issue of test report. 5. The test results relate only to the test items. 6. # not under scope of accreditation.

H.O.: # 18, 92nd Street, Ashok Nagar, Chennai - 600 083, Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0924 - 2408111, Email: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by McEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 16001 Certified.

Certificate No. TC-5786

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore – 574509
Sample Description	Guard Pond Pump Discharge (ETP Effluent)
Sample drawn by	HECS
Date of Sampling	12.10.2020
Qty. of sample received	2 L in HDPE Can + 1 L amber glass bottle
Date of sample received	12.10.2020
Date of Analysis start & completion	12.10.2020 & 19.10.2020
Sample Collected bý	Hubert Enviro Care Systems (P) Ltd
Report Date	20.10.2020
Report No	HECS/WW/006/121020

ETP EFFLUENT WATER RESULTS - OCTOBER 2020

S.No.	Parameters Monitored .	Test method followed	Units	Results	Permissible Limit
18,	Nickel as Ni	IS 3025 (Pt 54)2003 (RA 2009)	mg/L	BDL (DL 0.05)	1.0
19.	Fluoride as F-	IS 3025 Pt (60):2008	mg/L	8DL (DL 0.2)	1.0
20.	Sulphide as S ²⁻	IS 3025 (Pt 29)1986 (RA 2009)	mg/L	BDL (DL 0.04)	2.0
21.	Particle Size of Suspended Solids	APHA 23 rd Edition	-	Passed through 850 micron	850 micron
22.	Arsenic as As	IS 3025 (Pt 37)1988(RA 2009)	mg/L	BDL (DL 0.005)	0.2
23.	Mercury as Hg	IS 3025 (Pt 48)1994 RA 1999	mg/L	8DL (DL 0.001)	0.01
24.	Cadmium as Cd	IS 3025 (Pt 41)1991	mg/L	BDL (DL 0.01)	0.1
25.	Selenium as Se	IS 3025 (Pt 56)2003	mg/L	BDL (DL 0.005)	0.05
26	Cyanide as CN	IS 3025 (Pt 27)1986 RA. 2009	mg/L	BDL (DL 0.01)	0,2
27.	Phenols as C6H5OH	IS 3025 Pt (43)1992,RA 2009	mg/L	BDL (DL 0.001)	0.35
28.	Total Iron as Fe	IS 3025(Pt 53):2003(RA 2009)	mg/L	0.21	3
29.	Manganese	IS 3025 (Pt-59):2006	mg/L	BDL (DL 0.01)	2
30.	Total Phosphorous as P	IS 3025(Pt 31):1988(RA 2009)	mg/L	BDL (DL 0.01)	3
31.	Nitrate	IS 3025 (Pt 34):1988 (RA 2009)	mg/L	BDL (DL 1)	20
32.	Vanadium as V	IS 3025 (Pt 56)2003	mg/L	BDL (DL 0.01)	0.1
33,	Benzo(a)pyrene	USEPA 8270C	mg/L	BDL (DL 0.0001)	0.2
34.	Benzene	USEPA 8270C	mg/L	BDL (DL 0.0001)	0.1
35.	Bioassay Test	IS 6582(Pt 2):2001	Tf	9:1	90% survival of fish after 96 hrs in 100% effluen

Note:-BDL - Below Detection Limit; D.L- Detection Limit; mg/L - Milligrams per liter

CONCLUSION: ETP OUTLET EFFULENTWATER AS ABOVE PARAMETERSARE WITHIN STANDARDS

End of Report

Authorized Signatory (Dr K Bahesan - Lab Namager)

^{1.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are not drawn by HECS unless or otherwise mentioned 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances lab accepts any itability or loss / damage caused by use or misuse of test report after invoicing or issue of test report. 5. The test results relate only to the test items. 5. #not under scope of accreditation.

H.O.: #18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax: 42985500 E-mail: labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Emzil: kro@hecs.in, Website: www.hecs.in



Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)		
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore - 574509		
Sample Description	Guard Pond Pump Discharge (ETP Effluent)		
Sample drawn by	HECS		
Date of Sampling	23.10.2020		
Qty. of sample received	5 Lin HDPE Can + 1 Lamber glass bottle		
Date of sample received	23.10.2020		
Date of Analysis start & completion	23.10.2020 & 30.10.2020		
Sample Collected by	Hubert Enviro Care Systems (P) Ltd		
Report Date	02.11.2020		
Report No	HECS/WW/002/231020		

GUARD POND PUMP DISCHARGE (ETP EFFLUENT) RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	Permissible Limit
1.	Colour	IS 3025 (Pt 4)1983(RA 2006)	Hazen Units	3	All efforts should be made to remove
2.	Odour	IS 3025 (Pt 5)-1983,RA 2006	- -	Agreeable	colour and unpleasant odour as far as practicable
3.	Total Suspended Solids	2540D APHA 23 rd Edn., 2012	mg/L	BDL (DL 4)	100
4.	ρH	IS 3025 (Pt 11):1983(RA 2006)		7.02	6.0-8.5
5.	Temperature	IS 3025 (Pt 9):1983(RA:2006)	°C .	29	Shall not exceed 5 degree Centigrade above the receiving water temperature
6.	Oil & Grease	IS 3025,4(Pt 39):2000 (RA 2009)	mg/L	BDL (DL 2)	5
7.	Total Residual Chlorine as Cl ₂	IS 3025 (Pt26)1986(RA 2009)	mg/L	BDL (DL 0.1)	1
8.	Ammonical Nitrogen as N	IS 3025 Pt (34)1988	mg/L	5.7	50
9.	Total Kjeldhal Nitrogen as N	IS 3025 Pt (34)1988	mg/L	21.7	100
10.	Free Ammonia as NH ₃	IS 3025 (Pt 34)1998 RA. 2003	mg/L	BDL (DL 0.02)	. 5
	BOD, 3 days @ 27°C as O₂	IS 3025 (Pt 44)1993(RA 2009)	mg/L	2.5	30
	COD as O ₂	IS 3025 Pt (58)2006	mg/L	15,4	125
	Lead as Pb	IS 3025 (Pt 47)1994(RA 2009)	mg/L	BDL (DL 0.1)	0.1
14.	Chromium (Hexavalent) as Cr ⁶⁺	IS 3025 Pt (52):2003	mg/L	BDL (DL 0.01)	0.1
1 5.	Total Chromium as Cr	IS 3025 (Pt52):2003 (RA 2009)	mg/L	BDL (DL 0.01)	2.0
	Copper as Cu	IS 3025 5,(Pt 42)1992(RA 2009)	mg/L	BDL (DL 0.05)	1.0
17.	Zinc as Zn	IS 3025 (Pt 49)1994(RA 2009)	mg/L	BDL (DL 0.1)	5.0



The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are not drawn by HECS unless or etherwise
mentioned 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstations lab accepts any
liability or loss / damage caused by use or misuse of test report after invoicing or issue of test report. 5. The test results relationity to the test items. 6.8 not under accept of accreditation.

H.O.: #18, 92nd Street, Ashok Nagar, Chennai - 600 083. Ph: 42985555 Fax : 42985500 E-mail : labsales@hecs.in

C-45, Industrial Estate, Baikampady, Mangalore, Karnataka - 575011. Ph: 0824 - 2408111, Email: kro@hecs.in, Website: www.hecs.in

Laboratory Services Division

(Chemical & Biological Testing)
Recognized by MoEF, BIS
FSSAI Notified Laboratory
ISO 9001, 14001 & OHSAS 18001 Certified.

Certificate No. TC-5786

Name of the Industry	M/s. ONGC Mangalore Petrochemicals Limited (OMPL)			
Address of the Industry	Mangalore SEZ, Premude Village, Mangalore – 574509			
Sample Description	Guard Pond Pump Discharge (ETP Effluent)			
Sample drawn by	HECS			
Date of Sampling	23.10.2020			
Qty. of sample received	5 L in HDPE Can + 1 L amber glass bottle			
Date of sample received	23.10.2020			
Date of Analysis start & completion	23.10.2020 & 30.10.2020			
Sample Collected by	Hubert Enviro Care Systems (P) Ltd			
Report Date .	02.11.2020			
Report No	HECS/WW/002/231020			

ETP EFFLUENT WATER RESULTS - OCTOBER 2020

S.No.	Parameters monitored	Test method followed	Units	Results	Permissible Limit	
18.	Nickel as Ni	IS 3025 (Pt 54)2003 (RA 2009)	mg/L	BDL (DL 0.05)	1.0	
19.	Fluoride as F-	IS 3025 Pt (60):2008	mg/L	BDL (DL 0.2)	1.0	
20.	Sulphide as S ²⁻	IS 3025 (Pt 29)1986 (RA 2009)	mg/L	BDL (DL 0.04)	2.0	
21.	Particle Size of Suspended solids	APHA 23 rd Edition	-	Passed through 850 micron	850 micron	
22,	Arsenic as As	IS 3025 (Pt 37)1988(RA 2009)	mg/L	BDL (DL 0.005)	0.2	
23.	Mercury as Hg	IS 3025 (Pt 48)1994 RA 1999	mg/L	BDL (DL 0.001)	0.01	
24.	Cadmium as Cd	IS 3025 (Pt 41)1991	mg/L	BDL (DL 0.01)	0.1	
25.	Selenium as Se	IS 3025 (Pt 56)2003	mg/L	BDL (DL 0.005)	0.05	
26	Cyanide as CN	IS 3025 (Pt 27)1986 RA. 2009	mg/L	8DL (DL 0.01)	0.2	
27.	Phenols as C6H5OH	IS 3025 Pt (43)1992,RA 2009	mg/L	BDL (DL 0.001)	0.35	
28.	Total Iron as Fe	IS 3025 (Pt 53):2003(RA 2009)	mg/L	0.21	3	
29.	Manganese	IS 3025 (Pt-59):2006	mg/L	8DL (DL 0.01)	2	
30.	Total Phosphorous as P	IS 3025 (Pt 31):1988(RA 2009)	mg/L	BDL (Dt. 0.01)	3	
31,	Nitrate	IS 3025 (Pt 34):1988 (RA 2009)	mg/L	BDL (DL 1)	20	
32.	Vanadium as V	IS 3025 (Pt 56)2003	mg/L	BDL (DL 0.01)	0.1	
33.	Benzo(a)pyrene	USEPA 8270C	mg/L	BDL (DL 0,0001)	0,2	
34.	Benzene	USEPA 8270C	mg/L	BDL (DL 0.0001)	0.1	
25	Biogram Took	IC CEC2/04 23-2004	T.f		90% survival of	
35.	Bioassay Test	IS 6582(Pt 2):2001	Tf	9:1	fish after 96 hrs in 100% effluent	

Note:-BDL - Below Detection Limit; D.L- Detection Limit; mg/L - Milligrams per liter

CONCLUSION: ETP OUTLET EFFULENTWATER AS ABOVE PARAMETERSARE WITHIN STANDARDS

End of Report

Authorized gnatory
Dr. K. Ganesan - Landylanager)

^{2.} The report in full or part shall not be used for any promotional or publicity purpose without written consent by HECS organization 2. Samples are not trawn by HECS unless or otherwise mentioned 3. Unless specifically requested by customer the test items will not be retained more than 15 days from the date of issue of test report. 4. Under no circumstances lab accepts any liability or loss/damage caused by use or misuse of test report after invoicing or issue of test report. 5. The test results relate only to the test items. 6. #not under scope of accreditation.

Form-1 (Rule 4)
Consumed during the M

	Name and address of the Consul Purpose for which water consumed				M/s ONGC Mangalore Petrochemicals Limited,	Mangafore Special Economic	Zone, Permude, Mangalore -574	609					Total Co
Returns Regarding Water Consumed during the Month of October, 2020	Purpose for which water consumed	Industrial cooling, spraying in mine pits or boller feed	Cooling Water	Boiler Feed Water	1	Fire Water		Drinking Water & Sanitation	Processing whereby water gets	polluted and the pollutants are	easily bio-degradable	Service Water	Total Consumption
r Consumed during the	Reading at the beginning of the first day of the calendar calendar month under report		0	0		0		0				0	
e Montin of October	Reading at the end of the last day of the calendar month under report		14647	50304		25292		5/05				4708	
ZUZU	Quantity of Water Consumed in Kilo Leters		14647	50304	-	25292		5075				4708	1,00,026
	If the meter was out of order, the monthly average consumption of water for water qualifying the previous 3 months of for rebate the working period the assessee								i				THE REPORT OF THE PERSON OF TH
	Quantity of water qualifying for rebate according to the assessee												
	Remarks												

Signature of the Consumer

Nаme

Address

Shivaprakash, Sr. Manager(Env)

M/s ONGC Mangalore Petrochemicals Limited, Mangalore Special Economic Zone, Permude, Mangalore -574 509

YNNEKURE- H.

ONGC Mangalore Petrochemicals Limited

Production Details for October, 2020

Net Naptha Processed -36,512 MT

Si. No.	Name of the Product	Quantity, 'M3
1	Paraxylene (Product)	22,385
2	Benzene (Co product)	6,986
	.	

Richt